

COPY

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.
Coal Operator or Owner
1 BRIDGE ST. MONONGAH WV 26582
Address

CONSOLIDATION COAL CO.
Coal Operator or Owner
1 BRIDGE ST. MONONGAH WV 26582
Address

SPORTSMANS SQUARE CIRCLE
Lease or Property Owner
129 CIRCLE DR. FAIRMONT, WV 26554
Address

CONSOLIDATION COAL CO.
Name of Well Operator
1 BRIDGE ST. MONONGAH, WV 26582
Complete Address

GLOVER GAP 7.5'
Well Location

MANNINGTON
District

MARION
County

5079
Well No.

SPORTSMANS SQUARE CIRCLE
Farm

STATE INSPECTOR SUPERVISING PLUGGING *[Signature]*

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

MIKE MITCHELL and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 12th day of July, 2011 and that the well was plugged in the following manner:

Sand or Zone Record Formation	Filling Material	Plugs Used Size & Kind	Casing Pulled	Casing Left In
Removed sucker rods from the surface to 3062'. Removed 2 3/8" tubing from the surface to 3075'. Removed 5 1/2" casing from the surface to 2484'. Left 224' of 5 1/2" casing in the hole from 2484' to 2708'. Cemented bottom hole from 3080' back to 2231' with 105 sacks of 35/65 Poz Mix cement. Removed 7" casing from the surface to 1443'. Left 866' of 7" casing in the hole from 1443' to 2309'. Cut remaining 7" casing at the following depths; 2209', 2109', 2009', 1909', 1809', 1714', 1609' and 1533'. Cleaned 12 1/4" hole from the surface to 312'. Cleaned 9 7/8" hole from 312' to 1261'. Cleaned 7 7/8" hole from 1261' to 1448'. Cleaned 6 1/4" hole from 1443' back to top of bottom hole plug at 2231'. Cleaned 9 7/8" through Pittsburgh Coal (1035' - 1042'). Left 8' of 20" conductor pipe in the hole from 8' to surface. Cement hole from 3080' back to surface as follows. From 3080' to 2231' with 105 sacks of 35/65 Poz Mix cement. From 2231' 2231 to 1242' with 185 sacks of 35/65 Poz Mix cement. From 1242' to 935' with 165 sacks of Thixotropic cement with dye. From 935' to surface with 345 sacks of Econofill cement. A total of 800 sacks of cement were used to fill the hole from 3080' to surface. Cement did circulate at the surface.	20" Conductor	0'	8'	
	7" Casing	1443'	866'	
	5 1/2" Casing	2484'	224'	
	2 3/8" Tubing	3075'	0'	
	Sucker Rods	3062	0'	
Coal Seams		Description of Monument		
<u>PITTSBURGH</u>	<u>1035' to 1042'</u>	77" of 7" casing w/company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to the cement plug at ground level.		
(Name)				
(Name)				
(Name)				

RECEIVED
Office of Oil & Gas
OCT 17 2011
WV Department of Environmental Protection

... and that the work of plugging and filling said well was completed on the 3rd day of August, 2011

And further deponents saith not.

[Signature]
Mike Mitchell

[Signature]
Kevin S. Wright

Sworn to and subscribed before me this 19th day of September, 2011

[Signature]
Notary Public

My commission expires:
June 1, 2015

NOTARIAL SEAL
JACQUELINE L SHRIVER
Notary Public
DUNKARD TWP, GREENE COUNTY
My Commission Expires Jun 1, 2015

Permit No. 47-49-00546-P
Well No. 5079