

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL COMPANY
Coal Operator or Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address

CONSOLIDATION COAL COMPANY
Coal Operator or Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address

CONSOLIDATION COAL COMPANY
Lease or Property Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address

CONSOLIDATION COAL CO.
Name of Well Operator
1 BRIDGE STREET MONONGAH, WV 26554
Complete Address
GLOVER GAP 7.5'
Well Location
MANNINGTON
District
MARION
County
8005
Well No.
CONSOLIDATION COAL CO.
Farm

STATE INSPECTOR SUPERVISING PLUGGING Bill Hochstadt 3-24-15

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

RUSSELL SMALLWOOD and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 20th day of January, 2015 and that the well was plugged in the following manner:

Sand or Zone Record Formation	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In	
Removed 3112' of Sucker Rods from Surface to 3112'. Removed 3127' of 2 3/8" tubing from Surface to 3127'. Cleaned 3 1/2" hole from Surface to 3168' through 4 1/2" casing. Tagged solid plug at 3168'. Removed 1735' of 4 1/2" casing from Surface to 1735'. Left an unknown amount of 4 1/2" casing in the hole from 1735' to an unknown depth. Cemented bottom hole plug from 3168' to 1731' with 90 sacks of Expandable Cement. Cleaned 6 1/2" hole through 7" casing from Surface to 1731'. Tagged top of bottom hole plug at 1731'. Cut 7" casing at the following depths: 1009', 991', 891', 809', 785', 685', 585', 510', 485', 385', 310', 285', 185', and 85'. Removed 43' of 7" casing from Surface to 43'. Left an unknown amount of 7" casing in the hole from 43' to an unknown depth. Jet cut 7" and 10 1/2" casing at the following depths: 795', 793', 791', 789', 787', 785', 783', and 781'. Jet cut through the Pittsburgh Coal seam from 785' to 791'. Left an unknown amount of 10 1/2" casing in the hole from Surface to an unknown depth. All casing left in the hole showed extreme bond due to having been previously cemented. Left 6' of 16" conductor casing in the hole from Surface to 6'.	Sucker Rods		3112'	0'	
		2 3/8"		3127'	0'
		4 1/2"		1735'	Unknown
		7"		43'	Unknown
		10 1/2"		0'	Unknown
		16"		0'	6'
<p><u>Cemented hole from the top of the bottom hole plug at 1731' back to the Surface as follows:</u> From 1731' to 991' with 88 sacks of Expandable Cement. From 991' to 685' with 75 sacks of Thixotropic Cement with green dye. From 685' back to the Surface with 97 sacks of Expandable Cement. Cement did circulate at the surface.</p>					
Coal Seams		Description of Monument			
<u>Pittsburgh</u>	<u>(785' - 791')</u>	<u>77' of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to cement plug at ground level.</u>			

RECEIVED
Office of Oil and Gas
MAR 24 2015
WV Department of Environmental Protection

... and that the work of plugging and filling said well was completed on the 6th day of February, 2015.

And further deponents saith not.

Russell Smallwood
Russell Smallwood

Kevin S. Wright
Kevin S. Wright

03/27/2015

Sworn to and subscribed before me this 26 day of February 2015

Kara Beth Forst
Notary Public

My commission expires: 11/4/23

