FORM WR-38 (Affidavit of Plugging)

STATE OF WEST VIRGINIA DEPARTMENT OF ENERGY OIL AND GAS WELLS DIVISION

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.
Coal Operator or Owner

1 BRIDGE ST. MONONGAH WV 26554

Address

CONSOLIDATION COAL CO.
Coal Operator or Owner

1 BRIDGE ST. MONONGAH WV 26554

Address

DOUGLAS L. CYPHERS

Lease or Property Owner

8 SMOKEY VALLEY ROAD MANNINGTON, WV 26582

Address

Name of Well Operator

1 BRIDGE ST. MONONGAH, WV 26554

Complete Address

CLOVER GAP 7.5'

Well Location

MANNINGTON

District

MARION

County

5161

Well No.

CYPHERS, DOUGLAS L.

7-16-13

CONSOLIDATION COAL CO.

STATE INSPECTOR SUPERVISING PLUGGING which the best of the second supervising plugging with the second supervision supervision

AFFIDAVIT

STATE OF WEST VIRGINIA, County of MONONGALIA ss:

MIKE MITCHELL and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 30th day of May, 2013 and that the well was plugged in the following manner:

Formation	Filling Material	Casing Size & Kind	Casing Pulled	Casing Left In	
Cleaned 12 ¼" hole from the surface to 289'. Reduced hole to 9 7/8". Cleaned 9 7/8" hole from 289' to 1344'. Reduced hole to 7 7/8". Cleaned 7 7/8" hole from 1344' to 1380'. Reduced hole to 6 ¼". Cleaned 6 ¼" hole from 1380' to 1382'. Cleaned 9 7/8" hole through the Pittsburgh Coal seam from 853' to 862'.		16" Conductor	0,	30'	
3		RECEIVED			
Cemented hole from 1382' back to surface as follows; From 1382' to 1062' with 125 sacks of 35/65 Poz Mix Cement. From 1062' to 753' with 132 sacks of Thixotropic Cement w/ dye. From 753' to surface with 264 sacks of Econofill Cement. A total of 521 sacks of cement was used to cement the hole from 1382' to surface. Cement did circulate at the surface. Left 30' of 16" conductor casing in the hole from the surface to 30'.				of Oil	
			JI.	L 22 20	13
			WVD	epartm	ent of
		E	nvironn	iental F	rotection
Coal Seams		Description of Monume			
PITTSBURGH	853' to 862'	77" of 7" casing w/company name, well number,			
(Name)		permit number and date cemented stated on 7"]
(Name)		casing. Well marker will be attached to the			}
(Name)		cement plug at ground level.			<u> </u>

... And that the work of plugging and filling said well was completed on the 14th day of June, 2013

And further deponents saith not.

Mike Mitchell

Kevin S. Wright

Sworn to and subscribed before me this 1^{5} day of $J_{aly} = 2013$

Carole A Mayle Notary Public

My commission expires: 9-12-2017

Permit No. <u>47-49-02257-P</u>

Well No. <u>5161</u>