

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.
Coal Operator or Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address

CONSOLIDATION COAL CO.
Coal Operator or Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address

WILLIAM C. LUCAS
Lease or Property Owner
85 EVANS RUN ROAD MANNINGTON, WV 26582
Address

CONSOLIDATION COAL CO.
Name of Well Operator
1 BRIDGE STREET MONONGAH, WV 26554
Complete Address

GLOVER GAP 7.5'
Well Location
MANNINGTON
District
MARION
County
5348
Well No.

LUCAS, WILLIAM C. & VICKIE
Farm

STATE INSPECTOR SUPERVISING PLUGGING 

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

DELBERT MOORE and KEVIN WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 5th day of August, 2013 and that the well was plugged in the following manner:


Sand or Zone Record Formation	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In
Cleaned 12 1/2" hole from the surface to 334'. Reduced hole to 9 7/8". Cleaned 9 7/8" hole from 334' to 428'. Tagged top of 8 5/8" casing at 428'. Reduced hole to 7 7/8". Cleaned 7 7/8" hole through 8 5/8" casing from 428' to 1341'. Left 893' of 8 5/8" casing in the hole from 428' to 1341'. Continued to clean 7 7/8" hole from 1341' to 1701'. Tagged solid plug at 1701'. Section milled 20' window in 8 5/8" casing from 848' to 868'. Cut remaining 8 5/8" casing at the following depths: 1239', 1140', 1040', 940', 748', 646' and 544'. Cleaned 7 7/8" hole through the Pittsburgh Coal seam from 854' to 862'. Left 20' of 16" conductor casing in the hole from the surface to 20'.		16" Conductor 8 5/8" Casing	0' 0'	20' 893'
Cemented hole from 1701' back to surface as follows: From 1701' to 1062' with 109 sacks of SuperLite Cement. From 1062' to 754' with 49 sacks of SuperTropic Cement with white dye. From 754' to surface with 314 sacks of SuperLite Cement. A total of 472 sacks of cement were used to fill the hole from 1707' back to surface. Cement did circulate at the surface.				
Coal Seams		Description of Monument		
Pittsburgh	(854' - 862')	77" of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to cement plug at ground level.		

RECEIVED
Office of Oil & Gas
OCT 22 2013

WV Department of
Environmental Protection

... and that the work of plugging and filling said well was completed on the 4th day of September, 2013

And further deponents saith not.



Delbert Moore


Kevin S. Wright

Sworn to and subscribed before me this 14 day of October


Notary Public

My commission expires: 2/16/2021



10/25/2013