

**ORIGINAL**

**AFFIDAVIT OF PLUGGING AND FILLING WELL**

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.  
Coal Operator or Owner  
1 BRIDGE ST. MONONGAH WV 26554  
Address  
CONSOLIDATION COAL CO.  
Coal Operator or Owner  
1 BRIDGE ST. MONONGAH WV 26554  
Address  
CONSOLIDATION COAL CO.  
Lease or Property Owner  
1 BRIDGE STREET MONONGAH, WV 26582  
Address

CONSOLIDATION COAL CO.  
Name of Well Operator  
1 BRIDGE ST. MONONGAH, WV 26554  
Complete Address  
GLOVER GAP 7.5'  
Well Location  
MANNINGTON  
District  
MARION  
County  
5120B  
Well No.  
BAKER, MARGT A  
Farm

STATE INSPECTOR SUPERVISING PLUGGING *[Signature]* 5-12-14

**AFFIDAVIT**

STATE OF WEST VIRGINIA,  
County of MONONGALIA ss:

**ROGER MOORE** and **KEVIN S. WRIGHT** being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 8<sup>th</sup> day of April, 2014 and that the well was plugged in the following manner:

Formation	Filling Material	Casing Size & Kind	Casing Pulled	Casing Left In
	Cleaned 12 1/4" hole from the surface to 267'. Reduced hole to 9 7/8". Cleaned 9 7/8" hole from 267' to 1051'. Cleaned 9 7/8" hole through the Pittsburgh Coal seam from 916' to 923'. Tagged top of 8 5/8" casing at 1051'. Removed 73' of 8 5/8" casing from 1051' to 1124'. Continued to clean 9 7/8" hole from 1051' to 1124'. Left 234' of 8 5/8" casing in the hole from 1124' to 1358'. Cut remaining 8 5/8" casing at the following depth: 1254'. Reduced hole to 6 1/4". Cleaned 6 1/4" hole from 1124' to 1869'.	16" Conductor  8 5/8" Casing	0'  73'	20'  234'
<b>Cemented hole from 1869' to the surface as follows:</b> From 1869' to 1123' with 160 sacks of Expandable Cement. From 1123' to 816' with 160 sacks of Thixotropic Cement with Dye. From 816' to surface with 425 sacks of Expandable Cement. A total of 745 sacks of cement were used to cement the hole from 1869' to the surface. Cement did circulate at the surface. Left 20' of 16" conductor casing in the hole from the surface to 20'.				
<b>Coal Seams</b>		<b>Description of Monument</b>		
<u>PITTSBURGH</u>	916' to 923'	77" of 7" casing w/company name, well number,		
(Name)		permit number and date cemented stated on 7"		
(Name)		casing. Well marker will be attached to the		
(Name)		cement plug at ground level.		

... And that the work of plugging and filling said well was completed on the 28<sup>th</sup> day of April, 2014.

And further deponents saith not.

*[Signature]*  
Roger Moore


*[Signature]*  
Kevin S. Wright

Sworn to and subscribed before me this 12<sup>th</sup> day of May 2014

*[Signature]*  
Notary Public

My commission expires: 11/4/23

Permit No. 47-49-02291-P  
Well No. 5120B



**RECEIVED**  
Office of Oil & Gas

MAY 19 2014

WV Department of Environmental Protection 05/23/2014