

LATITUDE 39 32 30

+ .69s
.93w

LONGITUDE 80 17 30

7'5 OGIS topo location

7.5' loc _____ 15' loc _____
(calc.) _____

Company _____

Farm N. S. BEATTY 19

Quad MANNINGTON

County MARION

District LINCOLN

WELL LOCATION MAP

File No. 30006



I, the undersigned hereby certify that this map is correct and shows all the information to the best of my knowledge and belief, required by the Oil & Gas Section of the Mining Laws of West Virginia.

Jno. Egan
Engineer.

NAME	COLOR	CHARACTER	OIL, GAS OR WATER	TOP	BOTTOM	THICK- NESS	TOTAL RES- DEPTH	MARKS
Eighth				50				
Ninth				100				
			oil	150				
Tenth				200	2000	30		
Eleventh				250	2000	30		
Twelfth				300	2000	5		
			gas	350	2000	1		
Total depth							3000	

Well was ^{shot} shot at 2070 feet; well was shot at 2001 feet.

Salt
Fresh water at _____ feet; salt
fresh water at _____ feet.

Well was ^{producing} dry hole.

November 25, 1900

Approved

SOUTH TEXAS OIL COMPANY

Title No. _____ Well No. 19

South Penn Oil Company, of Pittsburgh, Pa.

on the M. A. Beaty Farm

containing 250 acres. Location Little Mods Run

Lincoln District, in Marion County, W. Va.

The surface of the above tract is owned in fee by _____

M. A. Beaty Heirs of Mannington, W. Va. and the

mineral rights are owned by M. A. Beaty Heirs of Mannington, W. Va.

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit No. _____

issued by the West Virginia Department of Mines, Oil and Gas Section,

_____ 1929.

Elevation of surface at top of well, 1113' ~~_____~~ spirit

The number of feet of the smallest sized casing used in the well.

15 feet 14" size. Rod conductor.

560 feet 10" size, csg. 1130 feet 8 1/2" sized csg.

1000 feet 6 5/8" size, csg. _____ feet _____ sized csg.

_____ feet _____ size, csg. _____ feet _____ sized csg.

_____ packer of _____ size, set at _____

_____ packer of _____ size, set at _____

_____ in. casing perforated at _____ feet to _____ feet.

_____ in. casing perforated at _____ feet to _____ feet.

Coal was encountered at 525 feet; thickness _____ inches, and at

_____ feet; thickness _____ inches; and at _____ feet;

thickness _____ inches.

Liners were used as follows: (Give details) 200 feet of 4 7/8"

Liner was used and then pulled and hole reamed, and 412 feet of 5 1/2"

Liner run in two sections, bottom of liner 2000 feet.

November 25, 1929.

Date.

Approved South Penn Oil Company Owner.

By Mann Superintendent.

NOTICE OF INTENTION TO PLUG AND ABANDON WELL
 (REQUIRED BY SECTION 9, CHAPTER 86, ACTS 1928)
 WEST VIRGINIA DEPARTMENT OF MINES
 OIL AND GAS SECTION

TO THE DEPARTMENT OF MINES,
 Charleston, W. Va.

H. B. Beaty, Mannington, W. Va.
 J. Fred. Beaty, Mannington, W. Va.

C. E. Beaty, 627 Benoni Ave.,
 Fairmont, W. Va.

L. N. Beaty, 455 Union St.,
 Morgantown, W. Va.

Mrs. Margaret Clark, Mannington, W. Va.
 Mrs. Chas. F. Cochran, 19 South 6th. St.,
 Martins Ferry, Ohio.

South Penn Oil Company
NAME OF WELL OPERATOR

P. O. Drawer 1255, Pittsburgh, Pa.
COMPLETE ADDRESS

November 25, 19 29
WELL TO BE ABANDONED

Lincoln District

Marion County

Well No. 19

M. A. Beaty Farm

Gentlemen:—

The undersigned well operator is about to abandon the above described well and will commence the


ONE COPY

work of plugging and abandoning said well on the 25th day of December, 19 29
 (which date shall be not less than five days after the day on which this notice so mailed is received, or in due course should be received by the Department of Mines).

This notice is given you in order that your respective representatives may be present at the plugging and filling of said well. You are further notified that whether you are represented or not represented the undersigned will proceed on that date, or shortly thereafter, to plug and fill said well in the manner required by law.

This notice is being mailed by registered mail to each of you at the above addresses on the above date.

Very truly yours,



SOUTH PENN OIL COMPANY
 By Sherry, Sup't.
Well Operator.

NOTE: Upon the abandonment of all wells drilled prior to June 1, 1928, a plat prepared by a competent engineer, showing the district and county in which the tract of land is located, the name and acreage of same, the names of the owners of adjacent tracts, and the location of the about to be abandoned well, determined by survey, and the courses and distances of such well from two permanent points or landmarks on said tract, shall be submitted with this notice.

Mar 6

J. Fred. Beaty-Mannington, W. Va. P. O. Drawer 1255, Pittsburgh, Pa.
 G. E. Beaty-627 Benoni Ave., Fairmont, W. Va. March 22, 19 30
 L. H. Beaty-455 Union St., Morgantown, W. Va. Lincoln District
 Mrs. Margaret Clark-Mannington, W. Va. Marion County
 Mrs. Chas. F. Cochran-19 South 6th St., Martins Ferry, Ohio Well No. 19
 M. A. Beaty Farm

AFFIDAVIT TO BE MADE IN TRIPLICATE: ONE COPY TO BE FILED BY REGISTRAR IN THE DEPARTMENT; ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE OTHER COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO THE WELL OPERATOR'S HOME ADDRESS AT THEIR RESPECTIVE ADDRESSES.

AFFIDAVIT

STATE OF WEST VIRGINIA.

COUNTY OF Marion

F. P. McGee

being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by South Penn Oil Company, well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 28th day of February, 19 30, and that the well was plugged and filled in the following manner:

210 411
 2773

Manner in which said well was plugged: Cleaned out well to a depth of 2625', then filled up with clay, sand and stone to 2500', then drove 8 3/16" x 3' wood dry hole plug to 2500', filled hole with clay, sand and stone to 2440', then bridged hole at 2100', filled hole up with clay, sand and stone to 2000', then drove 6 5/8" x 3' wood dry hole plug to 2000', filled hole up with clay, sand and stone to 1950', drove 6 5/8" x 3' wood dry hole plug to 1950', filled hole up with clay, sand and stone to 1600'. The 6 5/8" casing would not pull and was cut at 1600', 1300', 1200' and 1100', pulled 6 5/8" casing up to 475', bridged hole at 475', then filled hole with clay, sand and stone to 550', then run morning glory packer on 2" tubing with 10' of perforated anchor below packer. Top of packer set at 550' with 564' of 2" tubing on top of packer, and top of 2" tubing 8' above top of ground, then filled hole with cement from 256' to 300', pulled 6 5/8" casing and filled hole up with clay, sand and stone to 3' below top of ground, then cemented hole to 2' above top of ground.

(THE ABOVE DESCRIPTIONS MUST BE IN DETAIL AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 10, OIL AND GAS ACT OF 1920.)
 and that the work of plugging and filling said well was completed on the 28th day of February, 19 30.

And further deponents saith not.

F. P. McGee

Sworn to and subscribed before me this 1st day of April, 19 30

My Commission expires:
November 9, 1937

John Lemley
 Notary Public

APR - 5 1930