

Indo Petroleum
Marine - Ltd

Company
 Address

OIL OR GAS WELL *Var*

COMPLETION DATA SHEET
 No. 2
 FORMATION RECORD

WELL No. *142*

FARM *N B 1/2 mo 2*

Name	Color	Character	Oil, Gas or Water	Top	Bottom	Thickness	Total Depth	Remarks
<i>Pit Coal</i>	<i>black</i>				<i>401</i>	<i>415</i>		
<i>Lith &</i>					<i>716</i>	<i>749</i>		
<i>Tap Sand</i>					<i>1140</i>	<i>1056</i>		
<i>Sand.</i>					<i>1330</i>	<i>1250</i>		
<i>N.S.</i>			<i>HF water</i>	<i>1330</i>	<i>1345</i>			
<i>L. Lime</i>				<i>1360</i>	<i>1134</i>			
<i>Big lime</i>				<i>1152</i>	<i>1137</i>			<i>166</i>
<i>Opium</i>								<i>1450</i>
<i>Sand</i>				<i>1737</i>	<i>1753</i>			<i>Nothing below</i>
<i>50 ft S.</i>				<i>2250</i>	<i>2270</i>			<i>Opium</i>
<i>50 ft S.</i>				<i>2325</i>	<i>2365</i>			<i>bed of D</i>
<i>Sand.</i>				<i>2430</i>	<i>2460</i>			<i>9 ft</i>
<i>Sand.</i>				<i>2500</i>	<i>2510</i>			<i>Top of Sand</i>
<i>At sand</i>				<i>2640</i>	<i>2670</i>			<i>6" Sand</i>
				<i>2719</i>	<i>2775</i>			<i>in hole</i>
								<i>Reball</i>
								<i>at</i>

What 2915

Nothing below
Opium
bed of D
9 ft
Top of Sand
6" Sand
in hole
Reball
at

Well was shut at _____ feet, well was shut at _____ feet.
 Fresh water at *1860* feet, fresh water at _____ feet.
 producing _____ feet.
Sept 5 1926 *7-1-26*

WEST VIRGINIA DEPARTMENT OF MINES

OIL AND GAS DIVISION

PRELIMINARY DATA SHEET NO. 1

File No. Mar-143

Well No. 1

Company of _____

on the _____ Farm

containing 70 acres. Location _____

Rawl Run District, in Marion County, West Virginia

The surface of the above tract is owned in fee by H B Jones

of Farmington W Va address, and the mineral rights are owned by _____

of _____

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit

No. Opera Permits issued by the West Virginia Department of Mines, Oil and Gas Division

Elevation of surface at top of well 1115 ¹⁹⁸ _{feet} ^{Barometric}

The number of feet of the different sized casings used in the well.

<u>775</u>	feet	<u>10" Puller</u>	feet	<u>13"</u>	feet	Wood conductor
<u>1040</u>	feet	<u>8" Puller</u>	feet		feet	steel cas.
<u>1660</u>	feet	<u>6" Puller</u>	feet	<u>1750</u>	feet	steel cas.
	feet	<u>5" Puller</u>	feet		feet	steel cas.

number of _____ size, set at _____

number of _____ size, set at _____

in casing perforated at _____ feet to _____ feet

in casing perforated at _____ feet to _____ feet

Coal was encountered at 407 feet, thickness 96" inches, and at _____

feet; thickness _____ inches; and at _____ feet; thickness _____ inches.

Liners were used as follows: (Give details) _____

Date 2-1-28

STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION

AFFIDAVIT OF PLUGGING AND FILLING WELL

Permit No.

Koppers Coal Co.
COAL OPERATOR OR OWNER
Pittsburgh Pa,
ADDRESS

Victor E. Tennant
NAME OF WELL OPERATOR
Fairview V. Va.
COMPLETE ADDRESS

Oct. 11 19 39

COAL OPERATOR OR OWNER

WELL AND LOCATION

ADDRESS

Paw Paw District

LEASE OR PROPERTY OWNER

Marion County

ADDRESS

Well No. 1

Homer B. Amos Farm

AFFIDAVIT TO BE MADE IN TRIPPLICATE. ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT. ONE COPY TO BE OBTAINED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES.

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of Marion } ss:

Willie Reed and Victor E. Tennant
being first duly sworn according to law depose and say that they are experienced in the work of plugging
and filling oil and gas wells and were employed by Victor E. Tennant, well operator,
and participated in the work of plugging and filling the above well, that said work was commenced on the
2 day of Dec., 19 37, and that the well was plugged and filled in
the following manner:

Manner in which sand was plugged:

Filled with clay from 2915 to 2780- wood plug from 2780 to 2775
1 sack cement, then filled with clay to 2320. Wood plug 2320 to 2317
1 sack cement, then filled with clay to 1735. Wood plug 1735 to 1731
1 sack cement, then filled with clay to 1330. ~~Wood plug~~ 2 sacks se-
ment, then filled with clay to 440, sement to 380, filled with
clay to 330, sement to 290, clay to 12 'stone and sement to surface.

Manner in which coal was plugged:

Description of monument:

12" x 30" above surface.

(THE ABOVE DESCRIPTION MUST BE IN DETAIL AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 10, ARTICLE 4, CHAPTER 25 OF THE CODE)

and that the work of plugging and filling said well was completed on the 22 day of Dec

19 37
And the deponents saith not.



Victor E. Tennant
Signature