



STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION

Quadrangle Cameron

WELL RECORD

Permit No. MARS-319

Stacy
Oil or Gas Well Gas
(KIND)

Company The Manufacturers Light and Heat Company
Address 800 Union Trust Building, Pgh. 19, Penna.
Farm Hobson Teagarden Acres 150
Location (waters) _____
Well No. 4495 Elev. 807.78'
District Liberty County Marshall
The surface of tract is owned in fee by _____
Address _____
Mineral rights are owned by _____
Address _____
Drilling commenced April 15, 1958
Drilling completed October 29, 1958
Date Shot _____ From _____ To _____
With _____
Open Flow _____ /10ths Water in _____ Inch
_____ /10ths Merc. in _____ Inch
Volume _____ Cu. Ft.
Rock Pressure _____ lbs. _____ hrs.
Oil _____ bbls., 1st 24 hrs.
Fresh water _____ feet
Salt water _____ feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			
16" Pipe			Kind of Packer
13			
10"	966	966	Size of
8 1/4"	1301	1301	
7"	1704	1704	Depth set
5 3/16			
3			Perf. top
2			Perf. bottom
Liners Used			Perf. top
			Perf. bottom

CASING CEMENTED _____ SIZE _____ No. Ft. _____ Date _____
COAL WAS ENCOUNTERED AT _____ FEET _____ INCHES
_____ FEET _____ INCHES FEET _____ INCHES
_____ FEET _____ INCHES FEET _____ INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Schlumberger Well Survey							All pipe measured over threads
✓ Pittsburgh Coal		6	566	572			Run 966' of 10 3/4" Casing, Sm.H.32.75# on a steel shoe. Cemented with 400 bags, 15.2 lbs. per gallon. No return of cement at surface. Filled outside of the 10 3/4" to the surface with 205 bags cement. Run 1301' of 8 5/8" Casing SM.J.24# on a steel shoe. Cemented with 250 bags, 15 lbs. per gallon. No return of cement at the surface. Run 1704' of 7" Casing, Sm.J.20#, on a steel Shoe set at 1690'. Cemented with 225 bags, 14 lbs per gallon. No cement return at the surface. Filled between the 7" and 8 5/8 from the surface with 29 bags of cement. Plugged hole back to final depth of 1586' with 65 bags cement. Perforated the Maxton Sand with 93 shots from 1558' to 1581'.
✓ Maxon Sand		23	1557	1580			
✓ Big Lime			1646				
✓ Big Injun Sand				1945			
Total Depth				1586			
7" Shoe set at				1690			
			1646 808 838				

