

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE, on copy mailed to the Division, one copy to be retained by the Well Operator, and the third copy (and extra copies if required) should be mailed to each coal operator at their respective address

Consolidation Coal Co., River Operations
Coal Operator or Owner
Rd. #4, Box 425 Moundsville, WV 26041
Address

Consolidation Coal Co., River Operations
Coal Operator or Owner
Rd. #4, Box 425 Moundsville, WV 26041
Address

Danford & Deborah O'Brian
Lease or Property Owner
RR 4 Box 252 Cameron, WV 26033
Address of Lease or Property Owner

Consolidation Coal Co., River Operations
Name of Well Operator
Rd. #4, Box 425 Moundsville, WV 26041
Complete Address

Majorsville, WV 7.5'
Well Location

Webster
District
Marshall
County
SGW-96
Well No.

Danford & Deborah O'Brian
Farm

STATE INSPECTOR SUPERVISING PLUGGING K. O. 11-16-11
Date

AFFIDAVIT

State of West Virginia
County of Roane:

Leonard Blake and Dan Timm, being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company, Well Operator, and participated in the work of plugging and filling the above well, that said work was commenced on 9-14-11, and that the well was plugged in the following manner:

Sand or Zone Record Formation	Filling Material	Plugs Used Size & Kind	Casing Pulled	Casing Left In		
Kill well with water. Log with Denny/Coal company logger (showed TD at 1813.4, 4 1/2" from surface to 1774', roof coal 633' to 635', Pittsburgh Coal 636.7' to 642' and deviation off 3.1'). Tried to pull 4 1/2" (no movement). Run bond log with Blue Dot and showed was bonded. Talked to Derek Haught/State Man and Adrienne Carney/Consol about perffing 4 1/2", plugging bottom hole and then sand cutting and both said ok. Perf 4 1/2" with Blue Dot at 1574', 1374', 1174', 974', 842', 792', 742' and 692'. Log and perfs were ok. Plugged from 1813.4' up to 842' with Omega using 65 sacks of expanding cement and from 842' up to 692' using 15 sacks of thix with green dye. Sand cut 4 1/2" with BJ Services at 643', 640.5', 638', 635.5', 633', 630.5', 587' and 488'. Log sand cuts with Denny/Coal Company Logger and all were ok. Plug well with Omega using 15 sacks of thix with green dye from 692' up to 533' and from 533' to surface with 50 sacks of expandable cement.	Cemented hole from 1813.4' up to 842' with 65 sacks of expandable cement.	4 1/2" casing (0)	4 1/2" (1774')			
				Cemented hole from 842' to 533' with 30 sacks of Thix with <u>Green Dye</u> cement.	7" casing (0)	7" (unknown)
				Cemented hole from 533' to surface with 50 sacks of expandable cement.	10" casing (0)	10" (unknown)
				Total plug was 145 sacks and cement did circulate.		
Coal Seams	Description of Monument					
Pittsburgh Coal	636.7' to 642'	7" well marker, 77" long with Consol Coal Co.,				
(Name)		Well number, permit number, date and solid plug				
(Name)		Stated on 5" casing. Well marker will be attached				
(Name)		To solid cement plug at ground level.				

RECEIVED
Office of Oil & Gas
NOV 23 2011
WV Department of
Environmental Protection

... and that the work of plugging and filling said well was completed on 10-3-11.

And further deponents saith not.

Leonard Blake
Leonard Blake

Dan Timm
Dan Timm

Sworn to and subscribed before me this the 21 Nov 11

David N. Brannon
Notary Public

My commission expires on: December 10, 2017

