



Company HAROLD C. WILSON
 Address 1285 FAIRLAWNS AVENUE,
 MORGANTOWN, W.Va.
 Farm DAVIDSON-CONNELLSVILLE COAL & COKE Co.
 Tract No. 2. Acres 194.56 Lease No. 1
 Well (Farm) No. 3 Serial No. _____
 Elevation (Spirit Level) 915.25
 Quadrangle MORGANTOWN, W.Va. NW
 County MONONGALIA District UNION
 Engineer Ralph E. Baker
 Engineer's Registration No. 44
 File No. 2-19D-216 Drawing No. 8887
 Date OCT. 13-1958 Scale 1" = 600.

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. MON-237 #3

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.



STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION 7

Quadrangle Morgantown

Permit No. MOA-277

WELL RECORD

Oil or Gas Well Oil
(KIND)

Company H. C. Wilson
Address 1285 Fairbanks Ave Morgantown, W. Va.
Farm Williams Acres 174.56
Location (waters) Morningata
Well No. 7 Elev. 915.25
District Union County Morningata
The surface of tract is owned in fee by William Pembroke Williams
Charmley Pa Address _____
Mineral rights are owned by Same
Address _____

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer <u>None</u>
16			Size of _____
13	<u>14'</u>	<u>None</u>	Depth set _____
10	<u>79'-11"</u>	<u>79'-11"</u>	Perf. top _____
8 3/4	<u>363'-6"</u>	<u>None</u>	Perf. bottom _____
6 3/4	<u>1617'-5"</u>	<u>1617'-8"</u>	Perf. top _____
5 3/16			Perf. bottom _____
3			
2			
Liners Used			

Drilling commenced Oct 28, 1958
Drilling completed Nov 28, 1958
Date Shot Dec 5, 1958 From 1135 To 1140
With 10 qt
Open Flow 5/10ths Water in one Inch
/10ths Merc. in _____ Inch
Volume 26, 4/8 Cu. Ft.
Rock Pressure 340 lbs. 24 hrs.
Oil _____ bbls., 1st 24 hrs.

CASING CEMENTED None SIZE _____ No. Ft. _____ Date _____
COAL WAS ENCOUNTERED AT 298 FEET 12 INCHES
108 FEET 12 INCHES 378 FEET 12 INCHES
480 FEET None INCHES FEET INCHES

WELL ACIDIZED _____
WELL FRACTURED _____

Coal (Non-Commercial)

RESULT AFTER TREATMENT no increase
ROCK PRESSURE AFTER TREATMENT _____
Fresh Water 190' - 378' - 595' Feet Salt Water None Feet

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth	Remarks
Clay	yellow	soft	0	2.5			
Slate	gray	soft	2.5	6.5			
Rock Rock	pink	med	6.5	6.8			
Slate	gray	soft	6.8	10.8			
Coal	black	soft	10.8	10.9			
Slate	black	med	10.8	11.5			
Slate	gray	soft	11.5	12.0			
Slate	gray	med	12.0	16.0			
Lime	gray	soft	16.0	16.5			
Red Rock	red	soft	16.5	22.0	water	190 ft	4-10" Boiler for 1/4"
Grubby Lime	gray	Hard	22.0	25.0			
Slate	gray	soft	22.0	25.5			
Rock Rock	pink	soft	25.0	29.8			
Lime	gray	med	25.5	29.9			
Lime	gray	soft	29.8	29.9			
Upper part coal	black	soft	29.9	31.1			
Slate	dark gray	med	31.1	31.5			
Lime	gray	Hard	31.1	35.8			
Slate	gray	soft	31.5	35.8			
Lime	gray	med	35.8	37.8			



