FORM WR-38
(Affidavit of Plugging)

STATE OF WEST VIRGINIA DEPARTMENT OF ENERGY OIL AND CAS WELLS DIVISION

500	
VV.	Distriction of

61-1232

CFFICE

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

be mailed to each coal operato	or ac cherr re	spective address			
Consolidation Coal Company	Consolidation Coal Company				
Coal Operator or Owner P. O. Box 1314, Morgantown, WV 26505		Name of Well Operator P.O. Box 1314, Morgantown, WV 26505			
Address		July 17	Complete Address	19	 96
Coal Operator or Owner		WEI	LL AND LOCATION		
		Battelle		Distri	ct
Address		Monongalia			
Ralph L. Wright		Honongari	.a 	County	
Lease or Property Own	er				
Rt. 1, Box 17, Wadestown, WV	26589	WELL NO.	4171		
Address		Ralph L. Wr	right		Farm
STATE INSPECTOR SUPERVISING P	LUGGING				
	AFFI	DAVIT			
STATE OF WEST VIRGINIA,					
County of Harrison	ss:				
G. Andrew Lang		and Ke	evin Wright		
being first duly sworn accord	ing to law de			nced in	the
work of plugging and filling	oil and gas w	ells and were em	ployed by Consolid	dation (Coal
Company, well o	perator, and	participated in	the work of pluggi	ng and	f 111-
ing the above well, that said 19 96, and that the well w	work was com	menced on the $\frac{24}{100}$	and day of Ma	зу	·
, and that the well w	as prugged an	a lilled in the	rorrowring manner:		
Sand or Zone Record	Filling M	atorial	Plugs Used	Cas	ing
Formation	FILLING II	ateriai	Size & Kind	CSG	
Cleaned hole with 9 7/8" bit	from surface	to 810' top of 8	<u> </u>	PULLED	EF.LIN
Reduced hole to 7 7/8" & clea				 -	
8 5/8" casing from 810' to 89					
894' to 1552' and ripped in s	everal places	 Section milled 	8 5/8" with		
8 5/8" section mill from 1170	' to 1205'.	Shot 20 shots in	8 5/8" casing		
from 1212' to 1222'. Cleaned	9 7/8" hole	to 853'. Reduced	l hole to 7 7/8" &		
cleaned 7 7/8" hole from 894'	to 1714'. S	ection milled 8 5	/8" hole thru		
Pittsburgh Coal Irom 1196' t	p 1205'. kan	coar protection	string as iollows:		
301.07' of 2 3/8" tubing foll					
hole from 1701.61' back to su	rface using 6	75 sacks of poz m	ix and 135 sacks		
of thixatropic cement. Used	1000 gallons	of mud flush. La	tch down plug at		
1367.44'. Float valve at 140				<u> </u>	
Displaced cement to 1367.44'	with water,	let set and baile	d dry.		\
TOTAL DEPTH: 1,714 feet				17x1	11/a_
			8 5/8" casing (182.821	<u> </u>
Coal Seams			Description of		
(Name) Pittsburgh	1196' to 1	204 '	5' of 4½" casing		
(Name)			stating: Consoli		
(Name)	ļ		Coal Co. Well 41		
(Name)			Permit #47-61-123)Z-P	
and that the work of plu of <u>June</u> , 19		,	as completed on the		_ day

Sworn

NOTARY PUBLIC

Rt. I. Box 606 Mt. Clare, W.V 26408

My commission expires June 29; 1999?

and subset they helled the this 17th day of

ater

Notary Public

July

19 96

ULT US 1997