STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION OFFICE OF OIL AND GAS

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE IN TRIPLICATE, one copy mailed to the Department, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

Farm name: Husk, Ralph Operator Well No.: F2- 568	
LOCATION: Elevation: 1,128' District: Clay Latitude: 2,595 Longitude: 3,525 Well Type: OIL X GAS	Quadrangle: Blacksville County: Monongalia Feet South of 39 Deg. 42 Min. 30 Sec. Feet West of 80 Deg. 12 Min. 30 Sec.
Company: Eastern Associated Coal LLC 1044 Miracle Run Road Fairview, WV 26570 Coal Operator: or Owner Coal Operator: Or Owner Coal Operator: Or Owner Coal Operator: Or Owner Permit Issued Date: December 04, 2014 AFFIDAVIT STATE OF WEST VIRGINIA, County of Monongalia ss: April Sinc and Bradey Summers and Bradey Summers being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by the above named well operator, and participated in the work of plugging and filling the above well, and Gayne Knitowski, Oil and Gas Inspector representing the Director, say that said work was commenced on the 24th day of December, 2014, and that the well was plugged and filled in the following manner:	
TYPE FROM TO	PIPE REMOVED LEFT
Drilled with a 12 1/4" cone bit down to 792'. Drilled with a 8 7/8" cone bit down to 1,232'. Ran logs with Century Wireline Services. Based on the logs the Pittsburgh coal seam is 770'-777'. The well deviated 9.4' at the coal seam. There was no casing in the Pittsburgh coal seam. There is a bottom hole cement plug from 1,232 up to 990'. Then they set an expanding cement plug from 990' to 660'. Then from 660' to surface it was filled with cement. There were 660 sacks of Portland and 140 sacks of expanding cement used to plug the well.	
And further deponents saith not.	