

west virginia department of environmental protection

Office of Oil and Gas 601 57th Street SE Charleston, WV 25304 (304) 926-0450 (304) 926-0452 fax

Earl Ray Tomblin, Governor Randy C. Huffman, Cabinet Secretary www.dep.wv.gov

PERMIT MODIFICATION APPROVAL

February 17, 2016

NORTHEAST NATURAL ENERGY LLC 707 VIRGINIA STREET EAST CHARLESTO, WV 25301

Re: Permit Modification Approval for API Number 6101732, Well #: KASSAY 7H

Modified for Shallower Freshwater

Oil and Gas Operator:

The Office of Oil and Gas has reviewed the attached permit modification for the above referenced permit. The attached modification has been approved and well work may begin. Please be reminded that the oil and gas inspector is to be notified twenty-four (24) hours before permitted well work is commenced.

Please call James Martin at 304-926-0499, extension 1654 if you have any questions.

Sincerely,

Gene Smith Assistant Chief of Permitting

Office of Oil and Gas

Promoting a healthy environment.

WW-6B
(04/15)

API NO. 47- 0 61-	01732
OPERATOR WELL	NO. Kassay 7H
Well Pad Name:	Kassay

STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION, OFFICE OF OIL AND GAS WELL WORK PERMIT APPLICATION

1) Well Operator: Northeast	Natural Energy LLC	494498281	Monongalia	Clay	Blacksville
-		Operator ID	County	District	Quadrangle
2) Operator's Well Number:	Kassay 7H	Well Pa	d Name: Kassa	ау	
3) Farm Name/Surface Owne	r: Nehemiah and Patty A	. Kassay Public Roa	ad Access: Cour	nty Route 25	6/3 (Yank Hollow Road)
4) Elevation, current ground:	1,534' E	levation, proposed	post-construction	on: 1534'	
5) Well Type (a) Gas X	Oil	Und	erground Storag	ge	
Other		·····			
(b)If Gas S	Shallow X	Deep			
F	Iorizontal X				
6) Existing Pad: Yes or No \(\)	es		MAK	2/12/2	016
7) Proposed Target Formation Marcellus, 8,289', 103', 3,6	n(s), Depth(s), Antic 600 psl	pipated Thickness			
8) Proposed Total Vertical De	epth: 8,289'				
9) Formation at Total Vertical	l Depth: Marcellus	S			
10) Proposed Total Measured	Depth: 19,519.5	8'			
11) Proposed Horizontal Leg	Length: 10,315'				
12) Approximate Fresh Water	Strata Depths:	50' , 1,100'			
13) Method to Determine Free	sh Water Depths:	Driller's Log from	Offset Wells		
14) Approximate Saltwater De	epths: 1,946', 2,69	96'			
15) Approximate Coal Seam I	Depths: 316', 1,09	98'			
16) Approximate Depth to Po	ssible Void (coal m	ine, karst, other):	N/A		
17) Does Proposed well locati directly overlying or adjacent		ms Yes	No	<u>x</u>	
(a) If Yes, provide Mine Info	o: Name:				
	Depth:		· · · · · · · · · · · · · · · · · · ·		
	Seam:				
	Owner:	·	RECEIVED		

FEB 77 7816

WV Department of Environmental Protection

OPERATOR WELL NO. Kassay 7H
Weil Pad Name: Kassay

18)

CASING AND TUBING PROGRAM

TYPE	Size (in)	New or Used	Grade	Weight per ft. (lb/ft)	FOOTAGE: For Drilling (ft)	INTERVALS: Left in Well (ft)	CEMENT: Fill-up (Cu. Ft.)/CTS
Conductor	24"	New	NA	94.71	40'	40'	GTS
Fresh Water	13-3/8"	New	J-55	54.5	1,230'	1,200'	CTS
Coal		· · · · · · · · · · · · · · · · · · ·					
Intermediate	9-5/8"	New	J-55	40	2,780'	2,750'	CTS
Production	5-1/2"	New	P-110	20	19,519'	19,489'	4,497 Cu. Ft.
Tubing	2-7/8"	·New	N-80	6.5	NA	8,500'	NA
Liners							

MAK ZINZOIL

TYPE	Size (in)	Wellbore Diameter (in)	Wall Thickness (in)	Burst Pressure (psi)	Anticipated Max. Internal Pressure (psi)	Cement Type	Cement Yield (cu. ft./k)
Conductor	24"	30"	.375	415		4,500 psi Grout	NA
Fresh Water	13-3/8"	17 1/2"	.38"	2,760	2,000	Class A	1.23
Coal							······································
Intermediate	9-5/8"	12 1/4"	.395"	3,950	3,000	Class A	1.3
Production	5-1/2"	8 3/4"	.361"	12,530	9,700	50:50 Poz	1.21
Tubing	2-7/8"	NA	.217"	10,570	3,600	NA	NA
Liners					<u> </u>		

PACKERS

Kind:		
Sizes:		**************************************
Depths Set:		Personal Control of the Control of t
	RECEIVE)
	Office of Oil and	3as

FEH 7 7619

WV Department of Environmental Protection

OPERATOR WELL NO. Kessay 7H

Well Pad Name: Kessey

19) Describe p	roposed well work,	including the	drilling and pl	lugging back	of any pilot hole:

Drilling and completion of a horizontal Marcellus well. The well will be drilled on air to an approximate depth of 6,093.61' TVD/MD. The well will then be horizontally drilled on synthetic based mud from the KOP to approximately 8,289' TVD / 19,519.58' MD along a 323 degree azimuth.

20) Describe fracturing/stimulating methods in detail, including anticipated max pressure and max rate:

Multi-stage / high-rate slickwater fracture treatment using various size sands as proppant. First stage will be initiated via pressurization against a burst disc ran in the production casing string or perforated with coiled tubing. Subsequent stages will be perforated with pumped down guns ran on wireline. Individual stages will be isolated with composite frac plugs. Maximum pump rate during any stage will be 110 BPM with a maximum allowable surface pressure of 9,500 PSI. Composite bridge plugs will be set at the end of the last stage to isolate the treated formation.

- 21) Total Area to be disturbed, including roads, stockpile area, pits, etc., (acres): 15.85
- 22) Area to be disturbed for well pad only, less access road (acres): 13.00
- 23) Describe centralizer placement for each casing string:

Surface and intermediate casing strings will have bow spring centralizers placed every third joint (~120') from the shoe joint to surface. Production casing will have rigid body centralizers placed at a minimum of every fourth joint (~160') from TD to surface.

24) Describe all cement additives associated with each cement type:

Surface string cement will be a Class A + Max 3% bwoc Calcium Chloride Fresh Water blend. Intermediate string cement will be a Class A Cement + Max 3% bwoc Calcium Chloride + Fresh Water. Production string cement will be (50:50) Poz (Fly Ash):Type I Cement with a gas migration additive.

25) Proposed borehole conditioning procedures:

Surface string will use a 25.0 bbls Gel Pill + LCM + 25 lbs Cello Flake + 20 lbs/bbl Bentonite @ 8.4 ppg & 10 bbls fresh water spacer prior to cement. Intermediate string will use a 25.0 bbls Gel Pill + LCM + 25 lbs Cello Flake + 20 lbs/bbl Bentonite @ 8.4 ppg & 10 bbls fresh water spacer prior to cement. Production string will use a 50.0 bbls SealBond 25 + 1 gal/bbl US-40 + 275 lbs/bbl Barite + 1 gal/bbl SS-2 Spacer @ 13.5 ppg prior to cement.

-

RECEIVED
Office of Oil and Gas

*Note: Attach additional sheets as needed.

FEB 1-7 2016

WV Department of Environmental Protection Page 3 of 3 02/19/2016

OPERATOR WELL NO.
Well Pad Name:

Kassay

Kassay

STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION, OFFICE OF OIL AND GAS VOLUNTARY STATEMENT OF NO OBJECTION

Instructions to Persons Named on Page WW-6A

The well operator named on page WW-6A is applying for a permit from the State of West Virginia to conduct oil or gas well work. Well work permits are valid for twenty-four (24) months. Please contact the listed well operator and the Office of Oil and Gas if you do not own any interest in the listed surface tract.

Comment and Waiver Provisions

Pursuant to West Virginia Code § 22-6A-11(a), all persons described in subsection (b), section ten of this article may file written comments with the secretary as to the location or construction of the applicant's proposed well work within thirty days after the application is filed with the secretary.

Pursuant to West Virginia Code § 22-6A-8(b) No permit may be issued less than thirty days after the filing date of the application for any well work except plugging or replugging; and no permit for plugging or replugging may be issued less than five days after the filing date of the application except a permit for plugging or replugging a dry hole: *Provided*. That if the applicant certifies that all persons entitled to notice of the application under the provisions of subsection (b), section ten of this article have been served in person or by certified mail, return receipt requested, with a copy of the well work application, including the erosion and sediment control plan, if required, and the well plat, and further files written statements of no objection by all such persons, the secretary may issue the well work permit at any time.

listed above, and that	VOLUNTARY STATEM ders , hereby state that I have read the Instru I have received copies of a Notice of Application,	an Application for a Well Worl	age WW-6A and the associated provisions k Permit on Form WW-6A and attachments
consisting of pages o well work on the trac	ne (1) through, including the erosion	and sediment control plan, if re	equired, and the well plat, all for proposed
State:	West Vinginia	Faction	1,004,264,025
County:	Monongalia W	VSPN NAD 27 Easting: Northing:	1,804,364.035 422,594.593
District:		ublic Road Access:	422,394.393
Quadrangle:		enerally used farm name:	
Watershed:		one and a sum name.	
*Please check the b			BY A NATURAL PERSON
_ bold ACL o	WINER	Signature	
☐ SURFACE O	WNER (Road and/or Other Disturbance)	Print Name:	
		Date:	
☐SURFACE OV	VNER (Impoundments/Pits)		
			BY A CORPORATION, ETC.
⊠COAL OWNE	R OR LESSEE	Company:	CONSOL Mining Company LLC
		Ву:	Casey V. Saunders
⊠COAL OPERA		Ito	C . D
	ATOR	Its:	Senior Project Engineer
I IM/ATTED DITTO		1	Senior Project Engineer
□WATER PURY		Signature:	V. Samor
		Signature: Date:	V. James 2/12/2016

Oil and Gas Privacy Notice:

The Office of Oil and Gas processes your personal information, such as name, address and telephone function and Gas processes your personal information, such as name, address and telephone function and Gas part of our regulatory duties. Your personal information may be disclosed to other State agencies or third parties in the normal course of the same of the country or regulatory requirements, including Freedom of Information Act requests. Our office will appropriately secure your personal information. If you have any questions about our use or your personal information, please contact DEP's Chief Privacy of the philoscoffice wv.gov.