

#### west virginia department of environmental protection

Office of Oil and Gas 601 57th Street, S.E. Charleston, WV 25304 (304) 926-0450 fax: (304) 926-0452

Austin Caperton, Cabinet Secretary www.dep.wv.gov

## Thursday, August 29, 2019 PERMIT MODIFICATION APPROVAL Horizontal 6A / New Drill

NORTHEAST NATURAL ENERGY LLC 707 VIRGINIA STREET EAST STE 1200 CHARLESTON, WV 25301

Re:

Permit Modification Approval for LEMLEY 2H

47-061-01850-00-00

Change in freshwater casing.

#### NORTHEAST NATURAL ENERGY LLC

The Office of Oil and Gas has reviewed the attached permit modification for the above referenced permit. The attached modification has been approved and well work may begin. Please be reminded that the oil and gas inspector is to be notified twenty-four (24) hours before permitted well work is commenced.

If there are any questions, please feel free to contact me at (304) 926-0450.

James A. Martin

Chief

Operator's Well Number: LEMLEY 2H

Farm Name: CLARENCE W. LEMLEY JR. & CHARLOTTE E. L

U.S. WELL NUMBER: 47-061-01850-00-00

Horizontal 6A New Drill

Date Modification Issued:

Promoting a healthy environment.

WW-6B (04/15)

API NO. 47- <u>061</u>	_ 01850	
OPERATOR V	VELL NO. 2H	-
Well Pad Na	me: Lemley	

# STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION, OFFICE OF OIL AND GAS WELL WORK PERMIT APPLICATION

1) Well Operato	r: Northeast	Natural	Energy 🛔	4944	98281	Monongalia	Clay	Blacksville,	WV
•					rator ID	County	District	Quadrangle	
2) Operator's W	ell Number: 2	2H			Well Pad	Name: Lemle	ey .		
3) Farm Name/S	Surface Owner	. Clarence V	V Jr & Charlotte E	Lemley	Public Road	d Access: Stat	e Route 22	2	
4) Elevation, cu	rrent ground:	1,560'	Ele	evatio	n, proposed p	oost-construction	on: 1540'		
5) Well Type	(a) Gas X		Oil		Unde	rground Storag	e		
	Other								
	(b)If Gas S	hallow	X		_ Deep				
	Н	orizontal	X		_	Gayne	Digitally signed	i by Gayne	
6) Existing Pad:	Yes or No N	0				Knitowsl		9 07:48:43	
7) Proposed Tar Marcellus; 8,2	get Formation 206'; 53'; 3,60		h(s), Antici	pated	Thickness ar	nd Expected Pr	essure(s):		
8) Proposed Tot	al Vertical De	pth: 8,2	06'			F 7 500			
9) Formation at			Marcellus			OFFICE OF	E OIL AND	DAM	
10) Proposed To	9) Formation at Total Vertical Depth: Marcellus OFFICE OF OIL AND GAS 10) Proposed Total Measured Depth: 21,104'								
11) Proposed Horizontal Leg Length: 12,363' AUG 29 2019									
12) Approximate Fresh Water Strata Depths: 500', 1,070'									
13) Method to Determine Fresh Water Depths: Drillers Log from Offset Wells									
14) Approximat	14) Approximate Saltwater Depths: 2,037'; 2,511'								
15) Approximat	e Coal Seam I	Depths:	500', 1,070	)'					
16) Approximat	e Depth to Pos	ssible Vo	id (coal mi	ne, ka	rst, other): 1	,063' - 1,070'			
17) Does Propos directly overlyin					Yes	No	X		
(a) If Yes, prov	vide Mine Info	: Name	b:						
		Deptl	1:		_				
		Seam	:						
		Owne	er:						

WW-6B	
(04/15)	

API NO. 47-\_<sup>061</sup>\_\_ - <sup>01850</sup> OPERATOR WELL NO. <sup>2H</sup>\_

Well Pad Name: Lemley

# 18)

# **CASING AND TUBING PROGRAM**

TYPE	Size (in)	New or Used	Grade	Weight per ft. (lb/ft)	FOOTAGE: For Drilling (ft)	INTERVALS: Left in Well (ft)	CEMENT: Fill-up (Cu. Ft.)/CTS
Conductor	24"	New	NA	94.71	40'	40'	GTS
Fresh Water	13-3/8"	New	J-55	54.5	1,220'	1,170'	CTS
Coal							
Intermediate	9-5/8"	New	J-55	36	2,591'	2,561'	CTS
Production	5-1/2"	New	P-110	20	21,104'	21,074"	4,955 cu ft.
Tubing							
Liners							

Gayne Knitowski Digitally signed by Gayne Knitowski Date: 2019.08.29 07:49:04 -04'00'

TYPE	Size (in)	Wellbore Diameter (in)	Wall Thickness (in)	Burst Pressure (psi)	Anticipated Max. Internal Pressure (psi)	Cement Type	Cement Yield (cu. ft./k)
Conductor	24"	38"	.375"	415		4,500 psi grout	NA
Fresh Water	13-3/8"	17-1/2"	.38"	2,760	2,000	Class A	1.23
Coal							
Intermediate	9-5/8"	12-1/4"	.352"	3,520	2,800	Class A	1.3
Production	5-1/2"	8-3/4"	.361"	12,530 <b>A</b>	ECE9VED	50:50 poz	1.21
Tubing	2-7/8"	NA	.217"	QISTICE (	of Qiband	GA6A	NA
Liners					NUG <b>2 9</b> 2019		

# **PACKERS**

Kind:		
Sizes:		
Depths Set:		

WW-6B
(10/14)

API NO. 47061 01850
OPERATOR WELL NO. 2H
Well Pad Name: Lemley

19) Describe proposed well work, including the drilling and plugging back of any pilot hole:

Drilling and completion of a horizontal Marcellus well. The well will be drilled on air to an approximate depth of 6,100 TVD/MD. The well will then be horizontally drilled on synthetic based mud from the KOP to approximately 8,206 TVD/21,104' MD along a 147.50° azimuth.

20) Describe fracturing/stimulating methods in detail, including anticipated max pressure and max rate:

Multi-stage / high-rate slickwater fracture treatment using various size sands as proppant. First stage will be initiated via pressurization against a burst disc ran in the production casing string or perforated with coiled tubing. Subsequent stages will be perforated with pumped down guns ran on wireline. Individual stages will be isolated with composite frac plugs. Maximum pump rate during any stage will be 110 BPM with a maximum allowable surface pressure of 9,500 PSI. Composite bridge plugs will be set at the end of the last stage to isolate the treated formation.

- 21) Total Area to be disturbed, including roads, stockpile area, pits, etc., (acres): 23.73
- 22) Area to be disturbed for well pad only, less access road (acres): 8.39
- 23) Describe centralizer placement for each casing string:

Surface and intermediate casing strings will have bow spring centralizers placed every third joint (~120') from the shoe joint to surface. Production casing will have rigid body centralizers placed at a minimum of every fourth joint (~160') from TD to surface.

24) Describe all cement additives associated with each cement type:

Surface string cement will be a Type 1 + Max 3% bwoc Calcium Chloride + Fresh Water. Intermediate string cement will be a Type 1 Cement + Max 3% bwoc Calcium Chloride + Fresh Water. Production string cement will be (50:50) Poz (Fly Ash):Type I Cement with all as migration additive.

25) Proposed borehole conditioning procedures:

Surface string will use a 25.0 bbls Gel Pill + LCM + 25 lbs Cello Flake + 20 lbs/bbl Bentonite @ 8.4 ppg & 10 bbls fresh water spacer prior to cement. Intermediate string will use a 25.0 bbls Gel Pill + LCM + 25 lbs Cello Flake + 20 lbs/bbl Bentonite @ 8.4 ppg & 10 bbls fresh water spacer prior to cement. Production string will use a 50.0 bbls SealBond 25 + 1 gal/bbl US-40 + 275 lbs/bbl Barite + 1 gal/bbl SS-2 Spacer @ 13.5 ppg prior to cement.

<sup>\*</sup>Note: Attach additional sheets as needed.

**	VV -UM VV	
(1	-12)	

API NO. 47- 061 - 0185	50
OPERATOR WELL NO.	2H
Well Pad Name: Lemley	

# STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION, OFFICE OF OIL AND GAS VOLUNTARY STATEMENT OF NO OBJECTION

Instructions to Persons Named on Page WW-6A

The well operator named on page WW-6A is applying for a permit from the State of West Virginia to conduct oil or gas well work. Well work permits are valid for twenty-four (24) months. Please contact the listed well operator and the Office of Oil and Gas if you do not own any interest in the listed surface tract. RECEIVED

Comment and Waiver Provisions
Pursuant to West Virginia Code § 22-6A-11(a), all persons described in subsection (b), section ten of this article may file written comments with the secretary as to the location or construction of the secretary as to the location or construction is filed with the secretary

Pursuant to West Virginia Code § 22-6A-8(b) No permit may be issued less than thirty days after the filing date of the application for any well work except plugging or replugging; and no permit for plugging or replugging may be issued less than five days after the filing date of the application except a permit for plugging or replugging a dry hole: Provided, That if the applicant certifies that all persons entitled to notice of the application under the provisions of subsection (b), section ten of this article have been served in person or by certified mail, return receipt requested, with a copy of the well work application, including the erosion and sediment control plan, if required, and the well plat, and further files written statements of no objection by all such persons the secretary may issue the well work permit at any time.

## VOLUNTARY STATEMENT OF NO OBJECTION

WW-6A and attachments consisting of pages one (1) trequired, and the well plat, all for proposed well work on State:  West Virginia  County:  Monongalia  District:  Clay  Quadrangle:  Watershed:  Dunkard Creek  I further state that I have no objection to the planned work issued on those materials.	ead the Instructions to Persons Named on Page WW-6A and the associated of a Notice of Application, an Application for a Well Work Permit on Form hrough 3, including the erosion and sediment control plan, is the tract of land as follows:  - UTM NAD 83
*Please check the box that applies	FOR EXECUTION BY A NATURAL PERSON
□ SURFACE OWNER RECEIVED  □ SURFACE OWNER RECEIVED  □ SURFACE OWNER RECEIVED	
SURFACE OWNER (Impounding fits)	
■ COAL OWNER OR LESSEE	FOR EXECUTION BY A CORPORATION, ETC. Company: Consolidation coul company
☐ COAL OPERATOR	Its: coal, oil and gas relations manager
☐ WATER PURVEY → R	Signature: Musaph Sunts
$\ \square$ OPERATOR OF ANY NATURAL GAS STORA	

### Oil and Gas Privacy Notice:

The Office of Oil and Gas processes your personal information, such as name, address and telephone number, as part of our regulatory duties. Your personal information may be disclosed to other State agencies or third parties in the normal course of business or as needed to comply with statutory or regulatory requirements, including Freedom of Information Act requests. Our office will appropriately secure your personal information. If you have any questions about our use or your personal information, please contact DEP's Chief Privacy Officer at depprivacyofficer@wv.gov.