

LATITUDE 39°45'00"

80°22'30"

LONGITUDE

75'

7.5 OGIS topo location

7.5' loc 2.395
0.230

15' loc 2.395
(calc.) 2.450

Company _____

Farm _____

Quad Hundred (Mannington ave)

County Mannington

District Battelle

WELL LOCATION MAP

File No. 061-519A



STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION

WELL RECORD

Well No. _____ Oil or Gas Well _____

Company Nelson E. Richards

Address _____

Owner S. E. Kibble Acres 47

Location (town) Dunford Iron

Well No. 1 Elev. 1240

District Rutledge County Monongalia

The surface of land is owned in fee by S. E. Kibble

Map Reference _____

Mineral rights are owned by Address Unknown

and not over 500,000,000

Drilling commenced August 5th, 1955

Drilling completed _____

Date shut in From To

Well _____

Open Flow 40 /1000 Water in 2 Feet

/1000 Min. in. _____ Feet

Volume _____ Cu. Ft.

Rock Pressure 475 No. 18 lbs.

Oil _____ Mts. at 24 hrs.

Fresh water _____ feet

Salt water _____ feet

Casing and Tubing	Inside Diameter	Left in Well	Feet
Size			
18			Kind of Packer
18	740	340	Size of
18	1200	1400	
6 1/2	2500	2650	Depth set
6 3/8			
2			Feet top
2	3000	3150	Feet bottom
License Used			Feet top
			Feet bottom

CASING CEMENTED _____ No. Ft. _____

COAL WAS ENCOUNTERED AT 550 FEET 50 INCHES

350 FEET 50 INCHES FEET INCHES

FEET INCHES FEET INCHES

FEET INCHES FEET INCHES

FEET INCHES FEET INCHES

Description	Color	Kind or Sub	Top	Bottom	Oil or Gas or Water	Depth Feet	Remarks
Clay		Soft	0	15			
Lime		Broken	15	250			
Lime		Hard	250	500			
Sand		Hard	500	700			
Lime		Hard	700	850			
Mt Coal		Soft	850	950			
Lime Shells		Broken	950	960			
Pittsburgh Co 1		Soft	960	965			
Lime		Hard	965	1025			
Slate		Soft	1025	1105			
Marphy S-and		Hard	1105	1110			
Red Rock			1110	1300			
Lime Shells		Broken	1300	1325			
Little Dunford		Hard	1325	1405			
Slate			1405	1450			
Big Dunford		Hard	1450	1510			
Slate Shells			1510	1750			
1st Salt Sand		Broken	1750	1840			
2nd Salt Sand		Broken	1840	2050			
Little Lime		Hard	2050	2070			
Big Lime		Hard	2070	2150			
Big Injun		Hard	2150	2420			
Slate & Lime Shells		Broken	2420	2950	3-in	2953-65	
50 Foot		Hard	2950	3010			
Slate		Soft	3010	3030			
Gordon Sand		Broken	3030	3100			
Sand Shells		Broken	3100	3160			
Total Depth				3160			





STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN VERILGATE, ONE COPY MAILED TO THE COMMISSIONER, ONE COPY TO BE RETURNED BY THE WELL OPERATOR AND THE THIRD COPY (AND OTHER COPIES IF DESIRED) SHOULD BE MAILED TO EACH LOCAL OPERATOR AT THEIR RESPECTIVE OFFICES.

Address Winnon-Cool not being operated Nelson H. Richards
NAME OF WELL OPERATOR
NAME OF WELL OPERATOR
Star Route 2, Canaan, W. Va.
LOCAL ADDRESS
DATE OF WELL CLOSURE
October 16, 1961
WELL AND LOCATION
Buttle District
Monongalia County
WELL NO. 1
S. S. Stahle Firm

STATE INSPECTOR SUPERVISING PLUGGING Glycer H. Linberg

AFFIDAVIT

STATE OF WEST VIRGINIA,

County of Marshall

Nelson H. Richards and
being the duly sworn according to law deposes and says that they are experienced in the work of
plugging and filling oil and gas wells and were employed by Self
and operated, and participated in the work of plugging and filling the above well, that said work
was completed on the 16th day of September, 1961, and that the well was plugged
and filled in the following manner:

TYPE OF WELL CLOSURE	PLUGGING MATERIAL		PLUGGING METHOD	CASING	
	DEPTH	TO		TYPE	OD
<u>Set a permanent bridge at</u>	<u>2100</u>	<u>2200</u>	<u>clay</u>		
	<u>2200</u>	<u>2300</u>	<u>crushed stone</u>		
	<u>2300</u>	<u>2400</u>	<u>peat cement</u>		
<u>Set a permanent bridge at</u>	<u>2400</u>	<u>2500</u>	<u>clay</u>	<u>8 1/2"</u>	
	<u>2500</u>	<u>2600</u>	<u>clay</u>		
	<u>2600</u>	<u>2700</u>	<u>crushed stone</u>		
	<u>2700</u>	<u>2800</u>	<u>peat cement</u>		
<u>Filled casing and at</u>	<u>2800</u>	<u>filled</u>	<u>with peat cement at</u>		
<u>Set permanent bridge at</u>	<u>2800</u>				
<u>Filled with clay</u>	<u>2800</u>	<u>2900</u>	<u>clay</u>		
	<u>2900</u>	<u>3000</u>	<u>crushed stone</u>		
	<u>3000</u>	<u>3100</u>	<u>peat cement</u>		
<u>Set permanent bridge at</u>	<u>3100</u>				
<u>with clay</u>	<u>3100</u>	<u>320</u>	<u>peat cement and gravel</u>		
<u>and</u>	<u>320</u>	<u>330</u>	<u>clay</u>		<u>annular space</u>
<u>and</u>	<u>330</u>	<u>340</u>	<u>peat cement remove 6"</u>		<u>annular</u>
<u>and</u>	<u>340</u>	<u>350</u>	<u>filled with clay remove 10'</u>		<u>casing</u>
<u>and</u>	<u>350</u>	<u>360</u>	<u>filled with clay</u>		

and that the well was plugged and filling said well was completed on the 16th day of September 1961

Nelson H. Richards, affiant