

LATITUDE 39° 37' 30"

79° 52' 30"

LONGITUDE

75'

7'5 OGIS topo location

7.5' 10C	<u>2.79 S</u>	15' 10C	<u>5.67 S</u>
	<u>2.04 W</u>	(calc.)	<u>4.26 W</u>

Company _____

Farm _____

Quad Morgantown South (Hybrid C)

County Monongahelia

District Morgan

WELL LOCATION MAP

File No. 061-70095

Morganon District, Monongalia County, W. Va.
By James Kuntz, Jr. & Co., Owners.
Samuel Baker, contractor.

70095

Drilling commenced April 10, 1910, and completed, June 4, 1910.
10" casing, 191'; 8 1/2", 482'; 6-5/8", 1167'; all casing pulled;
hole plugged to protect sands.
Dry hole; sands broken and inferior from injun down.
Pittsburgh Coal 400' in the air at well mouth.

	Top.	Bottom.	Thickness.
Surface	0	6	6
Gravel	6	9	3
Slate and shells	9	16	7
Shell	16	20	4
Lime and sand	20	80	60
Slate	80	130	50
Lime	130	152	22
Slate	152	170	18
Sand	170	210	40
Coal	210	213	3
Slate	213	227	14
Sand	227	247	20
Slate	247	272	25
Shells	272	285	13
Lime and sand	285	310	25
Slate and shells	310	325	15
Sand and shells	325	335	10
Slate and shells	335	350	15
Slate	350	375	25
Red rock	375	415	40
Shells	415	465	50
Sand	465	480	15
Slate and lime	480	520	40
Salt Sand	520	560	40
Red rock and lime	560	635	75
Lime and sand	635	650	15
Slate and lime	650	690	40
Red rock and lime	690	780	90
Lime and sand	780	795	15
Red rock	795	825	30
Lime and sand	825	890	65
Slate and shells	890	1020	130
Big Injun Sand	1020	1145	125
Lime and slate	1145	1300	155
Sand	1300	1325	25
Slate and shells	1325	1400	75
Lime and sand	1400	1430	30
Sand	1430	1470	40
Slate	1470	1535	65
Sand and slate	1535	1585	50
Lime and sand	1585	1625	40
Slate and red rock	1625	1790	165
Shells and red rock	1790	1910	120
Sand and slate	1910	1965	55
Red rock and slate, to bottom	1965	2400	435