

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

TUNNEL RIDGE, LLC
Coal Operator or Owner
2596 BATTLE RUN RD, TRIADELPHIA, WV 26059
Address

TUNNEL RIDGE, LLC
Coal Operator or Owner
2596 BATTLE RUN RD, TRIADELPHIA, WV 26056
Address

AB HOLDINGS DE, LLC
Lease or Property Owner
5521 OHIO RIVER RD, POINT PLEASANT, WV 25550
Address

LOIS JACK
Name of Well Operator
2364 OVERBROOK AVENUE, WHEELING, WV 26003
Complete Address

VALLEY GROVE
Well Location
TRIADELPHIA

District
OHIO
County
20779-TPI
Well No.
JACK, EUGENE C., SR.
Farm

STATE INSPECTOR SUPERVISING PLUGGING



11.10.16

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

RUSSELL SMALLWOOD and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by LOIS JACK well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 17th day of October, 2016 and that the well was plugged in the following manner:

Formation	Filling Material	Casing Size & Kind	Casing Pulled	Casing Left In
Removed 5208' of 1 1/2" tubing from Surface to 5208'. Removed all 1 1/2" tubing from wellbore. Set permanent bridge plug in 4 1/2" casing at 5834'. Cemented bottom hole with 10 sacks of Class A Cement from 5834' to 5733' and 6% Gel from 5733' to 3330'. Removed 5260' of 4 1/2" casing from Surface to 5260'. Left ~1598' of 4 1/2" casing in the hole from 5260' to ~6858'. All approximate casing depths taken from previous well record. Cemented hole from 3330' back to Surface as follows: From 3330' to 3230' with 30 sacks of Class A Cement. From 3230 to 2550' with 6% Gel. From 2550' to 2450' with 30 sacks of Class A Cement. From 2450' to 1350' with 6% Gel. From 1350' to 1250' with 35 sacks of Class A Cement. From 1250' to 835' with 6% Gel. From 835' to 610' with 70 sacks of Class A Cement. From 610' to 250' with 6% Gel. From 250' back to the Surface with 955 sacks Class A Cement. Cement did circulate at the Surface.	20" Conductor Casing	0'	60'	
	11 3/8" Casing	0'	~785'	
	8 5/8" Casing	0'	~2514'	
	4 1/2" Casing	5260'	~1598'	
	1 1/2" Tubing	5208'	0'	
Coal Seams		Description of Monument		
<u>PITTSBURGH COAL</u>	~650' to ~660'	77" of 7" casing w/company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to the cement plug at ground level.		
(Name)				
(Name)				
(Name)				

He.
Office of Oil & Gas
NOV 18 2016

... And that the work of plugging and filling said well was completed on the 28th day of October, 2016

And further deponents saith not.


Russell Smallwood 11/18/2016