

STATE OF WEST VIRGINIA
 DIVISION OF ENVIRONMENTAL PROTECTION
 OFFICE OF OIL AND GAS

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE IN TRIPlicate, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

Farm Name: **Thomas J. Gallagher et. Al.** Operator Well No. : **Tormey #1**

LOCATION: Elevation **844 ft.** Quadrangle: **Scott Depot, West Virginia**
 District: **Scott District** County: **Putnam, West Virginia**
 Latitude: **11,700 Feet South of 38 Deg. 30 Min. 00 Sec.**
 Longitude: **6,575 Feet West of 81 Deg. 52 Min. 30 Sec.**

Well Type OIL GAS XX

Company: **Teavee Oil and Gas Inc.** Coal Operator NONE
112 Brooks Street
Charleston West Virginia 25301

Agent: **Duane Bowers**
 Permit Issued Date: **07/31/2015** AFFIDAVIT

STATE OF WEST VIRGINIA
 County of Putnam ss:

Richard Moore and **Grover Bulter** being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by the named well operator, and participated in the work of plugging and filling the above well, and **Jamie Stevens** Oil and Gas Inspector representing the Director, say that said work was commenced on the **12th** day of **October 2015** and that the well was plugged and filled in the following manner:

Note: There is no 2-3/8", 3-1/2", 4-1/2", 8-5/8" or 10" found in this well				
TYPE	FROM	TO	PIPE REMOVED	LEFT
CEMENT	2835	2735	12 sacks cement w/ latex paint added	Drilling tools stem jars wireline knife socket
GEL	2735	2330		450 feet 7/8 drilling line
CEMENT	2330	2230	12 sacks cement w/ latex paint added	
GEL	2230	2000		
CEMENT	2000	1900	Cement across 5-1/2 casing shoe	
GEL	1900	1708		
CEMENT	1708	1608		Ripped holes in 5-1/2" casing 1700-1600 ft
GEL	1608	1418		
CEMENT	1418	1318	Cut 5-1/2 casing @ 1390 feet	586 feet 5-1/2" casing
GEL	1318	1210		
CEMENT	1210	1110		Ripped holes in 7" casing 1200-1100 ft
GEL	1110	810		1652 feet 7 inch casing rotten
CEMENT	810	710		Ripped holes in 7" casing 800-700 ft
GEL	710	400		
CEMENT	400	300		Ripped holes in 7" casing 400-300 ft
GEL	300	100		
CEMENT	100	0		Ripped holes in 7" casing 100 ft. to surface

*** 7 inch casing rotten below surface dug 7 feet down could not weld and or nipple up to pull 7 inch casing

DESCRIPTION OF MONUMENT: **5 " set 36" above ground API # and Date Plugged, welded on the side of pipe.** And that the work of plugging and filling said well was completed on the **23rd** day of **October 2015**.

And further deponents saith not.
 Richard Moore
 Grover Bulter

Sworn and subscribed before me this 24th day of October, 2015 01/22/2016

My commission expires: 01/20/2018 Duane K Bowers Notary Public

Oil and Gas Inspector: Jamie Stevens 1/2/2015
 Jamie Stevens

