





STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION 4

Rotary   
Spudder   
Cable Tools   
Storage   
Rotary Oil or Gas Well  **Gas**  
(KIND)

38° 45'

Quadrangle Winfield 8-52

Permit No. Put. -755

WELL RECORD

Company Teavee Oil & Gas, Inc.  
Address 1901 Kanawha Valley Building  
Farm A. B. McCulloch Acres 252  
Location (waters) Little Hurricane Creek 542  
Well No. 1-TV. 84 Elev. 2591  
District Scott County Putman  
The surface of tract is owned in fee by Same  
Address  
Mineral rights are owned by Same  
Address

Drilling commenced April 24, 1969  
Drilling completed June 21, 1969  
Date Shot From To  
With

Open Flow 2/10ths Water in One Inch  
/10ths Merc. in Inch  
Volume Cu. Ft.  
Rock Pressure lbs. hrs.  
Oil bbls., 1st 24 hrs.

WELL ACIDIZED (DETAILS)

WELL FRACTURED (DETAILS) 20/40 Sand, 30,000#, 777bbl

RESULT AFTER TREATMENT (Initial open Flow or bbls.) 20/10th. Water in one inch & H2O 48,000 48 MCF6PD

ROCK PRESSURE AFTER TREATMENT HOURS

Fresh Water Feet Salt Water Feet

Producing Sand Berca 2084-25 Depth

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			
16			Kind of Packer
13			
10	58'	58'	Size of
8 1/4			
6 5/8	1,741' 10"	1,741' 10"	Depth set
4 1/2	2,107	2,107	
3			Perf. top 2,084
2			Perf. bottom 4 holes
Liners Used			Perf. top
			Perf. bottom

Attach copy of cementing record.  
CASING CEMENTED 10" SIZE 58 No. Ft. Date  
Amount of cement used (bags) Well cemented 1 1/2 26 sacks up from plug at 2162 Service, Inc.  
Name of Service Co. Service, Inc.  
COAL WAS ENCOUNTERED AT None FEET INCHES  
FEET INCHES FEET INCHES  
FEET INCHES FEET INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth	Remarks
Surface			0	2			
Red Rock			2	15			
Sand Blue Mud			15	27			
Sand Stone			27	35			
Red Rock			35	45			
Blue Rock			45	90			
Red Rock			90	100			
Blue Rock			100	370			
Sand			370	415			
Blue Rock			415	440			
Sand			440	470			
Slate			470	530			
Sand			530	555			
Slate			555	585			
Sand			585	680			
Slate			680	705			
Sand			705	745			
Slate			745	780			
Sand			780	805			
Slate			805	820			
Sand			820	840			
Slate			840	875			
Sand			875	960			
Slate			960	995			
Sand			995	1,015			
Sand			1,050	1,100			
Slate			1,100	1,130			
Sand (Salt Sand)			1,130	1,360			
Slate & Lime (Little Lime)			1,360	1,397			

See PI Comp. card

RECEIVED  
DEC 23 1969  
OIL & GAS DIVISION  
DEPT. OF MINES

Formation	Color	Hard or Soft	Top <sup>4</sup>	Bottom	Oil, Gas or Water	Depth Found	Remarks
Big Lime			1,397	1,565	35'		
Slate			1,565	1,600	36'		
Sand (Injun)			1,600	1,636			
Slate & Sand			1,636	1,650			
Slate & Shells			1,650	2,055			
Coffee Shale			2,055	2,070			
Berea Grit			2,070	2,097			
Slate & Shells			2,097	3,143			
Shale Light	Brown		3,143	3,190			
Slate White			3,190	3,272			
Brown Shale			3,272	3,380			
Slate			3,380	3,442			
Shale			3,442	3,490			
Slate			3,490	3,504			
Shale			3,504	3,690			
Slate			3,690	3,999			
Brown Shale (Marcellous)			3,999	4,250			
Corniferous	Onondaga		4,245	4,370	4245 592 3653		

Date....., 19.....

APPROVED....., Owner

By..... (Title)