

LATITUDE

LONGITUDE

7'5 OGIS topo location

7.5' loc _____ 15' loc _____
(calc.) _____

Company Thompkins Fuel Co

Farm GL Harvey I

Quad _____

County Putnam

District Scott

WELL LOCATION MAP

File No. 079-70009

Scott District, Putnam County, W. Va.

Completed, April 15, 1928.

Authority, Tompkins Fuel Co.

Elevation, 703' L. On 51 acres. Started spudding, March 17, 1928.

13" conductor, 16'; 8 $\frac{1}{4}$ " casing, 175' (pulled); 6-5/8" casing,
1498' (8' in Big Lime); 3" tubing, 1684'.

According to newspapers well made 4,500,000 cu. ft. of gas.

Drilled by Jones, Fink & Buckner, contractors.

	Top.	Bottom.
Surface	0	12
Red rock	12	90
Slate and lime	90	120
Red rock	120	205
Slate and lime	205	448
Sand	448	488
Slate	488	498
Sand (water, 498'; 1 bailer per hour)	498	528
Slate	528	600
Sand (water, 675'; little more than needed to drill)	600	675
Slate and shells	675	890
Sand	890	930
Slate and shell	930	1035
Sand	1035	1055
Slate	1055	1058
Salt Sand	1058	1412
Slate	1412	1417
Lime	1417	1430
Slate	1430	1445
Little Lime	1445	1469
Pencil Cave	1469	1473
Lime, black	1473	1479
Slate	1479	1489
Big Lime (SLM, 1511'; gas, 1561-1562' and 1591')	1489	1648
Slate	1648	1678
Big Injun Sand (gas, 1680-1684')	1678	1684
Total depth		1684

Casing Set: 13" wood conductor 16 ft.
8 $\frac{1}{4}$ " Casing (Shoe) 175 ft. 5 in.
6-5/8" Casing (Midget B. H. Packer), 1498 ft. 2 in. - 8 ft.
in Big Lime.
3" Tubing 1684 ft. - on bottom,
with 6" nipple, wood plug driven in, and cage adjoining B. H. packer
at set 1639 ft. in hard B. Lim.
Bradenhead 3 x 6-5/8" shutting in B. Lime. Anchored to 6-5/8".
Casing pulled: 8 $\frac{1}{4}$ " casing, 175 ft. 5 in.