



New Location X
 Drill Deeper
 Assignment

Company	COLUMBIAN CARBON COMPANY		
Address	BOX 873 CHARLESTON, W.VA.		
Farm	SAMUEL G. DAMRON		
Tract	Acres	Lease No.	
	455	C 2972	
Well (Farm) No.	1	Serial No.	
Elevation (Spirit Level)	2038.14'		
Quadrangle	ECCLES 5	S 525	W 220
County	RALEIGH	District	CLEAR FORK
Engineer	C. A. Brantman		
Engineer's Registration No.	683		
File No.	Drawing No.	W/35/48	
Date	JULY 16, 1948. Scale 1" = 1000'		

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. RAL-130

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500. latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.

6-6 248

WEST VIRGINIA DEPARTMENT OF MINES
OIL & GAS DIVISION
W E L L R E C O R D

Permit No. Ral 130

Gas Well
CASING & TUBING

Eccles Quad.			
Company	Columbian Carbon Company		
Address	Box 873, Charleston 23, W.Va.	40#13 3/8	31'7 31'7
Farm	S.G.Damron Acres 455	10 3/4 40#	524'6 Pld.
Location	Slick Rock Branch	8 1/2 24#	1759'6 Same
Well No.	1 GW 1088 Elev. 2038.14 G	6 5/3 24#	2781'5 Pld.
District	Clear Fork Raleigh County	2 3/8 4.7#	2396'1 Same
Surface	S.G.Damron et al, 157 Poplar St. with 2" cage St. Albans, W.Va.		Midget B.H.Packer Size 8 5/8" Depth 1753' SLM
Mineral	Same (for further addresses contact C.C.Co.)		
Commenced	9-25-48		
Completed	3-25-49		Coal at 1241' 48"
Not shot			
Open flow	2/10ths W in 2"		
Volume	60,000 C.F.?		
Rock Pressure	400 lbs. 48 hrs.		
Fresh Water	424'H.F.		
Salt Water	2432' 500' 24 hrs.		

Surface	0	25	Slate	2194	2213
Stone	25	61	Red Rock	2213	2253
Slate	61	114	Slate	2253	2276
Sand	114	138	Lime	2276	2294
Slate	138	184	Sand <i>un. number?</i>	2294	2342
Sand	184	226	Lime <i>L. number?</i>	2342	2400
Slate	226	238	Sand 2453 DLM-2453 SLM	2400	2460
Lime	238	250	Lime ~ 60' <i>?</i>	2460	2966
Slate	250	295	Red Sand - <i>Enjus? Mc</i>	2966	3020
Sand	295	433	Lime	3020	3050
Slate	433	521	Sand 3169 DLM-3160 SLM	3050	3134 <i>well</i>
Sand	521	530	Slate & Shells	3184	3301
Slate	530	556	Total depth		3301
Lime	556	605			
Slate & Shells	605	630	Gas 1760' show		
Sand	630	756	GAS PAYS:		
Slate & Shells	756	832	2166' 2/10 W 2" 60 MCF?		
Sand	832	970	2188.94 4/10 W 2" 84 MCF		
Slate	970	975	2331' 174 MCF		
Sand	975	1012			
Slate & Shells	1012	1021	CEMENT RECORD:		
Sand	1021	1225	12-13-48 10 1/2" casing- not aquagelled.		
Slate	1225	1241	1.7.49 8 5/8" casing- ran 21 sacks of		
Coal	1241	1245	aquagel. No returns.		
Sand	1245	1269	3-12-49 6 5/8" casing- not aquagelled.		
Lime	1269	1281	C.C.Co.Crew		
Sand	1281	1305			
Slate & Shells	1305	1330			
Sand	1330	1353			
Gritty Lime	1353	1373			
Red Rock	1373	1378			
Gritty Lime	1378	1393			
Sand	1393	1440			
Red Rock	1440	1507			
Slate	1507	1530			
Lime	1530	1594			
Slate	1594	1745			
Sand 1744' DLM-1753' SLM	1745	1790			
Lime	1790	1834			
Red Rock	1834	1893			
Slate & Shells	1893	1930			
Red Rock	1930	1940			
Lime	1940	1950			
Red Rock	1950	1975			
Sand	1975	1992			
Red Rock	1992	2050			
Slate	2050	2080			
Sand	2080	2174			
Red Rock	2174	2182	<i>U. HARTON?</i>		
Sand	2182	2194			