



HAUGHT-LAMBERT NO. 8 WELL.

1007A

Murphy District, Ritchie County, W. Va.  
 By Valley Steel Products Co., 124 Sidney St., St. Louis, Mo.  
 Abandoned under permit Rit-.....-A7  
 On 265 acres, on Dutchman Run.  
 Elevation, 882' L.  
 Surface owned by Joshua Haught and minerals by Joshua Haught et al.,  
 Taverner Ave., Vienna, W. Va.  
 Drilling commenced Dec. 1919; completed Jan. 7, 1920.  
 Shot Jan. 7, 1920, at 1684-1710', with 90 qts. glycerine.  
 No water reported.  
 10" casing, 317'; 8" casing, 988' (pulled); 6" casing, 1526'; 2" tubing, 1708'.  
 Oil well. Record to Dept. of Mines dated Nov. 4, 1950.  
 Record to RCF from Mrs. Griffith Aug. 17, 1951. Old File No. 899.  
 This well was drilled by South Penn Oil Co. (This is copy of well  
 log furnished by South Penn. Co.)

	Top.	Bottom.
Usual formations to Cobel rock	840	860
Slate, soft	860	985
Sand and slate, regular, medium	985	1280
Sand, white, gray, medium	1280	1380
Slate, black, soft	1380	1518
Gas Sand, gray, hard	1518	1535
Slate and shells, gray, black, medium	1535	1630
Salt Sand, gray, white, medium-hard	1630	1718
(oil, 1685-1710')		
Total depth		1718



7:00 - 7:30

1st on left up roller  
May 16<sup>th</sup> 51

STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION

899

WELL RECORD

Permit No. 917-1007A (drilled in 1920)

Oil or Gas Well oil  
(KIND)

Company VALLEY STEEL PRODUCTS CO  
 Address 124 Sidney St., St. Louis, Mo.  
 Farm HAUGHT-LAMBERT Acres 265  
 Location (waters) Dutchman Run  
 Well No. 8 Elev. 882  
 District MURPHY County RITCHIE  
 The surface of tract is owned in fee by Joshua Haught  
 Address \_\_\_\_\_  
 Mineral rights are owned by Joshua Haught et al  
Tavener Ave Address Vienna, W. Va.  
 Drilling commenced December 1919  
 Drilling completed January 7th, 1920  
 Date Shot Jan 7th From 1684 To 1710  
 With 90 quarts glycerine  
 Open Flow /10ths Water in none reported Inch  
/10ths Merc. in Inch  
 Volume none taken Cu. Ft.  
 Rock Pressure none taken lbs. hrs.  
 Oil do not know bbls., 1st 24 hrs.  
 Fresh water none reported feet  
 Salt water none reported feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer
16			
13			
10	317	none	Size of
8 1/4	988	none	
6 3/8	1526	1526	Depth set
5 3/16			
3			Perf. top
2		1708	Perf. bottom
Liners Used	none		Perf. top
			Perf. bottom

CASING CEMENTED	SIZE	No. Ft.	Date
COAL WAS ENCOUNTERED AT			
		FEET	INCHES
		FEET	INCHES
		FEET	INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Usual formations to Gobel Rock			840	860			
Slate	none	given soft	860	985			
Sand and slate	reg.	medium	985	1280			
Sand	white						
	grey	medium	1280	1380	none		
Slate	blk	soft	1380	1518			
Gas sand	grey	hard	1518	1535			
Slate & shells							
	grey blk	medium	1535	1630			
Salt sand	grey white	mod hard	1630	1718			
Oil found			1685	1710			
TOTAL DEPTH						1718TD	



Ray Laderman  
P. J. Daily

1300 ft  
4 5/8

1526  
1300  
226

