


LATITUDE 38° 47' 30"

LONGITUDE 81° 27' 30"



7'5 OGIS topo location

7.5' loc \_\_\_\_\_ 15' loc \_\_\_\_\_  
 (calc.) \_\_\_\_\_

Company \_\_\_\_\_

Farm \_\_\_\_\_

Quad Peniel 7 1/2'

County Roane

District Curtis

WELL LOCATION MAP

File No. 087-101A



101A

Curtis District, Roane County, W. Va.

By United Fuel Gas Co., Charleston, W. Va.

On 82 acres, mineral rights owned by Geo. L. Parsons et al.,  
Gay, W. Va.

Drilled previous to June 1, 1929.

Elevation, 1006' B.

13" casing, 32'; 10", 670'; 6-5/8", 2170'.

Anchor packer, 3 x 6-5/8 x 16, set at 2224'.

Casing perforated at 2629-2639 and 2590-2600'.

No coal was encountered.

Abandonment reported to Dept. of Mines Jan. 15, 1935.

Well was shot at 2572-2581'.

No record of water.

Producing hole.

	Top.	Bottom.	Thickness.
Conductor	0	- 31	31
Red rock	31	- 55	24
Sand	55	- 95	40
Slate and mud	95	- 115	20
Sand and lime	115	- 128	13
Slate and red rock	128	- 225	97
Slate and red rock	225	- 310	85
Sand	310	- 342	32
Sand, slate, mud, and shells	342	- 560	218
Pittsburgh Sand	560	- 670	110
Lime, shells, and slate	670	- 750	80
Sand	750	- 785	35
Slate and red rock	785	- 1060	275
Little Dunkard Sand	1060	- 1100	40
Black sand	1100	- 1110	10
Red rock	1110	- 1125	15
Slate and shells	1125	- 1150	25
Slate and red rock	1150	- 1190	40
Big Dunkard Sand	1190	- 1285	95
Shells and slate	1285	- 1365	80
Gas Sand	1365	- 1410	45
Slate	1410	- 1420	10
Sand	1420	- 1465	45
Black shale	1465	- 1506	41
Sand	1506	- 1570	64
Slate and shells	1570	- 1628	58
Sand	1628	- 1650	22
Slate and shells	1650	- 1725	75
Rotten lime	1725	- 1750	25
Slate and shells	1750	- 1790	40
Salt Sand	1790	- 2085	295
Sandy lime	2085	- 2125	40
Big Lime	2125	- 2156	31
Big Injun Sand	2156	- 2169	13
Slate and shells	2169	- 2574	405
Berea Grit, to bottom	2574	- 2593	19