


LATITUDE 38° 45'



151° 18' LONGITUDE

7'5 OGIS topo location

7.5' loc \_\_\_\_\_ 15' loc \_\_\_\_\_  
 \_\_\_\_\_ (calc.) \_\_\_\_\_

Company \_\_\_\_\_

Farm \_\_\_\_\_

Quad Walton (NE)

County Roane

District Smithfield

WELL LOCATION MAP

File No. 087-780A



780A

Smithfield District, Roane County, W. Va.

By The Ohio Fuel Oil Co.

Rig commenced Jan. 8, 1911, and completed Jan. 17, 1911.

Drilling commenced March 11, 1911, and completed April 21, 1911.

Contractor, Pratt Drilling Co.

Drillers, Joe Triplett and Bruce Duncan.

Conductor, 16'.

Well shot April 24, 1911, with 40 qts.

6-5/8" threads, 16' 11".

Examined and approved by E. H. Lange, Foreman.

Copied from Record Books of The Ohio Fuel Oil Co. by C. E. Krebs,

Nov. 9, 1911.

see microfilm for well record &amp; Plot

	Top.	Bottom.	Thickness.
Conductor	0	- 16	16
Red rock	16	- 40	24
Sandy lime	40	- 130	90
Slate and red rock	130	- 280	150
Sand	280	- 345	65
Red rock and sandy lime	345	- 850	505
Lime shells	850	- 890	40
Big Dunkard Sand	890	- 1015	25
Broken slate	1015	- 1090	75
Sand and lime	1090	- 1160	70
Broken slate	1160	- 1280	120
Sand and lime	1280	- 1510	230
Broken slate	1510	- 1560	50
Salt Sand (water, 1605')	1560	- 1885	325
Little Lime	1885	- 1915	30
Pencil Cave	1915	- 1923	8
Big Lime	1923	- 2037	114
Big Injun Sand (first oil, 2055-2057')	2037	- 2082	45
Total depth		2088	

(197)