

PORM OG-6

## STATE OF WEST VIRGINIA DEPARTMENT OF MINES

JUN 1 5 1972

## AFFIDAVIT OF PLUGGING AND FILLING WELL

| COAL OPERATOR OR OWNER  ADDRESS  COAL OPERATOR OR OWNER  COAL OPERATOR OR OWNER  APPRESS  APPRESS  APPRESS  EMMRA C. A.  | irgil B. Harr<br>nat they are experie<br>Roy G. Hildra<br>filling the above of<br>19.72, and that t  | CATION  List  Coult  Coult  Coult  List  Coult  Co | 5325 72_ trict unty arm 25185   |
|--|--|--|---|
| COAL OPERATOR OR OWNER  ADDRESS  ADDRESS  ADDRESS  ADDRESS  ADDRESS  ADDRESS  ADDRESS  APPERATOR OR PROPERTY OWNER  OVAPA, "FACT VIRGINIA, ADDRESS  STATE INSPECTOR SUPERVISING PLUGGING Fred Burde  AFFIDAVIT  STATE OF WEST VIRGINIA,  County of ROANE  Thomas Horper and V being first duly sworn according to law depose and say t plugging and filling oil and gas wells and were employed by well operator, and participated in the work of plugging and was commenced on the 20th day of April and filled in the following manner:  SAND OR ZONE RECORD  FILLING MATERIAL  PORMATION  PULLED IN 1730' to 1720'.  Culled on 1718' of 6-5/8" Casing. Would the following in the part of the pulled 1650' of 6-5/8" casing in bridge at 1650'. Three bags of neat "illed with Clay to 1150'; Crushed Stone from 1140' to 1130'; sealing off Salt San eft 598' of 10" casing in hole.  Set a bridge in 10" casing at 530'. Fill of 520'; Cement from 520' to 465'; Caly for the part of the principal of the | leston, West  COMPLETE ADE  BY 25.  WELL AND LO  Geary  Roans  Co. 1234  Clearinda Hil  tte, Sissonvi  irgil B. Harr  nat they are experie  Roy G. Hildre  filling the above w  19.72., and that t   | CATION  Dist  Cou  Let W. Va.  18  18  19  Cou  Let W. Va.  18  Cou  Let W. Va.  Casing  Casing  Casing  Casing  | trict unty arm 25185  |
| ADDRESS  ADDRESS  ADDRESS  ADDRESS  APPRESS  APPRESS  APPRESS  Well I  ADDRESS  STATE INSPECTOR SUPERVISING PLUGGING Fred Burde  AFFIDAVIT  STATE OF WEST VIRGINIA,  County of ROANE  Thomas Hemper and V  being first duly sworn according to law depose and say t  plugging and filling oil and gas wells and were employed by well operator, and participated in the work of plugging and filled in the following manner:  EAND OR ZONE RECORD  PILLING MATERIAL  PORMATION  PORMATION  PORMATION  Culled 1.35' of 2" tubing.  Clilled with Clay from 1/21' to 1740'; Cru  ement from 1730' to 1720',  ulled on 1718' of 6-5/8" Casing. Would t 1650' and pulled 1650' of 6-5/8" casin  et bridge at 1650'. Three bags of neat  Clilled with Clay to 1150'; Crushed Stone  rom 1140' to 1130'; sealing off Salt San  eft 598' of 10" casing in hole.  et a bridge in 10" casing at 530'. Fill o 520'; Cement from 520' to 465'; Caly f  | COMPLETE ADE  BY 25.  WELL AND LO  Geary  Roans  Co. 1234  Clearinda Hil  tte, Sissonvi  irgil B. Harri  nat they are experie  Roy G. Hildre  filling the above was a filling that they  PLUGS USED  | CATION  Dist  Cou  Lie W. Vo.  Lie Worl  eth & Son  well, that said whe well was plug  CASING  Case  Pulled Lie  | trict unty arm 25185  |
| ADDRESS  LEASE OR PROPERTY OWNER  OVERES OR PROPERTY OWNER  OVERES OF PROPERTY OWNER  AFFIDAVIT  STATE INSPECTOR SUPERVISING PLUGGING Fred Burde  AFFIDAVIT  STATE OF WEST VIRGINIA,  County of ROANE  Thomas Herper and V  being first duly sworn according to law depose and say t  plugging and filling oil and gas wells and were employed by well operator, and participated in the work of plugging and was commenced on the 20th day of April and filled in the following manner:  SAND OR ZONE RECORD FILLING MATERIAL  PORMATION  PULLED OF 25 of 2" tubing.  "Illed With Clay from 1921" to 1740"; Cru ement from 1730" to 1720".  "Ulled on 1718" of 6-5/8" Casing. Would t 1650" and pulled 1650" of 6-5/8" casin set bridge at 1650". Three bags of neat illed with Clay to 1150"; Crushed Stone rom 1140" to 1130"; sealing off Salt San eft 598" of 10" casing in hole, est a bridge in 10" casing at 530". Fill n 520"; Cement from 520" to 465"; Caly f   | Geary Reary Reary Roans  | is enced in the worketh & Son well, that said whe well was plug  | trict unty  arm 25185   |
| STATE INSPECTOR SUPERVISING PLUGGING Fred Burde  STATE INSPECTOR SUPERVISING PLUGGING Fred Burde  AFFIDAVIT  STATE OF WEST VIRGINIA,  County of ROANE  Thomas Horper and V being first duly sworn according to law depose and say t plugging and filling oil and gas wells and were employed by well operator, and participated in the work of plugging and was commenced on the 20th day of April and filled in the following manner:  SAND OR ZONE RECORD  FILLING MATERIAL  FORMATION  PULLED 1.35' of 3" tubing.  Sulled 1.35' of 6-5/8" Casing. Would to 1650' and pulled 1650' of 6-5/8" casin set bridge at 1650'. Three bags of neat Silled with Clay to 150'; Crushed Stone From 1140' to 1130'; sealing off Salt San seft 508' of 10" casing in hole. Set a bridge in 10" casing at 530'. Fill n 520'; Cement from 520' to 465'; Caly f  | Geary  Roans  10.1234  Clearinda Hilter, Sissonvi  irgil B. Harr  nat they are experience Roy G. Hildre  filling the above was a size a kind   | Distance of the work well, that said whe well was plug   | k of vork   |
| STATE INSPECTOR SUPERVISING PLUGGING Fred Burde  STATE INSPECTOR SUPERVISING PLUGGING Fred Burde  AFFIDAVIT  STATE OF WEST VIRGINIA,  County of ROANE  Thomas Harper and V being first duly sworn according to law depose and say t plugging and filling oil and gas wells and were employed by well operator, and participated in the work of plugging and was commenced on the 20th day of April and filled in the following manner:  SAND OR ZONE RECORD  PULLING MATERIAL  PORMATION  PULLIN | Clearinda Hil<br>tte, Sissonvi<br>irgil B. Herri<br>at they are experie<br>Roy G. Hildre<br>filling the above w<br>1972, and that t  | is enced in the worketh & Son well, that said whe well was plug  | k of vork   |
| STATE INSPECTOR SUPERVISING PLUGGING Fred Burde  AFFIDAVIT  STATE OF WEST VIRGINIA,  County of ROANE  Thomas Happer and V being first duly sworn according to law depose and say t plugging and filling oil and gas wells and were employed by well operator, and participated in the work of plugging and was commenced on the 20th day of April and filled in the following manner:  SAND OR ZONE RECORD FILLING MATERIAL  PORMATION  Pulled 1.35' of 3" tubing.  Tilled with Clay from 1921' to 1740'; Cru Sement from 1730' to 1720'.  Pulled on 1718' of 6-5/8" Casing. Would t 1650' and pulled 1650' of 6-5/8" casin set bridge at 1650'. Three bags of neat Tilled with Clay to 1150'; Crushed Stone rom 1140' to 1130'; sealing off Salt San seft 598' of 10' casing in hole. set a bridge in 10" casing at 530'. Fill n 520'; Cement from 520' to 465'; Caly f   | ingil B. Harriat they are experient they are experient filling the above to 19.72, and that they are a kind  | is enced in the worketh & Son well, that said whe well was plug  | k of vork   |
| STATE INSPECTOR SUPERVISING PLUGGING Fred Burde  AFFIDAVIT  STATE OF WEST VIRGINIA,  County of ROANE  Thomas Herper and V being first duly sworn according to law depose and say t plugging and filling oil and gas wells and were employed by well operator, and participated in the work of plugging and was commenced on the 20th day of April and filled in the following manner:  PAND OR ZONE RECORD  PILLING MATERIAL  PORMATION  PULLED 1 35' of 2" tubing.  "Illed with Clay from 1921' to 1740'; Cru dement from 1730' to 1720'.  "Ulled on 1718' of 6-5/8" Casing. Would t 1650' and pulled 1650' of 6-5/8" casin det bridge at 1650'. Three bags of neat "Illed with Clay to 1150'; Crushed Stone Trom 1140' to 1130'; sealing off Salt San eft 598' of 10' casing in hole.  "et a bridge in 10" casing at 530'. Fill n 520'; Cement from 520' to 465'; Caly f   | irgil B. Harrinat they are experied filling the above to 19.72, and that they are experied filling the above to 19.72, and that they are experied filling the above to 19.72.  | is enced in the worketh & Son well, that said whe well was plug  | k of vork   |
| STATE INSPECTOR SUPERVISING PLUGGING. Fred Burde  AFFIDAVIT  STATE OF WEST VIRGINIA,  County of ROANE  Thomas Harper and V being first duly sworn according to law depose and say t plugging and filling oil and gas wells and were employed by well operator, and participated in the work of plugging and was commenced on the 20th day of April and filled in the following manner:  SAND ON ZONE RECORD  PORMATION  PORMATION  PULLING MATERIAL  PULI | irgil B. Harrinat they are experied filling the above to 19.72, and that they are experied filling the above to 19.72, and that they are experied filling the above to 19.72.  | is enced in the work eth & Son well, that said w he well was plug  | 25185 k of vork   |
| STATE INSPECTOR SUPERVISING PLUGGING Fred Burde  AFFIDAVIT  STATE OF WEST VIRGINIA,  County of ROANE  Thomas Hemper and V being first duly sworn according to law depose and say t plugging and filling oil and gas wells and were employed by well operator, and participated in the work of plugging and was commenced on the 20th day of April and filled in the following manner:  SAND OR ZONE RECORD  PILLING MATERIAL  FORMATION  PULLED 1.35' of 2" tubing.  "Illed with Clay from 1.021' to 1740'; Cru ement from 1730' to 1720'.  "ulled on 1718' of 6-5/8" Casing. Would t 1650' and pulled 1650' of 6-5/8" casin et bridge at 1650'. Three bags of neat filled with Clay to 1150'; Crushed Stone rom 1140' to 1130'; sealing off Salt San eft 598' of 10" casing in hole. et a bridge in 10" casing at 530'. Fill a 520'; Cement from 520' to 465'; Caly f   | irgil B. Harriat they are experienced filling the above of the state o | is enced in the work eth & Son well, that said w he well was plug  | 25185 k of vork   |
| STATE INSPECTOR SUPERVISING PLUGGING Fred Burde  AFFIDAVIT  STATE OF WEST VIRGINIA,  County of ROANE  Thomas Hamper and V being first duly sworn according to law depose and say t plugging and filling oil and gas wells and were employed by well operator, and participated in the work of plugging and was commenced on the 20th day of April and filled in the following manner:  SAND OR ZONE RECORD FILLING MATERIAL  PORMATION  Pulled 1.35' of 2" tubing.  Cilled with Clay from 1.021' to 1740'; Cru ement from 1730' to 1720'.  Pulled on 1718' of 6-5/8" Casing. Would t 1650' and pulled 1650' of 6-5/8" casin let bridge at 1650'. Three bags of neat filled with Clay to 1150'; Crushed Stone from 1140' to 1130'; sealing off Salt San left 598' of 10" casing in hole.  Let a bridge in 10" casing at 530'. Fill on 520'; Cement from 520' to 465'; Caly f  | irgil B. Harriat they are experienced filling the above of the state o | is enced in the work eth & Son well, that said w he well was plug  | k of<br>vork<br>ged   |
| County of ROANE  The mas He mper and V being first duly sworn according to law depose and say t plugging and filling oil and gas wells and were employed by well operator, and participated in the work of plugging and filled in the following manner:  SAND OR ZONE RECORD  PILLING MATERIAL  PORMATION  PULLED 135' of 2" tubing.  Tilled with Clay from 1921' to 1740'; Cru ement from 1730' to 1720'.  Pulled on 1718' of 6-5/8" Casing. Would t 1650' and pulled 1650' of 6-5/8" casing et bridge at 1650'. Three bags of neat 111ed with Clay to 1150'; Crushed Stone from 1140' to 1130'; sealing off Salt San eft 598' of 10" casing in hole.  Set a bridge in 10" casing at 530'. Fill a 520'; Cement from 520' to 465'; Caly f  | irgil B. Harr<br>nat they are experie<br>Roy G. Hildra<br>filling the above of<br>19.72, and that t  | is enced in the worl eth & Son well, that said w he well was plug  CASING  | k of<br>vork<br>ged   |
| County of ROANE  Thomas Harper and V being first duly sworn according to law depose and say to plugging and filling oil and gas wells and were employed by well operator, and participated in the work of plugging and was commenced on the 20th day of April and filled in the following manner:  **AND OR ZONE RECORD FILLING MATERIAL PORMATION  PULLED 1.35' of 3" tubing.  Cilled with Clay from 1921' to 1740'; Crusted in 1750' and pulled 1650' of 6-5/8" Casing. Would be 1650' and pulled 1650' of 6-5/8" casing in hole.  Cilled with Clay to 1150'; Crusted Stone from 1140' to 1130'; sealing off Salt San aft 598' of 10' casing in hole.  Cet a bridge in 10" casing at 530'. Fill of 520'; Cement from 520' to 465'; Caly for the sealing of the casing at 530'.   | PLUES USED   | enced in the worketh & Son well, that said whe well was plug   | york<br>ged   |
| Thomas Harper and V being first duly sworn according to law depose and say to plugging and filling oil and gas wells and were employed by well operator, and participated in the work of plugging and was commenced on the 20th day of April and filled in the following manner:  SAND OR ZONE RECORD FILLING MATERIAL FORMATION  PULLED 1.35' of 3" tubing.  Pulled 1.35' of 3" tubing.  Pulled with Clay from 1921' to 1740'; Crusted on 1718' of 6-5/8" Casing. Would to 1650' and pulled 1650' of 6-5/8" casing et bridge at 1650'. Three bags of neat lilled with Clay to 1150'; Crusted Stone from 1140' to 1130'; sealing off Salt San seft 598' of 10" casing in hole.  Let a bridge in 10" casing at 530'. Fill of 520'; Cement from 520' to 465'; Caly formation of the sealing of to 465'; Caly formation of the sealing of the seali | PLUES USED   | enced in the worketh & Son well, that said whe well was plug   | york<br>ged   |
| Thomas Harper and V being first duly sworn according to law depose and say to plugging and filling oil and gas wells and were employed by well operator, and participated in the work of plugging and was commenced on the 20th day of April and filled in the following manner:  SAMD OR ZONE RECORD FILLING MATERIAL FORMATION  PULLED 1.35' of 3" tubing.  Pulled 1.35' of 3" tubing.  Pulled with Clay from 1921' to 1740'; Crusted on 1718' of 6-5/8" Casing. Would to 1650' and pulled 1650' of 6-5/8" casing et bridge at 1650'. Three bags of neat illed with Clay to 1150'; Crusted Stone from 1140' to 1130'; sealing off Salt San eft 598' of 10' casing in hole.  Let a bridge in 10" casing at 530'. Fill of 520'; Cement from 520'; Caly f   | PLUES USED   | enced in the worketh & Son well, that said whe well was plug   | york<br>ged   |
| plugging and filling oil and gas wells and were employed by well operator, and participated in the work of plugging and was commenced on the 20th day of April and filled in the following manner:  SAND OR ZONE RECORD  PILLING MATERIAL  PORMATION  PULLING MATERIAL  PORMATION  PULLING WATERIAL  PORMATION  PULLING MATERIAL  PULLING | PLUES USED   | enced in the worketh & Son well, that said whe well was plug   | york<br>ged   |
| plugging and filling oil and gas wells and were employed by well operator, and participated in the work of plugging and was commenced on the 20th day of April and filled in the following manner:  **CANNO OR ZONE RECORD   PILLING MATERIAL    **PORMATION   PULLING MATERIAL    **PORMATION   PULLING MATERIAL    **PORMATION   PILLING MATERIAL    **P | Roy G. Hildre filling the above we also that the state of | eth & Son well, that said w he well was plug  CASING  CASING   | york<br>ged   |
| plugging and filling oil and gas wells and were employed by well operator, and participated in the work of plugging and was commenced on the 29th day of April and filled in the following manner:  ***PORMATION**  ***PORMATION**  ***Ulled 1.35' of 3" tubing.*  illed with Clay from 1921' to 1740'; Cru ement from 1730' to 1720'.  ***ulled on 1718' of 6-5/8" Casing. Would to 1650' and pulled 1650' of 6-5/8" casing et bridge at 1650'. Three bags of neat illed with Clay to 1150'; Crushed Stone rom 1140' to 1130'; sealing off Salt San eft 598' of 10' casing in hole.  et a bridge in 10" casing at 530'. Fill of 520'; Cament from 520' to 465'; Caly form 520'; Caly form 520 | Roy G. Hildre filling the above we also that the state of | eth & Son well, that said w he well was plug  CASING  CASING   | york<br>ged   |
| well operator, and participated in the work of plugging and was commenced on the 20th day of April and filled in the following manner:  **MAND OR ZONE RECORD  | plues used   | well, that said whe well was plug  | ged   |
| was commenced on the 20th day of April and filled in the following manner:    AND OR ZONE RECORD   | PLUGS USED   | CASING   | ged   |
| PILLING MATERIAL  PORMATION  ulled 1.35' of 2" tubing.  illed with Clay from 1921' to 1740'; Cru ement from 1730' to 1720'.  ulled on 1718' of 6-5/8" Casing. Would t 1650' and pulled 1650' of 6-5/8" casin et bridge at 1650'. Three bags of neat illed with Clay to 1150'; Crushed Stone rom 1140' to 1130'; sealing off Salt San eft 598' of 10' casing in hole.  et a bridge in 10" casing at 530'. Fill o 520': Cement from 520' to 465'; Caly f   | PLUGS USED   | CASING CSG PULLED L  | C26<br>EFT IN   |
| ulled 1.35' of 3" tubing. illed with Clay from 1921' to 1740'; Cru ement from 1730' to 1720'. ulled on 1718' of 6-5/8" Casing. Would t 1650' and pulled 1650' of 6-5/8" casin et bridge at 1650'. Three bags of neat illed with Clay to 1150'; Crushed Stone rom 1140' to 1130'; sealing off Salt San eft 598' of 10' casing in hole. et a bridge in 10" casing at 530'. Fill o 520': Cement from 520' to 465'; Caly f   | SIZE & KIND  | CSG<br>PULLED LI   | EFT IN  |
| ulled 1.35' of 3" tubing.  illed with Clay from 1921' to 1740'; Cru ement from 1730' to 1720',  ulled on 1718' of 6-5/8" Casing. Would t 1650' and pulled 1650' of 6-5/8" casin et bridge at 1650'. Three bags of neat illed with Clay to 1150'; Crushed Stone rom 1140' to 1130'; sealing off Salt San eft 598' of 10" casing in hole. et a bridge in 10" casing at 530'. Fill o 520': Cement from 520' to 465'; Caly f   |  | PULLED LE  | EFT IN  |
| illed with Clay from 1921' to 1740'; Cru ement from 1730' to 1720', ulled on 1718' of 6-5/8" Casing. Would t 1650' and pulled 1650' of 6-5/8" casing et bridge at 1650'. Three bags of neat illed with Clay to 1150'; Crushed Stone rom 1140' to 1130'; sealing off Salt Sangeft 598' of 10" casing in hole. et a bridge in 10" casing at 530'. Fill o 520'; Cement from 520' to 465'; Caly f  | hed Stone fr   |  |   |
| ement from 1730' to 1720'.  ulled on 1718' of 6-5/8" Casing. Would  t 1650' and pulled 1650' of 6-5/8" casin  et bridge at 1650'. Three bags of neat  illed with Clay to 1150'; Crushed Stone  rom 1140' to 1130'; sealing off Salt San  eft 598' of 10" casing in hole.  et a bridge in 10" casing at 530'. Fill  n 520': Cement from 520' to 465'; Caly f  | hed Stone fr   | an 1740' to  | 17301:  |
| dement from 1730' to 1720', bulled on 1718' of 6-5/8" Casing. Would t 1650' and pulled 1650' of 6-5/8" casing et bridge at 1650'. Three bags of neat filled with Clay to 1150'; Crushed Stone rom 1140' to 1130'; sealing off Salt Sangeft 598' of 10" casing in hole.  Let a bridge in 10" casing at 530'. Fill of 520'; Cement from 520' to 465'; Caly f   | Commence of the second  |  |   |
| et bridge at 1650'. Three bags of neat illed with Clay to 1150'; Crushed Stone rom 1140' to 1130'; sealing off Salt San eft 598' of 10" casing in hole. et a bridge in 10" casing at 530'. Fill o 520': Cement from 520' to 465'; Caly f   |  | 10   |   |
| et bridge at 1650'. Three bags of neat illed with Clay to 1150'; Crushed Stone rom 1140' to 1130'; sealing off Salt San eft 598' of 10" casing in hole. et a bridge in 10" casing at 530'. Fill o 520': Cement from 520' to 465'; Caly f   | ot pull. Ri  | bed casing   | in two  |
| illed with Clay to 1150; Crushed Stone rom 1140; to 1130; sealing off Salt San eft 598; of 10 casing in hole. et a bridge in 10 casing at 530; Fill o 520; Cement from 520; to 465; Caly f   | •  |  |   |
| illed with Clay to 1150; Crushed Stone rom 1140; to 1130; sealing off Salt San eft 598; of 10" casing in hole. et a bridge in 10" casing at 530; Fill a 520; Cement from 520; to 465; Caly f   | ement on top   | of bridge.   | ***************************************   |
| rom 1140° to 1130°; sealing off Salt San<br>eft 598° of 10° casing in hole.<br>et a bridge in 10" casing at 530°. Fill<br>o 520°; Cement from 520° to 465°; Caly f   | rom 1150 to  | 1140'; Ceme  | ent   |
| et a bridge in 10" casing at 530°. Fill<br>a 520°: Cement from 520° to 465°: Caly f  |  |  | Name and Association of the Control |
| o 520': Coment from 520' to 465': Caly f   |  |  |   |
| o 520°: Cement from 520° to 465°: Caly firected monument as prescribed by law.   | d with C ush   | d Stone fro  | om 530'   |
| rected monument as prescribed by law.  | om 4651 to St  | rface.   |   |
|  |  |  |   |
| - Committee of the comm |  |  |   |
|  | The second secon |  |   |
| COAL SEAMS   |  |  | Mantales Application of the second  |
|  | Partie Control | n of Monument  |   |
|  | One Joint of   | ···  | CONTRACTOR OF THE PROPERTY OF |
|  | United Push (  |  |   |
|  | No. 1234, dat  | ced May 4, ]   | 172.  |
|  |  |  |   |
| and that the work of plugging and filling said well was  | and the lease of   | 4th day  | - A   |
| May 19 72  |  | Ath day  | or or   |
|  |  |  |   |
| And further deponents saith not.   | 187220 Sept. 2 42 249  | 7  |   |
|  | 10 0 17  |  |   |
| Sworn to and subscribed before me this 25th day  | soil 14  | , 1972   | 2   |
| 2 2 A STATE OF THE | rgill St   |  |   |
| My commission expires:  August 5, 1,775.   | rgil Sty   | THE TO   |   |