

LATITUDE

3840

0218

LONGITUDE

→ 7.5' loc  
Kla 8/7/91

7.5' ~~0.975~~ topo location

7.5' loc	<u>1.975</u>	15' loc	_____
	<u>1.31W</u>	(calc.)	_____

Company \_\_\_\_\_

Farm \_\_\_\_\_

Elevation 815' Topo Est.

Quad Looneville

County \_\_\_\_\_

District Walton

WELL LOCATION MAP

File No. Roone 70113

70113

Walton District, Roane County, W. Va.

By The Ohio Fuel Oil Co.

Rig commenced April 6, 1910, and completed April 14, 1910.

Drilling commenced July 29, 1910, and completed Sept. 6, 1910.

Contractor, Pratt Drilling Co., Charleston, W. Va.

Drillers, Cyrus Dawson and Charley Devore.

Conductor, 16'.

Well shot Sept. 5, 1910.

15' 6" threads, 6-5/8".

	Top.	Bottom.	Thickness.
Conductor	0	- 16	16
Red rock	16	- 25	9
Sand	25	- 150	125
Slate	150	- 205	55
Red rock	205	- 230	25
White slate	230	- 240	10
Sand	240	- 300	60
Slate	330	- 640	310
White slate	640	- 655	15
Sand	655	- 690	35
Red rock	690	- 740	50
Big Dunkard Sand	740	- 815	75
Slate and coal	815	- 880	65
Lime	880	- 908	28
White slate	908	- 915	7
Sand	915	- 930	15
(water, 930-985')			
Black slate	985	- 1040	55
Sand	1040	- 1085	45
Slate	1085	- 1165	80
Sand	1165	- 1350	185
Lime	1350	- 1445	95
Slate	1445	- 1460	15
Salt Sand (gas, 1535'; hole full water, 1530')	1470		
Little Lime	1800		
Sand	1830		
Big Lime	1845		
Big Injun Sand (top pay, 1992'; bott. pay, 2012'; bot. shr. 2013')	1980	- 2014	34
Total depth		2016	

