

Latitude

39 35

→ 7.5' loc  
via 917195

80 57 30

Longitude

**Topo Location**

7.5' Loc. 0.59S      15' Loc. 0.59S  
0.47W                      (calc.) 2.69W

Company \_\_\_\_\_

Farm \_\_\_\_\_

15' Quad New Martinsville SW  
(sec.) \_\_\_\_\_

7.5' Quad Padon City \_\_\_\_\_

District Lincoln \_\_\_\_\_

**WELL LOCATION PLAT**

County 095      Permit 30774

McCOY HEIRS NO. 12 WELL.

774A

Lincoln District, Tyler County, W. Va.  
By St. Marys Pipe & Supply Co., St. Marys, W. Va.  
Abandoned under permit Tyl-.....-A?

On 214 acres.  
Elevation, ..... ' L.

Surface and minerals owned by McCoy Heirs, Sistersville, W. Va.  
10" casing, 116'; 8 1/4", 504'; 6 5/8", 1130'; 4-7/8", 1168'; 3 1/2" tubing, 100,  
on wall packer; all left in.

Oil well. Record to Dept. of Mines stamped April 7, 1952.  
Record to RCT from Mrs. Griffith Feb. 11, 1953. O.F.No.696.

	Top.	Bottom.
Top of sand		1430 - ....
(top of pay, 1450')		
(soft sand, 1450-1490')		
Total depth		1600

774A9.

Lincoln District, Tyler County, W. Va.  
Reno Oil Co.  
Elevation, 685' N.  
Oil and gas well.  
Survey No. 10.

7

	Top.	Bottom.
Big Injun Sand (oil and gas)	1430	
Total depth		1500

The gas in this area is more valuable than the oil at present. Production of oil is about 1 bbl. per week. Salt water is present in large quantity.



STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION

696

WELL RECORD

Permit No. T42-1774-A

Oil or Gas Well \_\_\_\_\_ (KIND)

Company St Marys Pipe & Supply Co.  
 Address St Marys W.Va.  
 Farm McCoy heirs Acres 214  
 Location (waters) \_\_\_\_\_  
 Well No. 18 Elev. \_\_\_\_\_  
 District Lincoln County Tyler  
 The surface of tract is owned in fee by McCoy heirs  
 Address Distorsville W.Va.  
 Mineral rights are owned by McCoy heirs  
 Address Distorsville W.Va.  
 Drilling commenced \_\_\_\_\_  
 Drilling completed \_\_\_\_\_  
 Date Shot \_\_\_\_\_ From \_\_\_\_\_ To \_\_\_\_\_  
 With \_\_\_\_\_  
 Open Flow \_\_\_\_\_ /10ths Water in \_\_\_\_\_ Inch  
 \_\_\_\_\_ /10ths Merc. in \_\_\_\_\_ Inch  
 Volume \_\_\_\_\_ Cu. Ft.  
 Rock Pressure \_\_\_\_\_ lbs. \_\_\_\_\_ hrs.  
 Oil \_\_\_\_\_ bbls., 1st 24 hrs.  
 Fresh water \_\_\_\_\_ feet \_\_\_\_\_ feet  
 Salt water \_\_\_\_\_ feet \_\_\_\_\_ feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer
16			
13			
10			Size of
8 1/4	110'	110'	Depth set
6%	504'	504'	
5 3/16	1150'	1150'	
3	1100'	1100'	Perf. top
2	100'	100'	Perf. bottom
Liners Used	Oil Well Packer		Perf. top
			Perf. bottom

CASING CEMENTED \_\_\_\_\_ SIZE \_\_\_\_\_ No. Ft. \_\_\_\_\_ Date \_\_\_\_\_

COAL WAS ENCOUNTERED AT \_\_\_\_\_ FEET \_\_\_\_\_ INCHES  
 \_\_\_\_\_ FEET \_\_\_\_\_ INCHES FEET \_\_\_\_\_ INCHES  
 \_\_\_\_\_ FEET \_\_\_\_\_ INCHES FEET \_\_\_\_\_ INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
		Top Sand 1450' Top Pay 1450' Soft Sand 1450' to 1400' Depth of Wells 1500'					



FEB 11 1953