

Proctor District, Wetzel County, W. Va.

By The Wiser Oil Co., Sistersville, W. Va.

On 88 acres, surface and mineral rights owned by Sanford Woods
et al., Proctor, W. Va.

Drilled under permit Wet-78, issued March 2, 1934.

Elevation, 677.4' L.

1 1/2" conductor; 10" casing, 147'; 8 1/2", 800'; 6-5/8", 1292'.

Coal was encountered at 198-200, 270-272, 290-292, and 655-657'.

Completion reported to Dept. of Mines May 8, 1934.

Well was shot at 2279'. Gas well.

	Top.	Bottom.
Gravel (wood conductor, 15')	0	15
Shale and lime (water, 40')	15	147
Line	147	198
✓ Coal, Mapletown (Sewickley) (gas)	198	200
Line	200	270
✓ Coal (gas)	270	272
Line	272	290
✓ Coal, Pittsburgh	290	292
Shale and lime shells	292	360
✓ Sand (gas) <i>Murphy</i>	360	370
Shale and shells	370	470
Line	470	505
Red rock	505	515
Shale and shells	515	600
Line	600	655
✓ Coal, Presport (gas) <i>Baltimore</i>	655	657
Red rock	657	690
Shale and shells	690	780
Pink rock	780	785
✓ Cow Run Sand (Dunkard) <i>Big</i>	785	885
Shale and shells	885	1000
✓ 1st Salt Sand (hole full water, 1010')	1000	1070
Shale	1070	1110
✓ 2nd Salt Sand	1110	1165
Shale and shells	1165	1235
✓ Sand <i>3rd salt</i>	1235	1290
Shale	1290	1315
✓ Maxton Sand	1315	1327
Shale	1327	1335
Sand	1335	1350
✓ Shale <i>Small</i>	1350	1355
✓ Big Lime	1355	1440
✓ Shale <i>Kenn</i>	1440	1450
✓ Big Injun Sand	1450	1640
Shale and shells	1640	1910
✓ Berea Grit Sand <i>Squaw</i>	1910	1920
Shale and shells	1920	2080
Red rock	2080	2135
Shale	2135	2196
Shell, hard (SLM)	2196	2200
Shale	2200	2247
✓ Gordon Sand (gas, 2268-2272')	2264	2273
Shale, blue	2273	2279
Total depth of well when shot		2279
Drilled 6' pocket after shot.		
Total depth of well including 6' pocket		2285