

LATITUDE

3940

082408

LONGITUDE

OGIS
7.5' loc

7.5 OGIS topo location

7.5' loc	<u>1.075</u>	15' loc	<u>1.075</u>
	<u>2.11W</u>	(calc.)	<u>4.33W</u>

Company _____

Farm _____

Quad Wileyville Littleton Wc

County _____

District Proctor

WELL LOCATION MAP

File No. Wet 93

Praetor District, Wetzel County, W. Va.

By C. B. Lewis et al., New Martinsville, W. Va.

On 45 acres, surface and minerals owned by S. O. Adams,
New Martinsville, W. Va.

Drilled under permit Wet-93, issued April 11, 1935.

Elevation, 1362' B.

13" conductor, 12'; 10" casing, 461' 4"; 8 1/2", 1320'; 6", 1559';
5", 2184'; 2" tubing, 2192'

Packer, 5 1/2", set at 2169'; packer, 2 x 5, set at 2156', inside
of casing. No liners used.

Completion reported to Dept. of Mines Sept. 9, 1935.

No water. Gas well.

Record to RCT from Mrs. Griffith Sept. 2, 1938.

	Top.	Bottom.	Thickness.
Clay, yellow, soft	0	- 20	20
Sand shells, gray, hard	20	- 136	116
Red rock, soft	136	- 152	16
Slate and lime, gray, medium	152	- 315	243
Red rock, soft	315	- 390	75
Lime, gray, hard	390	- 595	205
Red rock, soft	595	- 664	69
Lime, gray, hard	664	- 978	314
Red rock, soft	978	- 1065	87
Slate, black, soft	1065	- 1205	140
Lime, gray, hard	1205	- 1382	177
Slate, gray, soft	1382	- 1515	133
Sand, gray, hard	1515	- 1525	10
Slate, gray, soft	1525	- 1596	71
Sand, gray, hard	1596	- 1614	18
Lime shells, dark, medium	1614	- 1740	126
1st Salt Sand, gray, hard	1740	- 1771	31
Slate, black, soft	1771	- 1971	200
2nd Salt Sand	1971	- 1984	13
Slate, black, soft	1984	- 2156	172
Sand, gray, hard (gas, 2169-2180')	2156	- 2180	24
Total depth		2180	

Zin tubing to 2192'