

LATITUDE

39 40

8020

OGIS
75' loc

LONGITUDE

7'5 OGIS topo location

7.5' loc 0.84S
0.29W

15' loc 0.84S
(calc.) 0.29W

Company _____

Farm _____

Quad Hundred Mannington WC

County _____

District Church

WELL LOCATION MAP

File No. Wet. 112

Church District, Wetzel County, W. Va.

By Maxton Oil & Gas Co.

Contractor, G. W. Hull.

Drilled under permit ~~Wet-112~~, issued.....10" casing, 265'; 8 $\frac{1}{2}$ " , 1380'; 6 $\frac{3}{8}$ " , 1895'.Log to Dept. of Mines not on regular forms, and not dated;
date of filing not given.

Record to RCF from Mrs. Griffith Sept. 2, 1938.

	Top.	Bottom.
Clay, yellow, soft	0	13
Sand, light, hard	13	50
Clay, yellow, soft	50	110
Red rock, soft	110	125
Slate, dark, soft	125	265
Lime, white, firm	265	300
Slate, gray, soft	300	386
Lime (shell), light, hard	386	405
Slate, gray, soft	405	585
Lime, (gritty), white, hard	485	605
Slate, gray, soft	605	615
Sand, white, hard	615	635
Fairview (Waynesburg) Coal, black, soft	635	640
Sand, white, hard	640	680
Slate, dark, soft	680	780
Mapletown (Sewickley) Lime, white, hard	780	880
Mapletown (Sewickley) Coal, black, soft	880	885
Slate, dark, soft	885	960
Lime, white, hard	960	970
Slate, dark, soft	970	980
Pittsburgh Coal, black, soft	980	987
Slate, gray, soft	987	1035
Red rock, soft	1035	1050
Lime, light, hard	1050	1150
Red rock, soft	1150	1380
Little Dunkard Sand, light, hard	1380	1412
Slate, dark, soft	1412	1445
Big Dunkard Sand, white, hard	1445	1505
Slate, black, soft	1505	1580
Lime (gritty), white, hard	1580	1610
Shale, black, soft	1610	1650
First Salt Sand, white, hard <i>Cur Sand</i>	1650	1680
Slate, white, hard	1680	1700
Lime, white, hard	1700	1730
Slate, dark, soft	1730	1785
Second Salt Sand, white, hard	1785	1848
Slate, white, hard	1848	1890
Third Salt Sand, white, hard	1890	1971
Slate, light, soft	1971	1990
Slate, black, soft	1990	2050
Red rock, soft	2050	2055
Lime (shell and slate), light, hard	2055	2095
Lime, white, hard	2095	2106
Maxton Sand (oil at 2138-2142', SLM; oil at 2152-2156')	2106
Total depth		2171