

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.
Coal Operator or Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address
CONSOLIDATION COAL CO.
Coal Operator or Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address
DALLISON LUMBER INC
Lease or Property Owner
P.O. BOX 159 JACKSONBURG, WV 26377
Address

CONSOLIDATION COAL CO.
Name of Well Operator
1 BRIDGE STREET MONONGAH, WV 26554
Complete Address
FOLSOM 7.5'
Well Location
GRANT
District
WETZEL
County
7148
Well No.
W.Z. STARKEY
Farm

STATE INSPECTOR SUPERVISING PLUGGING Derek M. Haught

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

DELBERT E. MOORE and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 15th day of May, 2017 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In
Formation				
Cleaned 12 1/2" hole from the Surface to 378'. Reduced hole to 9 7/8" at 378. Cleaned 9 7/8" hole from 378" to 899'. Top of 8 5/8" casing, cleaned 7 7/8" hole through 8 5/8" casing from 899' to 1651'. Cleaned 7 7/8" hole from 1651' to 1799'. Tagged solid plug at 1799'. Removed 453' of 8 5/8" casing from 899' to 1352'. Cleaned 9 7/8" hole from 899' to 1352'. Left 299' of 8 5/8" casing in hole from 1352' to 1651'. Pulled 150% of string weight on remaining 8 5/8" casing with no movement detected. Cleaned 9 7/8" hole through Pittsburgh Coal Seam 1124.8' to 1131'. Left 15' of 16" conductor at the surface.	8 5/8" 16" Conductor	453' 0'	299' 15'	
<u>Cemented hole from 1799' back to Surface as follows:</u> From 1799' to 1331' with 125 sacks of Expandable Cement. From 1331' to 1009' with 185 sacks of Thixotropic Cement with green dye. From 1009' back to the Surface with 615 sacks of Expandable Cement. A total of 740 sacks of Expandable Cement were used to cement hole. Cement did circulate at the Surface.				
Coal Seams		Description of Monument		
<u>Pittsburgh</u>	<u>(1124.8' - 1131')</u>	<u>77" of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to cement plug at ground level.</u>		

... and that the work of plugging and filling said well was completed on the 8th day of June, 2017

And further deponents saith not.

Delbert E. Moore
Delbert E. Moore

Kevin S. Wright
Kevin S. Wright

Sworn to and subscribed before me this 10th day of July 2017

[Signature]
Notary Public



Permit No. 47-103-03181-P
Well No. 7148