



Surface: Ino. D. Judge, Pine Grove, Wetzel Co., W.Va.  
 Coal: Imperial Oil & Gas Products Co., Pittsburgh, Pa.

5,74 S  
 2,87 W

New Location   
 Drill Deeper   
 Abandonment  Map N 68

N 10 W 1

Company Randall-Zogg Supply Co.  
 Address Owensboro, Ky.  
 Farm Ruth Jolliffe  
 Tract \_\_\_\_\_ Acres 144 1/2 Lease No. \_\_\_\_\_  
 Well (Farm) No. A Serial No. \_\_\_\_\_  
 Elevation (Spirit Level) Casinghead - 1210.30  
Ground - 1209.30  
 Quadrangle LITTLETON  
 County Wetzel District Grant  
 Engineer E.C. Tabler  
 Engineer's Registration No. \_\_\_\_\_  
 File No. \_\_\_\_\_ Drawing No. \_\_\_\_\_  
 Date April 29<sup>th</sup> 1948 Scale 1" = 800 Feet

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

WELL LOCATION MAP  
 FILE NO. Wet-738-A

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.  
 - Denotes one inch spaces on border line of original tracing.

RUTH JOLLIFFE NO. 4 WELL.

Grant District, Wetzel County, W. Va.

By Randall-Zogg Supply Co., Box 526, Charleston, 22, W. Va.

Abandoned under permit Wet-738-A?

On 144 $\frac{1}{2}$  acres, on Maud Run of North Fork.

Elevation, 1209.30' L.

Surface owned by John D. Judge, Pine Grove, W. Va., and minerals by Imperial Oil & Gas Products Co., Pittsburgh, Pa.

Drilling commenced June 25, 1903; completed Sept. 5, 1903.

Shot Sept. 8, 1903, with 10 qts.; April 4, 1905, with 60 qts.;

Jan. 8, 1906, with 50 qts.; July 25, 1904, with 30 qts.;

Nov. 12, 1906, with 80 qts.; Feb. 23, 1910, with 80 qts.;

Nov. 26, 1929, with 60 qts.; top of shot, 3034'.

10" casing, 520' (pulled); 8 $\frac{1}{2}$ "", 1420'; 6 $\frac{3}{4}$ "", 2510'; 5 $\frac{1}{2}$ "", 174 $\frac{1}{2}$ ';

2" tubing, 3048'; 5 $\frac{1}{2}$ x5" liner, 550'.

Coal was encountered at 860-865'.

NOTE: May 23, 1921. Ran 174 $\frac{1}{2}$ ' of 5 $\frac{1}{2}$ " casing on C. C. packer. No wall.

Section set on bottom, top, 2873 $\frac{1}{2}$ '. Jan. 11, 1930, put in 550' of

5 $\frac{1}{2}$ " x 5" liner; lower section, 9 joints, 182'; middle section, 9

joints, 186'; top section, 9 joints, 182'; top of liner, 2502'.

Oil well. Abandonment reported to Dept. of Mines Aug. 20, 1948.

Record to RCT from Mrs. Griffith Jan. 5, 1949. Old File No. 1146.

	Top.	Bottom.
Pittsburgh Coal	860	- 865
Dunkard Sand	1460	- 1500
Salt Sand	1853	- 1920
Maxton Sand	2100	- 2115
Pencil Cave	2130	- 2138
Big Lime	2138	- 2200
Big Injun Sand	2200	- 2470
Stray Sand	3005	- 3030
Gordon Sand (gas and oil, 3034')	3030	- 3048
Total depth		3048.