



New Location   
 Drill Deeper   
 Abandonment

Company UNITED FUEL GAS CO.  
 Address CHARLESTON, W. VA.  
 Farm I. T. TOMPSON  
 Tract \_\_\_\_\_ Acres 110 Lease No. 44289  
 Well (Farm) No. 1 Serial No. 6335  
 Elevation (Spirit Level) 1001.25'  
 Quadrangle BELLEVILLE - SE  
 County WIRT District TUCKER  
 Engineer \_\_\_\_\_  
 Engineer's Registration No. 662  
 File No. 64-105 Drawing No. \_\_\_\_\_  
 Date MARCH 19, 1948 Scale 1" = 400'

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

**WELL LOCATION MAP**  
 FILE NO. WIRT - 258

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border of original tracing

6-6 274 Deep Well

WEST VIRGINIA DEPARTMENT OF MINES  
OIL & GAS DIVISION  
WELL RECORD

Permit No. Wir 258  
Belleville Quad.

Gas Well  
CASING & TUBING

Company	United Fuel Gas Co.			
Address	P.O. Box 1273, Charleston 25, W.Va.	13 3/8	610	Same
Farm	I.T. Thompson Acres 110	10 1/2	1162	"
Location	Left Fork of Sandy Cr	8 5/8	1801	"
Well No.	6335 Elev. 1001.25 Gr	7	2432	"
District	Tucker Wirt County	5 1/2	5188	"
Surface		2 tubing		5200
Mineral	Carol & Lena Thompson Rt. 1 Rockport, W.Va.			
Commenced	4-25-48			
Completed	8-30-48			
Date shot	8-31-48 Depth 5309 to 5358 with 354 1/6# EL 409 and 37 1/2# Gel.			
Open flow	36/10ths W in 7"			
Volume	2 588 M Oriskany			
Rock Pressure	1750 lbs. 24 hrs.			

Yellow Sand	0	20 White Sand	1710	1825
Lime Shells	20	50 Slate & Shells	1825	1995
Blue Rock	50	65 Gray Lime	1995	2000
Pink Rock	65	70 White Sand	2000	2135
Red Rock	70	85 Black Lime	2135	2145
Blue Mud	85	150 White Lime	2145	2200
Red Rock	150	170 Gritty Lime	2200	2235
Lime	170	195 Lime	2235	2445
Blue Rock	195	225 White Slate	2445	2460
Red Rock	225	250 Slate & Shells	2460	2705
Blue Slate	250	265 White Lime	2705	3005
Red Rock	265	300 Slate & Shells	3005	3300
Blue Lime	300	320 White Slate	3300	3475
Red Rock	320	350 Gray Lime	3475	3515
Blue Rock	350	400 Slate & Shells	3515	3700
Red Rock	400	500 Lime	3700	4145
Lime Shells	500	510 Brown Shale	4145	4475
Red Rock	510	550 White Slate	4475	4816
Shells	550	613 Brown Shale	4816	5160
Red Rock	613	630 Black Shale - <i>Marcellus</i>	5160	5172
Shells	630	660 Corniferous Lime	5172	5309
Red Rock	660	700 Oriskany Sand	5309	5350
White Lime	700	765 Gritty Lime - <i>Helderberg</i>	5350	5358
Red Rock	765	775 Total Depth		5358
White Sand	775	825		
White Slate	825	850 Oriskany gas 5309 1/2-5312 1/2	38/10 W 2"	260 M
Lime	850	875		
Soft Sand	875	925 Blew down to 10/10 W 2"	133 M	
Black Lime	925	935 Oriskany gas 5325 -5327	42/10 W 2"	
White Sand	935	985	273 M	
Red Rock	985	1005 Blew down to 33/10 W 2"	242 M	
White Slate	1005	1058 Oriskany gas 5339-5340	50/10 W 2"	298 M
Red Rock	1058	1108		
Lime Shells	1122	1132 Test before shot	38/10 W 2"	260 M
White Slate	1132	1141 Shot 8-31-48 with 354 1/6# EL		
Red Rock	1141	1165 409 and 37 1/2# gel.	5309-5358	
Lime	1165	1180 Test 1 hr. A.S.	36/10 W 7"	22# 2,588 M
White Sand	1180	1200		
Red Rock	1200	1312		
Lime Stone	1312	1360		
White Slate	1360	1403		
White Sand	1403	1435		
Break	1435	1440		
Sand	1440	1470		
White Slate	1470	1492		
Black Lime	1492	1520		
Slate & Shells	1520	1575		
Black Slate	1575	1600		
Salt Sand	1600	1650		
Black Slate	1650	1685		
Gritty Lime	1685	1710		

5172	5309
1001	1001
-4171	-4308