



F. M. Lewis Farm

FORMATION RECORD

Name	Color	Character	Oil, Gas or Water	Top	Bottom	Thickness	Total Depth	Remarks
Soil		Top soil		10	14		10	
Gravel				14	412			
Slate and shales				412	437	27		
Sand		Mitchell		437	720	283		
Big hole						13		
Slate and shales				830	880	50		
Sand		Little Lincast		880	904	24		
Slate				904	947	43		Little bit 927 to 930
Sand		Big Lincast		947	962	15	962	
Slate								

shot Well was not shot at \_\_\_\_\_ feet, well was shot at \_\_\_\_\_ feet.

fresh Fresh water at 12 \_\_\_\_\_ feet, fresh water at \_\_\_\_\_ feet.

producing Well was ~~shot~~ hole. dry

Date

Approved

*C. P. Dick*  
Owner

PRELIMINARY DATA SHEET NO. 1

File No. \_\_\_\_\_ Well No. \_\_\_\_\_

C. T. Fieck Et Als Company of Walker, Rout #2

West Virginia on the W. W. Lewis Farm

containing 50 acres. Location \_\_\_\_\_

Clay District, in Wirt County, West Virginia

The surface of the above tract is owned in fee by W. W. Lewis

of Elizabeth, W. Va. address, and the mineral rights are owned by same of \_\_\_\_\_

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit No. no permit issued by the West Virginia Department of Mines, Oil and Gas Division

193

Elevation of surface at top of well, 805 feet Spirit \_\_\_\_\_

The number of feet of the different sized casings used in the well.

10 feet 12 size. Wood conductor.

84 feet 7 1/2 size, csg. feet sized csg.

257 feet 6 1/2 size, csg. feet sized csg.

720 feet 4 3/8 size, csg. feet sized csg.

\_\_\_\_\_ packer of \_\_\_\_\_ size, set at \_\_\_\_\_

\_\_\_\_\_ packer of \_\_\_\_\_ size, set at \_\_\_\_\_

\_\_\_\_\_, in casing perforated at \_\_\_\_\_ feet to \_\_\_\_\_ feet.

\_\_\_\_\_, in casing perforated at \_\_\_\_\_ feet to \_\_\_\_\_ feet.

Coal was encountered at No coal feet, thickness \_\_\_\_\_ inches, and at \_\_\_\_\_

feet; thickness \_\_\_\_\_ inches; and at \_\_\_\_\_ feet; thickness \_\_\_\_\_ inches.

Liners were used as follows: (Give details) No liners

Oct 12 - 1930

Date.

Approved C. T. Fieck Et Als, Owner

By C. T. Fieck

NOTICE OF INTENTION TO PLUG AND ABANDON WELL  
(REQUIRED BY SECTION 9, ARTICLE 4, CHAPTER 22 OF THE CODE)  
 WEST VIRGINIA DEPARTMENT OF MINES  
 OIL AND GAS DIVISION

To THE DEPARTMENT OF MINES,  
 Charleston, W. Va.

F. M. Lewis (owner)

COAL OPERATOR OR COAL OWNER

C. T. Fleck ET ALS

NAME OF WELL OPERATOR

Elizabeth, W. VA.

ADDRESS

Walker, Route #2

COMPLETE ADDRESS

October 17, 1936

WELL TO BE ABANDONED

Clay District

Wirt County

Well No. 1 39° 10' 81° 15' 5.00 AC

F. M. Lewis Farm

Gentlemen:—

The undersigned well operator is about to abandon the above described well and will commence the work of plugging and abandoning said well on the 17th day of October, 1936, (which date shall not be less than five days after the day on which this notice so mailed is received, or in due course should be received by the Department of Mines).

This notice is given you in order that your respective representatives may be present at the plugging and filling of said well. You are further notified that whether you are represented or not represented the undersigned will proceed on that date, or shortly thereafter, to plug and fill said well in the manner required by Section 10, Article 4, Chapter 22 of the Code and given in detail on the reverse side of this notice, in "Work Order."

This notice is being mailed by registered mail to each of you at the above addresses on the above date.

Very truly yours,

*C. T. Fleck*

Well Operator.

NOTE: Upon the abandonment of all wells drilled prior to June 1, 1929, a plat prepared by a competent engineer, showing the district and county in which the tract of land is located, the name and acreage of same, the names of the owners of adjacent tracts, and the location of the about to be abandoned well, determined by survey, and the courses and distances of such well from two permanent points or landmarks on said tract, shall be submitted with this notice.

(Over)

## WORK ORDER

Well to be plugged and filled as follows:

In accordance with the provisions of Sec. 10, Art. 4,  
Chapter 22 of the Code of West Virginia.

WORK ORDER ARRANGED BY THE DEPARTMENT OF MINES:

Total depth 962'

Fill with red clay from the bottom 962' - 917'

Wood plug 917 - 914'

Cement 914 - 904' sealing hole

Continue to fill with red clay from 904' - 735' - 15' below 4-7/8" casing

Wood plug 735 - 732'

Cement 735 - 722'

PULL 6-5/8" casing out

continue to fill with red clay to 215'

Wood plug 215 - 212'

1 sack of cement on top of plug and

PULL 6-5/8" casing out

Fill with red clay to the surface.

Erect marker such as is described in Rule 18, 1931 Regulations.

All be done in a workman-like manner.

ALL CEMENT BE MIXED WITH WATER ONLY.

To the Department of Mines,  
Coal Owner or Operator,  
Lease or Property Owner.

Gentlemen:

This "work order" is submitted for your approval and concurrence and unless notified of your disapproval or non-concurrence, the undersigned will proceed with the plugging and filling of said well in the above described manner on the date stated in the notice of intention to plug and abandon the said well on opposite side of this sheet.

Very truly yours,

Well Operator.

No objections have been filed by the coal owner or coal operator, or any available adjacent lease or property owners or interposed by the Department of Mines to the manner herein described for the plugging and filling of the well above mentioned. Therefore, the same is hereby approved this 20th day

of 1931

DEPARTMENT OF MINES  
Oil and Gas Division

LEWIS, F. M., NO. 1.

Wirt-14-A.

By C. T. Feick et al.

Clay Dist.