

STATE OF WEST VIRGINIA
DEPARTMENT OF ENVIRONMENTAL PROTECTION
OFFICE OF OIL AND GAS

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE IN TRIPLICATE, one copy mailed to the Department, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

Farm name: Ettinger, Helen Morris (Stokes-Ritter) Operator Well No.: 142131

LOCATION: Elevation: 1923 Quadrangle: Oceana
District: Clear Fork County: Wyoming
Latitude: 37 Feet South of 65 Deg. 00 Min. 21 Sec.
Longitude: -81 Feet West of 73 Deg. 11 Min. 44 Sec.

Well Type: OIL _____ GAS X

Company EQT Production Company Coal Operator Helen Ettinger & First Citizens Bank/Trust
120 Professional Place or Owner C/O EM Energy
Bridgeport, WV 26330 PO Box 1085
Coal Operator Beckley, WV 25801
Agent _____ or Owner _____
Permit Issued Date 6-27-18

AFFIDAVIT

STATE OF ~~WEST VIRGINIA~~ KY
County of Floyd ss:

Charles Moore and Rodney Osborne being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by the above named well operator, and participated in the work of plugging and filling the above well say that said work was commenced on the 30th day of May, 2018, and the well was plugged and filled in the following manner:

TYPE	FROM	TO	PIPE REMOVED	LEFT
See Attachment A			2177' of 5 1/2"	234' of 11 3/4" (CTS)
				2075' of 8 5/8" (CTS)
				3531' of 5 1/2"
				Perfd 5 1/2" casing @ 4328', 4300', 3310', 3300', 2963', 2300', 2200'

Description of monument: 7" casing w/ API # 36" above ground and that the work of plugging and filling said well was completed on the 31 day of July, 2018.

And further deponents saith not. Charles Moore
Rodney Osborne

Sworn and subscribe before me this 1st day of August, 2018

My commission expires: 9-26-18

Michelle Handshoe
Notary Public



Affidavit reviewed by the Office of Oil and Gas: [Signature] Title: Inspector

142131 Stokes-Ritter
47-109-01456
Attachment A

Cement Plugs

4283' to 3673', 70 sks of Class A Cement

3673 to 3670', CIBP

3670' to 3564, 15 sks of Class A Cement

3366' to 3258', 30 sks of Class A Cement

3033' to 3258', 30 sks of Class A Cement

3033' to 2913', 15 sks of Class A Cement

2405' to 1998', 132 sks of Class A Cement w/ 10% Gypsum

1410' to 1177', 60 sks of Class A Cement

660' to Surface, 190 sks of Class A Cement

40' to Surface (Grouted between 8 5/8" and 11 3/4"), 12 sks of Class A Cement

