

Boford 6/14/91

CORE LABORATORIES, INC.
 Petroleum Reservoir Engineering
 DALLAS, TEXAS

15-735

Page No. 1

#735

CORE ANALYSIS RESULTS

CP-10-1005

Company THE PRESTON OIL COMPANY Formation AS NOTED File CP-1-4854
 Well V-2022 Core Type DIAMOND Date Report 8-29-63
 Field GRANNY CREEK Drilling Fluid WATER BASE MUD Analysts WELBORNE-BOYLE
 County CLAY State W. VIRGINIA Elev. 1152.5 Location HENRY DISTRICT PERMIT CLA-735

Lithological Abbreviations

SAND-SS SHALE-SH LINE-LH OOLITE-OOO CHERT-CN GYPSUM-GYP ANHYDRITE-ANHY COAGULATED-CCO FOSILIFEROUS-FOS SANDY-SBY SHALY-SHY LIMY-LHY FINE-FN MEDIUM-MED COARSE-CSE CRYSTALLINE-ILN GRAIN-GRN GRANULAR-GRNL BROWN-BRN GRAY-GV YUGGY-YGY FRACTURED-FRAC LAMINATION-LAM STYLOLITIC-STY SLIGHTLY-SL VERY-V/ WITH-W/

SAMPLE NUMBER	DEPTH FEET	PERMEABILITY MILLIDARCY		POROSITY PER CENT	RESIDUAL SATURATION PER CENT PORE		SAMPLE DESCRIPTION AND REMARKS
		PERM. MAX.	PERM. 90°		OIL	TOTAL WATER	

BIG LIME FORMATION - WHOLE CORE ANALYSIS

1	1931.0-32.0	<0.1	<0.1	1.6	0.0	36.3	Lm
2	1933.5-34.5	<0.1	<0.1	1.4	0.0	30.0	Lm
3	1937.0-38.0	<0.1	<0.1	1.8	0.0	91.7	Lm, sl/shy
4	1939.4-40.5	<0.1	<0.1	1.2	0.0	75.0	Lm
5	1943.8-45.0	<0.1	<0.1	20.7	2.7	57.1	Lm
6	1963.3-64.9	<0.1	<0.1	1.1	0.0	66.4	Lm
7	64.9-65.5	<0.1	<0.1	2.4	0.0	57.1	Lm
8	65.5-66.4	<0.1*		3.3	0.0	75.8	Lm
9	66.4-67.4	<0.1	<0.1	2.0	0.0	91.0	Lm
10	1967.4-68.4	<0.1	<0.1	1.3	0.0	76.9	Lm
11	1978.0-78.6	<0.1	<0.1	1.4	0.0	89.3	Lm, oolitic
12	78.6-80.4	<0.1	<0.1	1.2	0.0	73.3	Lm, oolitic
13	80.4-82.0	<0.1	<0.1	1.9	0.0	77.9	Lm
14	82.0-83.5	<0.1	<0.1	1.8	0.0	62.8	Lm
15	83.5-84.7	<0.1	<0.1	1.2	0.0	29.2	Lm
16	84.7-86.0	<0.1	<0.1	2.1	0.0	49.0	Lm, sl/vgy
17	86.0-87.5	<0.1	<0.1	0.9	0.0	45.6	Lm
18	87.5-89.2	<0.1	<0.1	1.2	0.0	43.3	Lm
19	89.2-90.9	<0.1	<0.1	1.0	0.0	52.0	Lm
20	90.9-92.1	<0.1	<0.1	0.9	0.0	57.8	Lm, sl/shy, vert frac
21	92.1-93.8	<0.1	<0.1	1.2	0.0	37.5	Lm
22	93.8-95.5	<0.1	<0.1	2.4	0.0	93.3	Lm, sl/shy
23	95.5-96.2	<0.1	<0.1	8.2	11.3	79.9	Lm, sl/shy, sl/chalky
24	1996.2-97.0	<0.1	<0.1	13.2	29.5	61.0	Lm, sl/sdy, chalky

INJUN FORMATION - CONVENTIONAL ANALYSIS

25	1997.0-98.0	<0.1		7.1	12.7	40.7	
26	98.0-99.0	<0.1		6.0	3.3	63.3	
27	99.0-00.0	33		16.0	18.1	40.5	
28	2000.0-01.0	182	15.8	22.4	17.4	60.8	
29	01.0-02.0	266		19.9	12.1	68.3	150
30	02.0-03.0	21	A-8	19.7	16.7	42.6	
31	03.0-04.0	1.0		16.3	27.0	43.0	
32	1904.0-05.0	<0.1		13.0	19.3	46.0	

These analyses, opinions or interpretations are based on observations and materials supplied by the client to whom, and for whose exclusive and confidential use, this report is made. The interpretations or opinions expressed represent the best judgment of Core Laboratories, Inc. (all errors and omissions excepted); but Core Laboratories, Inc. and its officers and employees, assume no responsibility and make no warranty or representation, as to the productivity, proper operations, or profitability of any oil, gas or other mineral well or sand in connection with which such analyses were made.

Entered

6/14/91
CORE LABORATORIES, INC.
Petroleum Reservoir Engineering
DALLAS, TEXAS

15-735

File CP-10-1005, CP-1- Page No. 2

Well No. V-2022

4854

CORE ANALYSIS RESULTS

SAMPLE NUMBER	DEPTH FEET	PERMEABILITY MILLIDARCY	POROSITY PER CENT	RESIDUAL SATURATION PER CENT PORE		SAMPLE DESCRIPTION AND REMARKS
				OIL	TOTAL WATER	
33	2005.0-06.0	0.4	11.1	23.4	41.4	
34	06.0-07.0	0.3	8.7	10.2	46.0	
35	07.0-08.0	<0.1	8.8	12.5	44.3	
36	08.0-09.0	0.1	7.4	12.1	33.8	
37	2009.0-10.2	0.7	6.9	13.0	34.8	
38	2011.5-12.0	<0.1	10.2	22.5	37.2	
39	12.0-13.0	<0.1	9.6	23.9	30.2	
40	13.0-14.0	0.7	10.6	16.0	33.9	
41	14.0-15.0	268 10=8	16.1	11.2	34.2	
42	15.0-16.0	41	15.3	10.4	33.4	
43	16.0-17.0	<0.1	9.5	17.9	25.3	
44	17.0-18.0	65	15.5	12.2	31.5	
45	18.0-19.0	17	15.9	10.1	52.7	
46	19.0-20.0	23	12.0	14.1	30.0	
47	20.0-21.0	<0.1	2.2	0.0	77.5	
48	21.0-22.0	12	18.4	15.8	38.0	
49	22.0-23.0	<0.1	7.8	19.2	38.5	
50	23.0-24.0	<0.1	21.7	20.8	52.5	
51	24.0-25.0	0.1	18.3	22.4	33.4	
52	25.0-26.0	43	26.8	10.1	39.6	
53	26.0-27.0	4.4	21.9	13.7	39.7	
54	27.0-28.0	1.6	11.3	23.9	65.3	
55	28.0-29.0	5.1	24.4	14.4	35.7	
56	29.0-30.0	6.3	18.5	19.5	46.5	
57	30.0-31.0	2.5	20.6	15.5	41.7	
58	31.0-32.0	2.8	21.8	15.2	39.9	
59	32.0-33.0	5.4	23.4	15.4	56.8	
60	33.0-34.0	8.0 20	23.0	15.7	50.0	
61	34.0-35.0	9.3	21.9	16.5	53.9	
62	35.0-36.0	17	23.2	15.1	49.6	
63	36.0-37.0	6.7	22.3	17.9	50.5	
64	37.0-38.0	1.0	20.2	16.3	54.9	
65	38.0-39.0	2.7	20.6	15.5	54.8	
66	39.0-40.0	1.6	19.6	14.2	52.0	
67	40.0-41.0	1.0	16.8	13.1	52.3	
68	41.0-42.0	<0.1	15.1	16.6	72.1	
69	42.0-43.0	<0.1	15.1	12.6	72.1	
70	2043.0-43.6	<0.1	17.5	8.0	62.3	
71	2044.5-45.0	<0.1	15.4	14.8	58.7	
72	2045.0-46.0	<0.1	15.4	14.8	58.7	

1274

1988

These analyses, opinions or interpretations are based on observations and materials supplied by the client to whom, and for whose exclusive and confidential use, this report is made. The interpretations or opinions expressed represent the best judgment of Core Laboratories, Inc. (all errors and omissions excepted); but Core Laboratories, Inc. and its officers and employees, assume no responsibility and make no warranty or representations, as to the productivity, proper operations, or profitability of any oil, gas or other mineral well or sand in connection with which such report is used or relied upon.