

Entered

6/19/91

15-903

#903

CORE ANALYSIS RESULTS

Company PRESTON OIL COMPANY Formation BIG INJUN SAND File CP-1-7283
 Well B. G. S. GEARY NO. V-2072 Core Type DIAMOND Date Report 9-29-70
 Field GRANNIES CREEK Drilling Fluid _____ Analysts BOYLE
 County CLAY State W. VA. Elev. _____ Location _____

Lithological Abbreviations

SAND - SS SHALE - SH LIME - LM	DOLOMITE - DOL CHERT - CH GYPSUM - GYP	ANHYDRITE - ANHY CONGLOMERATE - CONG FOSSILIFEROUS - FOSS	SANDY - SBY SHALY - SHY LIMY - LIMY	FINE - FW MEDIUM - MED COARSE - CSE	CRYSTALLINE - XLN GRAIN - GRN GRANULAR - GRNL	BROWN - BRN GRAY - GRV MUSBY - MUSBY	FRACTURED - FRAC LAMINATION - LAM STYLOLITIC - STY	SLIGHTLY - SL VERY - V/ WITH - W/
--------------------------------------	--	---	---	---	---	--	--	---

SAMPLE NUMBER	DEPTH FEET	PERMEABILITY MILLIDARCS		POROSITY PER CENT	RESIDUAL SATURATION PER CENT PORE		VERT. PERM.	SAMPLE DESCRIPTION AND REMARKS
		PERM. MAX.	PERM. 90°		OIL	TOTAL WATER		

WHOLE CORE ANALYSIS

1	1747-48	1.6	1.2	0.8	0.0	33.3	<0.1	Lm
2	48-49	4.4	0.5	4.5	Tr	80.8	<0.1	Sd, shy, congl
3	49-50	1.2	0.9	10.2	8.6	65.5	0.4	Sd
4	50-51	3.5	3.0	6.6	8.1	48.5	0.4	Sd
5	51-52	8.2	7.4	7.1	11.4	57.1	0.9	Sd
6	52-53	69.0	63.0	15.1	8.5	49.3	6.3	Sd
7	53-54	96.0	93.0	17.5	7.3	48.8	92	Sd
8	54-55	2.2	1.3	9.9	9.4	50.9	<0.1	Sd
9	55-56	3.0	2.4	11.6	6.5	49.4	0.1	Sd, congl
10	56-57	3.5	0.7	7.4	7.9	47.4	<0.1	Sd
11	57-58	2.3	1.7	12.6	9.1	56.3	<0.1	Sd
12	58-59	3.0	1.5	10.5	9.3	46.3	<0.1	Sd, congl
13	59-60	1.5	1.4	11.7	9.8	51.2	<0.1	Sd
14	60-61	2.4	2.2	10.7	10.0	50.0	<0.1	Sd
15	61-62	2.6	1.3	10.0	8.5	55.3	0.1	Sd
16	62-63	3.5	1.9	6.3	9.7	54.8	0.1	Sd, congl
17	63-64	0.8	0.5	9.1	8.9	51.1	0.1	Sd
18	64-65	3.2	2.5	11.0	10.8	52.7	0.1	Sd, shy, congl
19	65-66	10.0	9.7	16.8	9.0	61.5	0.2	Sd
20	66-67	1.2	0.9	14.1	10.9	65.2	<0.1	Sd
21	67-68	8.2	7.2	14.6	14.9	68.7	0.1	Sd
22	68-69	13.0	12.0	16.6	11.0	59.8	0.3	Sd
23	69-70	0.9	0.2	6.8	7.9	57.9	<0.1	Sd
24	70-71	33.0	31.0	11.7	7.7	76.9	3.8	Sd, silty
25	71-72	4.0	3.1	8.8	8.3	77.8	0.1	Sd, silty
26	72-73	1.6	0.6	14.1	14.1	67.2	<0.1	Sd, silty
27	73-74	1.2	1.1	14.7	11.6	69.8	<0.1	Sd, silty
28	74-75	3.9	3.2	15.2	14.1	68.8	0.1	Sd, silty
29	75-76	1.8	0.8	15.6	12.0	70.0	<0.1	Sd, silty
30	76-77	1.7	0.9	15.7	12.2	61.0	<0.1	Sd, silty
31	77-78	2.1	1.9	17.7	11.6	55.8	0.6	Sd, silty
32	78-79	2.4	2.4	17.5	12.9	55.3	0.7	Sd, silty
33	79-80	3.4	1.7	16.7	12.3	60.0	0.4	Sd, silty
34	80-81	2.1	1.6	16.9	11.4	58.1	0.2	Sd, silty
35	81-82	2.0	1.1	16.6	11.7	57.8	0.2	Sd, silty
36	82-83	1.0	1.0	16.5	16.9	57.1	0.1	Sd, silty
37	83-84	1.6	1.2	16.6	13.3	58.3	0.1	Sd, silty
38	84-85	2.4	1.7	16.0	13.7	63.0	0.1	Sd, silty
39	85-86	1.4	1.1	14.7	14.3	57.1	<0.1	Sd, silty
40	86-87	2.7	2.2	13.0	12.7	57.1	0.2	Sd, silty
41	87-88	3.9	3.4	18.6	14.8	55.7	1.6	Sd, silty

These analyses, opinions or interpretations are based on observations and materials supplied by the client to whom, and for whose exclusive and confidential use, this report is made. The interpretations or opinions expressed represent the best judgment of Core Laboratories, Inc. (all errors and omissions excepted); but Core Laboratories, Inc. and its officers and employees, assume no responsibility and make no warranty or representations, as to the productivity, proper operations, or practicability of any oil, gas or other mineral well or sand in connection with which such report is used or relied upon.

Entered
6/19/91

CORE LABORATORIES, INC.
Petroleum Reservoir Engineering
DALLAS, TEXAS

15-903

File CP-1-7283 Page No. 2
Well B. G. S. Geary No. V-2072

CORE ANALYSIS RESULTS

SAMPLE NUMBER	DEPTH FEET	PERMEABILITY MILLIDARCYs		POROSITY PER CENT	RESIDUAL SATURATION PER CENT PORE		VERT. PERM	SAMPLE DESCRIPTION AND REMARKS
		MAX.	90°		OIL	TOTAL WATER		
42	1788-89	3.6	3.1	18.9	15.4	55.9	1.5	Sd, silty
43	89-90	4.3	3.6	18.6	15.6	55.0	1.6	Sd, silty
44	90-91	4.3	4.2	18.6	14.6	57.3	1.2	Sd, silty
45	91-92	3.8	3.6	18.3	17.5	57.5	1.3	Sd, silty
46	92-93	5.1	4.1	19.0	17.5	51.5	2.4	Sd, silty
47	93-94	2.4	2.0	17.9	14.3	60.0	0.6	Sd, silty
48	94-95	3.2	3.1	18.7	12.8	59.6	1.1	Sd, silty
49	95-96	5.3	4.8	17.5	14.7	53.3	1.8	Sd, silty
50	96-97	3.9	3.9	17.7	12.0	58.1	0.5	Sd, silty
51	97-98	1.8	1.6	15.7	10.9	68.8	<0.1	Sd, silty
52	98-99	1.8	1.0	10.3	14.9	70.2	<0.1	Sd, silty
53	99-00	0.1	<0.1	12.7	Tr	92.1	<0.1	Sd, v/silty
54	1000-01	0.1	0.1	4.1	0.0	88.9	0.1	Sh, silty

THIS IS THE FINAL REPORT.