

west virginia department of environmental protection

Office of Oil and Gas 601 57th Street, S.E. Charleston, WV 25304 (304) 926-0450 fax: (304) 926-0452

Harold D. Ward, Cabinet Secretary www.dep.wv.gov

Friday, January 13, 2023 PERMIT MODIFICATION APPROVAL Vertical / Plugging

UNKNOWN - DEP PAID PLUGGING CONTRACT 601 57TH STREET

CHARLESTON, WV 25304

Re:

Permit Modification Approval for 1

47-011-00446-00-00

Class L Cement Variance

UNKNOWN - DEP PAID PLUGGING CONTRACT

The Office of Oil and Gas has reviewed the attached permit modification for the above referenced permit. The attached modification has been approved and well work may begin. Please be reminded that the oil and gas inspector is to be notified twenty-four (24) hours before permitted well work is commenced.

If there are any questions, please feel free to contact me at (304) 926-0450.

James A. Marti Chief

Operator's Well Number: 1

Farm Name: SALT ROCK COMMUNITY CHURCH

U.S. WELL NUMBER: 47-011-00446-00-00

Vertical Plugging

Date Modification Issued: 01/13/2023

Promoting a healthy environment.



west virginia department of environmental protection

Office of Oil and Gas 601 57th Street, S.E. Charleston, WV 25304 Phone: (304) 926-0450 Fax: (304) 926-0452 Harold D. Ward, Cabinet Secretary dep.wv.gov

January 11, 2023

Salt Rock Community Church P O Box 126 Salt Rock, WV 25559

RE: 47-011-00446 plugging permit modification for Class L cement

Mr. Salmons,

According to records held by the Office of Oil and Gas, you are the landowner of the parcel described formally as:

Parcel Description: Salt Rock Con

Salt Rock Community Church ID: 06-08-0016-0080-0000

DESC: SUR 2.17 AC Tyler Creek; 9881 & 9897 Route 10

The Office of Oil and Gas has issued a permit to permanently plug well API# 47-011-00446 on the above listed property and now intends to modify that permit to allow for the use of Class L cement in place of Class A due to manufacturing shortage. Enclosed you will find the proposed modification to the plugging work order and a copy of the approved variance authorizing the use of Class L in this manner.

As the landowner of the affected parcel, you are entitled to submit comments to this modification of the existing permit. If you choose to waive this right, please sign and return the closed surface owner waiver.

If you have any questions regarding this modification request please contact me at (304) 926-0499 ext. 41102.

Respectfully,

Jason Harmon

Deputy Chief, Office of Oil and Gas

Salt Rock Church # 1 PLUGGING PROJECT 47 - 011 - 00446

V. REMEDIATION AND/OR PLUGGING WORK PLAN

Notify Inspector Specialist, Allen Flowers @ (304)552-8308. Email address is allen.d.flowers@wv.gov. Notification is required 24 hrs prior to commencing plugging operations

- 1. Install 24 inch cellar around existing well head.
- 2. Move in and rig up to existing 7 inch casing. Unhook 2 inch production line and cap off below surface.
- 3. TIH check TD @ or below 1900 Ft, pull all 2 inch tubing from the well. If estimated depth cannot be reached begin cleaning out hole to approved depth/TD by Inspector Specialist.
- 4. Once TD has been reached and approved by Inspector Specialist a bond log will be ran inside the 7 inch casing to determine casing depth and cement bonding location.
- ★ 5. TIH to estimated TD @ 1900 Ft or inspector approved depth with tubing, spot 6% gel and pump bottom hole cement plug from 1900' to 1700' TOH. WOC, tag top of cement plug. Add cement if needed.
- ★ 6. TIH with tubing and spot gel from 1700' to 1400'. Pump 100' cement plug from 1400' to 1300'. WOC, tag top of plug and add cement if needed.
- 7. TIH with tubing spot gel from 1300' to 1250' followed by cement plug from 1250' to 1150' to cover 7 inch casing shoe. TIH free point 7 inch casing and attempt to pull. All casing that can not be retrieved and is not cemented/boned must be cut or perforated at all gas,oil,fresh water,salt water,coal and elevation.
- 8. TIH with tubing and spot gel from 1250' to 900'. Pump 100' cement plug from 900' to 800'. WOC, tag top of plug and add cement if needed.
- 9. TIH with tubing and spot gel from 800' to 650'. Pump cement from 650' to 550'. WOC, tag top of plug and add cement if needed.
- ★ 10. TIH with tubing and spot gel from 550' to 200'. Pump cement from 200' to surface. WOC, add cement id needed.

- 11. Rig down and set monument. Reclaim site.
- 12. NOTE.. Any casing found in the well with out cement in the annulus that cannot be retrieved must be perforated and cement at all saltwater, freshwater, coal, oil, gas, casing shoe and elevation points.

Allen D Flowers 7/5/2022

* Class L comet may be substituted for Class A
HOW 1/3/23

SURFACE OWNER WAIVER

Operator's Well Number

47-011-004460

INSTRUCTIONS TO SURFACE OWNERS NAMED ON PAGE WW4-A

The well operator named on page WW-4A is applying for a permit from the State to plug and abandon a well. (Note: If the surface tract is owned by more than three persons, then these materials were served on you because your name appeared on the Sheriff's tax ticket on the land or because you actually occupy the surface tract. In either case, you may be the only owner who will actually receive these materials.) See Chapter 22 of the West Virginia Code. Well work permits are valid for 24 months. If you do not own any interest in the surface tract, please forward these materials to the true owner immediately if you know who it is. Also, please notify the well operator and the Office of Oil and Gas.

NOTE: YOU ARE NOT REQUIRED TO FILE ANY COMMENT.
WHERE TO FILE COMMENTS AND OBTAIN ADDITIONAL INFORMATION:

Chief, Office of Oil and Gas
Department of Environmental Protection
601 57th St. SE
Charleston, WV 25304
(304) 926-0450

Time Limits and methods for filing comments. The law requires these materials to be served on or before the date the operator files his Application. You have FIVE (5) DAYS after the filing date to file your comments. Comments must be filed in person or received in the mail by the Chief's office by the time stated above. You may call the Chief's office to be sure of the date. Check with your postmaster to ensure adequate delivery time or to arrange special expedited handling. If you have been contacted by the well operator and you have signed a "voluntary statement of no objection" to the planned work described in these materials, then the permit may be issued at any time.

Comments must be in writing. Your comments must include your name, address and telephone number, the well operator's name and well number and the approximate location of the proposed well site including district and county from the application. You may add other documents, such as sketches, maps or photographs to support your comments.

The Chief has the power to deny or condition a well work permit based on comments on the following grounds:

- 1) The proposed well work will constitute a hazard to the safety of persons.
- 2) The soil erosion and sediment control plan is not adequate or effective;
- 3) Damage would occur to publicly owned lands or resources;
- 4) The proposed well work fails to protect fresh water sources or supplies;
- 5) The applicant has committed a substantial violation of a previous permit or a substantial violation of one or more of the rules promulgated under Chapter 22, and has failed to abate or seek review of the violation..."

If you want a copy of the permit as it is issued or a copy of the order denying the permit, you should request a copy from the Chief.

VOLUNTARY STATEMENT OF NO OBJECTION

I hereby state that I have read the instructions to surface owners and that I have received copies of a Notice and Application For A Permit To Plug And Abandon on Forms WW-4A and WW-4B, and a survey plat.

I further state that I have		anned w	ork described in these n	naterials, and I have no
objection to a permit being issued on those materials. FOR EXECUTION BY A NATURAL PERSON			FOR EXECUTION BY A CORPORATION,	
ETC// O//	11			
you De	Date 1/13/23	_ Name		
Signature		By		Britania Balan
		Its		Date
			Signature	Date

01/13/2023



west virginia department of environmental protection

Office of Oil and Gas 601 57th Street, SE Charleston, WV 25304 Phone (304) 926-0450

Haroid D. Ward, Cabinet Secretary dep.wv.gov

BEFORE THE OFFICE OF OIL AND GAS DEPARTMENT OF ENVIRONMENTAL PROTECTION STATE OF WEST VIRGINIA

IN THE MATTER OF A VARIANCE FROM)		
LEGISLATIVE RULE 35CSR4)	ORDER NO.	2022-13
SECTION 14.1. AND LEGISLATIVE RULE	j		
35CSR8 SECTION 20.1,)		
RELATING TO THE CEMENTING)		
OF OIL AND GAS WELLS)		
	,		

REPORT OF THE OFFICE

In response to industry requests, the West Virginia Department of Environmental Protection, Office of Oil and Gas has reviewed the proposed use of American Petroleum Institute (API) Class L cement to be used in place of API Class A cement for well plugging.

FINDINGS OF FACT

- 1. On July 28, 2022, Diversified Gas & Oil Co. (DGO) submitted a variance request from Legislative Rule 35CSR4 for the use of API Class L cement in place of API Class A cement, relating to the plugging of conventional wells.
- 2. Laboratory analysis submitted by DGO on July 28, 2022, indicates API Class L cement is comparable to API Class A cement and thereby satisfies the requirements of the West Virginia Code.
- 3. Contemporaneously, the Chief of the Office of Oil and Gas also chose to consider a variance to Legislative Rule 35CSR8 Section 20.1., for the use of API Class L cement in place of API Class A cement, relating to the plugging of horizontal wells.

Promoting a healthy environment

 On August 18, 2022, the Office of Oil and Gas provided public notice of acceptance of public comments on the variance consideration. During the 20-day public comment period, no comments were received.

CONCLUSIONS OF LAW

Pursuant to Article 6 and Article 6A, Chapter 22 of the Code of West Virginia, the Office of Oil and Gas has jurisdiction over the subject matter, and the persons interested therein, and jurisdiction to promulgate the hereinafter prescribed Order.

Pursuant to Legislative Rule 35CSR4, Section 18 and Legislative Rule 35CSR8, Section 14, the Chief of the Office of Oil and Gas may grant a variance from any requirement of these rules.

ORDER

It is ordered that the Class L cement product approved and monogramed by API is approved for use in place of API Class A cement for well plugging subject to the provisions of Legislative Rule 35CSR4 and Legislative Rule 35CSR8.

Dated this, the 13th day of September, 2022.

IN THE NAME OF THE STATE OF WEST VIRGINIA

OFFICE OF OIL AND GAS
DEPARTMENT OF ENVIRONMENTAL PROTECTION
OF THE STATE OF WEST VIRGINIA

James Martin, Chief Office of Oil and Gas



Kennedy, James P < james.p.kennedy@wv.gov>

Clement Variance approved 4701100446

1 message

Kennedy, James P < james.p.kennedy@wv.gov>

Fri, Jan 13, 2023 at 3:46 PM

To: Allen D Flowers <allen.d.flowers@wv.gov>, Henry J Harmon <henry.j.harmon@wv.gov>

To whom it may concern, a modification has been approved for 4701100446.

James Kennedy

WVDEP OOG

