


Latitude  $39^{\circ} 05' 00''$

Longitude  $80^{\circ} 05' 00''$



2.090  
1.64w

Topo Location

7.5' Loc. \_\_\_\_\_ 15' Loc. \_\_\_\_\_  
  (calc.) \_\_\_\_\_

Company HNG Co.

Farm L.C. Morrison # 5713

15' Quad \_\_\_\_\_  
(sec.)

7.5' Quad Auburn

District Troy

**WELL LOCATION PLAT**

County 021 Permit 30002

Troy District, Gilmer County, W. Va.  
Hope Natural Gas Co., 445 W. Main St., Clarksburg, W. Va.  
On 89-3/4 acres, surface and mineral rights owned by L. C. Morrison,  
Route 2, Coxs Mills, W. Va.  
Well drilled prior to June 1, 1929.  
Elevation, 1265.2' L.  
10" casing, 149'; 8 1/2", 1065'.

"Our records of this well do not show that there was any workable coal seam encountered when drilling this well."

Abandonment reported to Dept. of Mines Oct. 24, 1929.

NO RECORD.  
(Completion Data Sheet No. 2 not Filed).



COMPLETION DATA SHEET NO. 2

FORMATION RECORD

*See*

NAME	COLOR	CHARACTER	OIL, GAS OR WATER	TOP	BOTTOM	THICK- NESS	TOTAL DEPTH	RE- MARKS
								Our records show that no native oil was found.
								No Pittsburgh vein of coal was found.
								We have no record of formations above [unclear] [unclear].

Well was not shot at \_\_\_\_\_ feet; well was shot at \_\_\_\_\_ feet.

Salt Fresh water at \_\_\_\_\_ feet; Salt fresh water at \_\_\_\_\_ feet.

WEST VIRGINIA DEPARTMENT OF MINES

OIL & GAS SECTION

PRELIMINARY DATA SHEET NO. 1

Sil-2

File No. \_\_\_\_\_

Well No. 5713

HOPE NATURAL GAS COMPANY Company, of 445 West Main St.  
Clarksburg, W. Va. on the L. C. Morrison Farm  
containing 89<sup>3</sup> acres. Location Troy  
District, in Gilmer County, West Va.

The surface of the above tract is owned in fee by  
L. C. Morrison of Cox Mills, Route #2. address, and the  
mineral rights are owned by L. C. Morrison of Cox Mills, R-2.

The oil and gas privileges are held under lease by  
the above named company, and this well is drilled under permit  
No. \_\_\_\_\_ issued by the West Virginia Department of Mines, Oil and  
Gas Section, Well drilled prior to June 1st, 1929. 1929.

Elevation of surface at top of well, 1265.2' ~~1265.2'~~ <sup>Spirit</sup>

The number of feet of the different sized casings used in the well.

\_\_\_\_\_ feet \_\_\_\_\_ size. Wood conductor.  
149 feet 10" size, csg. 1065 feet 8<sup>1</sup>2" sized csg.  
\_\_\_\_\_ feet \_\_\_\_\_ size, csg. \_\_\_\_\_ feet \_\_\_\_\_ sized csg.  
\_\_\_\_\_ feet \_\_\_\_\_ size, csg. \_\_\_\_\_ feet \_\_\_\_\_ sized csg.

\_\_\_\_\_ packer of \_\_\_\_\_ size, set at \_\_\_\_\_  
\_\_\_\_\_ packer of \_\_\_\_\_ size, set at \_\_\_\_\_  
\_\_\_\_\_ in. casing perforated at \_\_\_\_\_ feet to \_\_\_\_\_ feet.  
\_\_\_\_\_ in. casing perforated at \_\_\_\_\_ feet to \_\_\_\_\_ feet.

Coal was encountered at \_\_\_\_\_ feet; thickness \_\_\_\_\_ inches, and at  
\_\_\_\_\_ feet; thickness \_\_\_\_\_ inches; and at \_\_\_\_\_ feet; thick-  
ness \_\_\_\_\_ inches.

Liners were used as follows: (Give details) \_\_\_\_\_

Our records of this well do not show that there was any workable coal seen



AFFIDAVIT IN TRIPLICATE TO TIME AND MANNER OF PLUGGING AND FILLING WELL (REQUIREMENT SECTION 10, CHAPTER 26, ACTS 1928) WEST VIRGINIA DEPARTMENT OF MINES AND GAS SECTION

*M. J. ...*

COAL OPERATOR \_\_\_\_\_ NAME OF WELL OPERATOR \_\_\_\_\_  
 ADDRESS \_\_\_\_\_ COMPLETE ADDRESS \_\_\_\_\_  
 COAL OPERATOR \_\_\_\_\_ WELL AND LOCATION \_\_\_\_\_  
 ADDRESS \_\_\_\_\_ District \_\_\_\_\_  
 COAL OPERATOR \_\_\_\_\_ County \_\_\_\_\_  
 ADDRESS \_\_\_\_\_ Well No. \_\_\_\_\_  
 Farm \_\_\_\_\_

AFFIDAVIT TO BE MADE IN TRIPLICATE. ONE COPY TO BE MAILED TO THE DEPARTMENT, ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES.

AFFIDAVIT

STATE OF WEST VIRGINIA  
COUNTY OF GILBERT

John E. Aman and James S. Dennison  
being first duly sworn according to law and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Hope Natural Gas Company, well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 27th day of October, 1929, and that the well was plugged and filled in the following manner:

Manner in which said well was plugged and filled: Filled to depth of 1750 with red mud; bridged at depth of 1750 at top of mud; filled with mud to depth of 1767-foot with 8" Lead Plug at 1767; filled to surface with mud.

Manner in which coal was encountered: No coal seams encountered.

Description of monument: 129

and that the work of plugging and filling said well was completed on the 2nd day of November, 1929

And further deponents

*File 13*

*1 1 1 1*