

40°30'00"

Latitude

80°32'30"

1.08s  
.41w

Longitude

Topo Location

7.5' Loc. \_\_\_\_\_ 15' Loc. \_\_\_\_\_  
(calc.) \_\_\_\_\_

Company Glenn Devitt et al

Farm Melford Marten #1

15' Quad \_\_\_\_\_  
(sec.)

7.5' Quad Wenton

District Chy

**WELL LOCATION PLAT**

County 029 Permit 77





STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION 4

Quadrangle Steubenville, Ohio

**WELL RECORD**

Permit No. HAN-77

Oil or Gas Well Dry  
(KIND)


Company Glenn Devitt ET-AL  
Address R.D. 1, Hookstown, Pa.  
Farm Milford Martin Acres 10.61  
Location (waters) \_\_\_\_\_  
Well No. 1 Elev. 1205  
District Clay County Hancock  
The surface of tract is owned in fee by Milford Martin  
Address R.D. 1, New Cumberland, W.Va.  
Mineral rights are owned by Milford Martin  
Address New Cumberland W.Va.  
Drilling commenced Nov. 27, 1960  
Drilling completed Jan. 14, 1961  
Date Shot None From \_\_\_\_\_ To \_\_\_\_\_  
With \_\_\_\_\_  
Open Flow /10ths Water in \_\_\_\_\_ Inch  
/10ths Merc. in \_\_\_\_\_ Inch  
Volume \_\_\_\_\_ Cu. Ft.  
Rock Pressure \_\_\_\_\_ lbs. \_\_\_\_\_ hrs.  
Oil NO bbls., 1st 24 hrs.  
Fresh water 70 feet \_\_\_\_\_ feet  
Salt water 1000 feet 1032 feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer <u>No</u>
16			
13			
10			Size of _____
8 1/4	200	200	
6 3/4	941	941	Depth set _____
5 3/16			
3			Perf. top _____
2			Perf. bottom _____
Liners Used			Perf. top _____
			Perf. bottom _____

CASING CEMENTED NO SIZE \_\_\_\_\_ No. Ft. \_\_\_\_\_ Date \_\_\_\_\_

COAL WAS ENCOUNTERED AT 215 FEET \_\_\_\_\_ INCHES  
420 FEET \_\_\_\_\_ INCHES \_\_\_\_\_ FEET \_\_\_\_\_ INCHES  
\_\_\_\_\_ FEET \_\_\_\_\_ INCHES \_\_\_\_\_ FEET \_\_\_\_\_ INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Sand	Brown	Soft	0	14	Water	70	Fresh small am't.
Slate	Gray	Soft	14	74			
Slate	Black	Soft	74	80			
Sand	White	Hard	80	100			
Red Rock	Red	Soft	100	103			
Slate	Gray	Soft	103	110			
Rock	Red	Soft	110	115			
Sand	Black	Hard	115	140			
Slate	Gray	Soft	140	165			
Rock	Red	Soft	165	175			
Slate	Gray	Hard	175	190			
Sand	Gray	Hard	190	215			
Coal	Black	Soft	215	216			
Slate	Gray	Hard	216	250			
Slate	Black	Soft	250	280			
Sand	White	Hard	280	285			
Slate	Gray	Soft	285	305			
Lime Shl's	Gray	Hard	305	415			
Slate	Black	Soft	415	420			
Show of Coal	Black	Soft	420	422			
Fire Clay	White	Soft	422	445			
Slate	Black	Soft	445	485			
Sand	Brown	Hard	485	560			
Slate & Shells	Gray	Hard	560	730			
Sand	Black	Soft	730	770			
Slate Brk	Grey	Soft	770	772			
Sand	White	Hard	772	780			
Slate & Shells	Gray	Hard	780	790			
Slate	Gray	Soft	790	800			
Lime	Black	Hard	800	880			
Shell	Gray	Hard	880	922			
Big Ins.							



Formation	Color	Hard or Soft	Top 4	Bottom	Oil, Gas or Water	Depth Found	Remarks
Slate	Gray	Soft	922	940			
Lime	Black	Hard	940	941			
Shell							
Slate	Gray	Soft	941	1000			
Squaw	Gray	Hard	1000	1032	a salt water	1025	Small Amount
Sand							
Slate	Gray	Soft	1032	1035			
Lime	Black	Hard	1035	1145			
Shells							
Slate	Gray	Hard	1145	1190			
Berea Stray	White	Hard	1190	1224			
Sand							
Slate	Black	Soft	1224	1257			
Top Berea	White	Soft	1257	1289	Salt Water		A very little Amount
Sand							

Date Jan 25, 1961  
APPROVED Glenn D. Smith, Owner  
By \_\_\_\_\_ (Title)