

WR-35  
Rev (5-01)

DATE: June 29, 2011  
API #: 47-033-05548

State of West Virginia  
Department of Environmental Protection  
Office of Oil and Gas

Well Operator's Report of Well Work

Farm name: Fox, Clifford

Operator Well No.: Barren 1

LOCATION: Elevation: 1,123'

Quadrangle: Salem 7.5'

District: Tenmile

County: Harrison

Latitude: 4,034 Feet South of 39 Deg. 18 Min. 57.5 Sec.

Longitude: 6,325 Feet West of 80 Deg. 30 Min. 51.3 Sec.

Company: Tenmile Land LLC

|  | Casing & Tubing | Used in drilling | Left in well | Cement fill up Cu. Ft. |
|--|-----------------|------------------|--------------|------------------------|
| Address: 1807 W. Pike St. Ste. E<br>Clarksburg, WV 26301 | 13 3/8"         | 32'              | 32'          |                        |
| Agent: Chad Johnson                                      | 9 5/8"          | 252'             | 252'         | 90 sx                  |
| Inspector: Tristan Jenkins                               | 7"              | 1,736'           | 1,736'       | 270 sx                 |
| Date Permit Issued: 4/27/2011                            | 4 1/2"          | 5,264'           | 5,264'       | 195 sx                 |
| Date Well Work Commenced: 5/28/2011                      |                 |                  |              |                        |
| Date Well Work Completed: 6/16/2011                      |                 |                  |              |                        |
| Verbal Plugging:   |                 |                  |              |                        |
| Date Permission granted on:                              |                 |                  |              |                        |
| Rotary X Cable Rig                                       |                 |                  |              |                        |
| Total Depth (feet): 5352'                                |                 |                  |              |                        |
| Fresh Water Depth (ft.): 200'                            |                 |                  |              |                        |
| Salt Water Depth (ft.): 1150'                            |                 |                  |              |                        |
| Is coal being mined in area (N/Y)? N                     |                 |                  |              |                        |
| Coal Depths (ft.): N/A                                   |                 |                  |              |                        |

OPEN FLOW DATA

Producing formation Benson Pay zone depth (ft) 5050' - 5080'  
 Gas: Initial open flow odor MCF/d Oil: Initial open flow Bbl/d  
 Final open flow 350 MCF/d Final open flow Bbl/d  
 Time of open flow between initial and final tests 72 Hours  
 Static rock Pressure 1000 psig (surface pressure) after Hours  
 Second producing formation Bradford, Balltown, Speechley and Forth Sand  
 Pay zone depth (ft) 2850' - 4535'  
 Gas: Initial open flow \* MCF/d Oil: Initial open flow \* Bbl/d  
 Final open flow \* MCF/d Final open flow \* Bbl/d  
 Time of open flow between initial and final tests Hours  
 Static rock Pressure \* psig (surface pressure) after \* Hours  
 \* Comingled

RECEIVED  
Office of Oil and Gas

APR 20 2011

WV Department of  
Environmental Protection

NOTE: ON BACK OF THIS FORM PUT THE FOLLOWING: 1). DETAILS OF PERFORATE INTERVALS, FRACTURING OR STIMULATING, PHYSICAL CHANGE, ETC. 2). THE WELL LOG WHICH IS A SYSTEMATIC DETAILED GEOLOGICAL RECORD OF ALL FORMATIONS, INCLUDING COAL ENCOUNTERED BY THE WELLBORE.

Signed:

By: Chad Johnson

Date: 6-29-11

04/29/2016

Tenmile Land Co.

Barren #1

47-033-05548

|            |             |               |              |
|------------|-------------|---------------|--------------|
| Benson     | 5061 - 5071 | 35,000# 20/40 | 163 bbl. SLF |
| Bradford   | 4436- 4509  | 20,000# 20/40 | 107 bbl. SLF |
| Balltown   | 3881- 4008  | 25,000# 20/40 | 132 bbl. SLF |
| Speechley  | 3480- 3670  | 30,000# 20/40 | 139 bbl. SLF |
| Forth Sand | 2854 - 2890 | 12,900# 20/40 | 85 bbl. SLF  |

---

| FORMATION    | COLOR | HARD/SOFT | TOP  | BOTTOM | REMARKS                    |
|--------------|-------|-----------|------|--------|----------------------------|
| KB/fill      |       |           | 0    | 8      |                            |
| Sand & shale |       |           | 8    | 1643   |                            |
| Salt Sand    |       |           | 1643 | 1690   |                            |
| Sand & shale |       |           | 1690 | 2080   |                            |
| Log Tops:    |       |           |      |        |                            |
| Big Lime     |       |           | 2080 | 2130   |                            |
| Big Injtm    |       |           | 2130 |        |                            |
| 50' Sand     |       |           | 2648 | 2675   |                            |
| Gordon       |       |           | 2802 | 2869   |                            |
| Forth Sand   |       |           | 2867 | 3428   |                            |
| Warren       |       |           | 3428 | 3550   | Gas check @ 2917'5/10 - 2" |
| Speechley    |       |           | 3670 | 4010   | Oil odor @ 3515'           |
| Balltown     |       |           | 4010 | 4060   |                            |
| Bradford     |       |           | 4440 | 4470   | Gas check 1/10 - 2"        |
| Benson       |       |           | 5050 | 5080   |                            |
| Total Depth  |       |           | 5352 |        | Gas check @ TD 6/10- 2"    |

RECEIVED  
Office of Oil and Gas

APR 26 2016

WV Department of  
Environmental Protection

04/29/2016