

JK

WR-35
Rev (9-11)

State of West Virginia
Department of Environmental Protection
Office of Oil and Gas
Well Operator's Report of Well Work

DATE: 9/16/2013
API #: 47-033-05730

Farm name: Stamm, Jeffrey O. Operator Well No.: Riffee Unit 1H

LOCATION: Elevation: 1240' Quadrangle: Salem

District: Tenmile County: Harrison
Latitude: 643' Feet South of 39 Deg. 20 Min. 00 Sec.
Longitude 15,238' Feet West of 80 Deg. 32 Min. 30 Sec.

Company: Antero Resources Corporation

Address:	Casing & Tubing	Used in drilling	Left in well	Cement fill up Cu. Ft.
1625 17th Street Denver, CO 80202	20" 94#	40'	40'	38 Cu. Ft. Class A
Agent: CT Corporation System	13 3/8" 48#	375'	375'	521 Cu. Ft. Class A
Inspector: Sam Ward	9 5/8" 36#	2,854'	2,854'	1162 Cu. Ft. Class A
Date Permit Issued: 03/08/2013	5 1/2" 20#	18,346'	18,346'	4529 Cu. Ft. Class H
Date Well Work Commenced: 3/12/2013				
Date Well Work Completed: 8/20/2013	2 3/8 4.7#	7,919'		
Verbal Plugging: N/A				
Date Permission granted on: N/A		Top	Bottom	
Rotary <input checked="" type="checkbox"/> Cable <input type="checkbox"/> Rig <input type="checkbox"/>	Cement Plug	6,675'	7,530'	177 Cu. Ft. Class H
Total Vertical Depth (ft): 7552' (Deepest Point Drilled)				
Total Measured Depth (ft): 18,629' MD, 7416' (BHL)				
Fresh Water Depth (ft.): 106'				
Salt Water Depth (ft.): 600', 1575'				
Is coal being mined in area (N/Y)? No				
Coal Depths (ft.): None Available				
Void(s) encountered (N/Y) Depth(s) None				

OPEN FLOW DATA (If more than two producing formations please include additional data on separate sheet)

Producing formation Marcellus Pay zone depth (ft) 7,368' (TOP)

Gas: Initial open flow ---- MCF/d Oil: Initial open flow ---- Bbl/d

Final open flow 783 MCF/d Final open flow ---- Bbl/d

Time of open flow between initial and final tests ---- Hours

Static rock Pressure 3800 psig (surface pressure) after ---- Hours

Second producing formation ----- Pay zone depth (ft) -----

Gas: Initial open flow ----- MCF/d Oil: Initial open flow ----- Bbl/d

Final open flow ----- MCF/d Final open flow ----- Bbl/d

Time of open flow between initial and final tests ----- Hours

Static rock Pressure ----- psig (surface pressure) after ----- Hours

I certify under penalty of law that I have personally examined and am familiar with the information submitted on this document and all the attachments and that, based on my inquiry of those individuals immediately responsible for obtaining the information I believe that the information is true, accurate, and complete.

Kaullen Bush
Signature

1/30/2014
Date

05/30/2014

Were core samples taken? Yes _____ No Were cuttings caught during drilling? Yes _____ No Were Electrical, Mechanical or Geophysical logs recorded on this well? If yes, please list Yes, CBLThis is a subsequent well. Antero only runs wireline logs on the first well on a multi-well pad (Hustead North Unit 1H API# 47-033-05413). Please reference wireline logs submitted with Form WR-35 for Hustead North Unit 1H.

NOTE: IN THE AREA BELOW PUT THE FOLLOWING: 1). DETAILS OF PERFORATED INTERVALS, FRACTURING OR STIMULATING, PHYSICAL CHANGE, ETC. 2). THE WELL LOG WHICH IS A SYSTEMATIC DETAILED GEOLOGICAL RECORD OF THE TOPS AND BOTTOMS OF ALL FORMATIONS, INCLUDING COAL ENCOUNTERED BY THE WELLBORE FROM SURFACE TO TOTAL DEPTH.

Perforated Intervals, Fracturing, or Stimulating:

Preforations: 8,065'- 18,290' MD (2,100 Holes)

Frac'd w/ 22,504 gals 15% HCL Acid, 295,611 bbls Slick Water carrying 1,381,380# 100 mesh,
6,100,500# 40/70 sand and 3,742,680# 20/40 sand.

Plug Back Details Including Plug Type and Depth(s): N/A

Formations Encountered:	Top Depth	/	Bottom Depth
<u>Surface:</u>			
Big Lime	est. 2,243'		2,292'
Big Injun	est. 2,293'		2,678'
Gantz Sand	est. 2,679'		2,805'
Fifty Foot Sandstone	est. 2,806'		2,902'
Gordon	est. 2,903'		3,234'
Fifth Sandstone	est. 3,235'		3,262'
Bayard	est. 3,263'		3,873'
Speechley	est. 3,874'		4,131'
Baltown	est. 4,132'		4,656'
Bradford	est. 4,657'		5,211'
Benson	est. 5,212'		5,478'
Alexander	est. 5,479'		5,697'
Elk	est. 5,698'		6,212'
Rhinstreet	est. 6,213'		6,813'
Sycamore	6,814'		7,038'
Middlesex	7,039'		7,193'
Burkett	7,194'		7,216'
Tully	7,217'		7,314'
Hamilton	7,315'		7,367'
Marcellus	7,368'		7552' (TVD)

33.05730

Hydraulic Fracturing Fluid Product Component Information Disclosure

Job Start Date:	8/9/2013
Job End Date:	8/20/2013
State:	West Virginia
County:	Harrison
API Number:	47-033-05730-00-00
Operator Name:	Antero Resources Corporation
Well Name and Number:	Riffee Unit 1H
Longitude:	-80.54331110
Latitude:	39.29147780
Datum:	NAD27
Federal/Tribal Well:	NO
True Vertical Depth:	7,552
Total Base Water Volume (gal):	12,522,540
Total Base Non Water Volume:	47,093



Hydraulic Fracturing Fluid Composition:

Trade Name	Supplier	Purpose	Ingredients	Chemical Abstract Service Number (CAS #)	Maximum Ingredient Concentration in Additive (% by mass)**	Maximum Ingredient Concentration in HF Fluid (% by mass)**	Comments
Freshwater	Antero Resources	Water	Water	7732-18-5	100.00000	90.70898	
40/70 White	JS Silica	Proppant	Sand	14808-60-7	100.00000	4.91440	
20/40 White	JS Silica	Proppant	Sand	14808-60-7	100.00000	2.92370	
100 Mesh	JS Silica	Proppant	Sand	14808-60-7	100.00000	1.26770	
Beta M-4.0	PIP	Guar Gel	Petroleum Distillate	64742-47-8	55.00000	0.04677	
			Guar Gum	9000-30-0	50.00000	0.04252	
			Clay	1302-78-9	5.00000	0.00425	
			Surfactant	154518-36-2	1.00000	0.00085	
Plexslick 953	Chemplex	Friction Reducer	Water	7732-18-5	35.00000	0.02152	
			Polyacrylamide-co-acrylic acid	9003-06-9	32.00000	0.01967	
			Hydrotreated Petroleum Distillate	64742-47-8	30.00000	0.01844	
			Alcohol Ethoxylate Surfactants	Proprietary	8.00000	0.00492	

33-05730

Hydrochloric Acid 10-15%	Reagent	Acid				
			Hydrochloric Acid	7647-01-0	15.00000	0.03424
Plexicide 15G	Chemplex	Biocide				
			Water	7732-18-5	90.00000	0.02285
			Glutaraldehyde	111-30-8	14.00000	0.00355
			Alkyl Dimethyl Benzyl Ammonium Chloride	68424-85-1	3.00000	0.00076
			Ethanol	64-17-5	3.00000	0.00076
			Didecyl Dimethyl Ammonium Chloride	7173-51-5	3.00000	0.00076
Plexaid 673	Chemplex	Scale Inhibitor				
			Water	7732-18-5	85.00000	0.01335
			Methyl Alcohol	67-56-1	25.00000	0.00393
			Sodium Salt of Phosphonodimethylated Diamine	Proprietary	5.00000	0.00079
Sodium Persulfate	Chemplex	Breaker				
			Sodium Persulfate	7775-27-1	100.00000	0.00123
Plexhib 256	Chemplex	Corrosion				
			Methyl Alcohol	67-56-1	70.00000	0.00049
			thiourea-formaldehyde copolymer	68527-49-1	30.00000	0.00021
			Alcohol Ethoxylate Surfactants	Proprietary	30.00000	0.00021
			n-olefins	Proprietary	10.00000	0.00007
			Propargyl Alcohol	107-19-7	8.00000	0.00006
Plexbreak 145	Chemplex	Non-emulsifier				
			Water	732-18-5	66.00000	0.00052
			Ethylene Glycol Monobutyl Ether	111-76-2	15.00000	0.00012
			Methyl Alcohol	67-56-1	15.00000	0.00012
			Cocamide Diethanolamine Salt	68603-42-9	10.00000	0.00008
			Diethanolamine	111-42-2	5.00000	0.00004
Ferriplex 66	Chemplex	Iron Control				
			Acetic Acid	64-19-7	50.00000	0.00022
			Water	7732-18-5	35.00000	0.00016
			Citric Acid	77-92-9	30.00000	0.00013

Ingredients shown above are subject to 29 CFR 1910.1200(i) and appear on Material Safety Data Sheets (MSDS). Ingredients shown below are Non-MSDS.

* Total Water Volume sources may include fresh water, produced water, and/or recycled water

** Information is based on the maximum potential for concentration and thus the total may be over 100%

Note: For Field Development Products (products that begin with FDP), MSDS level only information has been provided.

Ingredient information for chemicals subject to 29 CFR 1910.1200(i) and Appendix D are obtained from suppliers Material Safety Data Sheets (MSDS)