

west virginia department of environmental protection

Office of Oil and Gas 601 57th Street, S.E. Charleston, WV 25304 (304) 926-0450 fax: (304) 926-0452

Austin Caperton, Cabinet Secretary www.dep.wv.gov

Thursday, January 7, 2021 PERMIT MODIFICATION APPROVAL Horizontal 6A / New Drill

HG ENERGY II APPALACHIA, LLC 5260 DUPONT ROAD

PARKERSBURG, WV 26101

Re: Permit Modification Approval for ANTONIO 1206 N-1H

47-033-05978-00-00

Lengthen Surface casing 75'

HG ENERGY II APPALACHIA, LLC

The Office of Oil and Gas has reviewed the attached permit modification for the above referenced permit. The attached modification has been approved and well work may begin. Please be reminded that the oil and gas inspector is to be notified twenty-four (24) hours before permitted well work is commenced.

If there are any questions, please feel free to contact me at (304) 926-0450.

James A. Martin Chief

Operator's Well Number: ANTONIO 1206 N-1H

Farm Name: CHARLES R. & FRANKLIN L. SUTTON

U.S. WELL NUMBER: 47-033-05978-00-00

Horizontal 6A New Drill Date Modification Issued: 1/7/2021

Promoting a healthy environment.

WW-6B (04/15) API NO. 47- 033 - 05978

OPERATOR WELL NO. Antonio 1206 N-1H

Well Pad Name: Antonio 1206

STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION, OFFICE OF OIL AND GAS WELL WORK PERMIT APPLICATION

1) Well Operator: HG I	Energy II Appa	alachia, 📙	494519932	Harrison	Grant	West Milford 7.5'
1) Well Operator			Operator ID	County	District	Quadrangle
2) Operator's Well Num	ber: Antonio 1	206 N-1H	Well Pad	Name: Antor	nio 1206	
3) Farm Name/Surface (Owner: HG Energ	gy II Appalach	ia, LLC Public Roa	d Access: Ha	ckers Cree	ek Rd @ SR 19
4) Elevation, current gro	ound: 1364'	Ele	evation, proposed j	post-constructi	on: 1350'	
5) Well Type (a) Gas Other	X	_ Oil	Unde	erground Stora	ge	
(b)If Ga	s Shallow	X	Deep			
	Horizontal	<u>x</u>				
6) Existing Pad: Yes or				-		
7) Proposed Target Form Marcellus at 7081'/726	nation(s), Deptl 30' and 179' in th	n(s), Antic nickness. <i>A</i>	ipated Thickness a Anticipated pressure	nd Expected P at 4314#.	ressure(s):	
8) Proposed Total Vertic	cal Depth: 725	52'				
9) Formation at Total V		Marcellus	3			
10) Proposed Total Mea	sured Depth:	21,980'				
11) Proposed Horizonta	l Leg Length:	13,268'				
12) Approximate Fresh	Water Strata D	epths:	135', 480', 637',	731'		
13) Method to Determin	ne Fresh Water	Dopuis	Nearest offset we			
14) Approximate Saltwa	ater Depths: _\	lo S/W depth	ns found on WR-35's fo	or offset wells, salt	water expec	ted to be below elevation.
15) Approximate Coal S	Seam Depths:	323', 1010)' to 1015'			
16) Approximate Depth	to Possible Vo	id (coal m	ine, karst, other):	None		
17) Does Proposed well directly overlying or ad	l location contai	n coal sea ve mine?	ms Yes	No	, <u>X</u>	RECEIVED Office of Oil and Gas
(a) If Yes, provide Mi	ne Info: Nam	e:				NOV 1 6 2020
	Dept	h:				WV Department of Environmental Protection
	Seam	ı:				EUALOURIEMENT
	Own	er:				

WW-6B	
(04/15)	

API NO. 47- 033 _ 05978

OPERATOR WELL NO. Antonio 1206 N-1H
Well Pad Name: Antonio 1206

18)

CASING AND TUBING PROGRAM

TYPE	Size (in)	New or Used	Grade	Weight per ft. (lb/ft)	FOOTAGE: For Drilling (ft)	INTERVALS: Left in Well (ft)	CEMENT: Fill-up (Cu. Ft.)/CTS
Conductor	30"	New	LS	157.5	125'	125'	Drilled In
Fresh Water/Coal	20"	NEW	J-55	94	1175'	1175'	40% excess,CTS
Intermediate I	13 3/8"	NEW	J-55	68	2200'	2200'	40% excess,CTS
Intermediate 2	9 5/8"	NEW	J-55	40	3000'	3000'	40% excess tail, CTS
Production	5 1/2"	NEW	P-110	23	21980'	21980'	20% excess tail, CTS
Tubing		1 11					
Liners							

SAW 11/13/2020

TYPE	Size (in)	Wellbore Diameter (in)	Wall Thickness (in)	Burst Pressure (psi)	Anticipated Max. Internal Pressure (psi)	Cement Type	Cement Yield (cu. ft./k)
Conductor	30"	30"	.500				Drilled In
Fresh Water/Coal	20"	24"	.438	2110	1200	Type 1, Class A	40 % excess yield = 1.20, CTS
Intermediate1	13 3/8"	17 1/2"	.480	3450		Type 1/Class A	Load 40% excess, Toll 0% excess
Intermediate 2	9 5/8"	12 1/4"	.395	3950		Type 1/Class A	Lend 40% expens, Tail 0% Expens Lend
Production	5 1/2"	8 1/2"	.415	16240	12500	Type 1/ClassA	20% excess yeld = 1,19, sall yield 1
Tubing				/			
Liners							

RECEIVED Office of Oil and Gas

PACKERS

NOV 1 6 2020

Kind:	WV Department of Environmental Protection
Sizes:	
Depths Set:	

WW-6B (10/14) API NO. 47- 033 - 05978

OPERATOR WELL NO. Antonio 1206 N-1H

Well Pad Name: Antonio 1206

19) Describe proposed well work, including the drilling and plugging back of any pilot hole:

Drill the vertical depth to the Marcellus at an estimated total vertical depth of approximately 7252 feet. Drill horizontal leg to estimated 13,268' lateral length, 21,980' TMD. Hydraulically fracture stimulate and be capable of producing from the Marcellus Formation. Should we encounter an unanticipated void in the coal, we will install a minimum of 20' of casing below the void but not more than 100' below the void, set a basket and grout to surface. We plan to run an ECP above the Gantz/Dominion Storage interval to aid in sealing off and isolating the storage interval.

20) Describe fracturing/stimulating methods in detail, including anticipated max pressure and max rate:

The stimulation will be completed with multiple stages divided over the lateral length of the well. Stage spacing is dependent upon engineering design. Slickwater fracturing technique will be utilized on each stage using sand, water, and chemicals. See attached list. Maximum pressure not to exceed 12,500 psi.

- 21) Total Area to be disturbed, including roads, stockpile area, pits, etc., (acres): 68.187 acres
- 22) Area to be disturbed for well pad only, less access road (acres): 11.058 acres

23) Describe centralizer placement for each casing string:

No centralizers will be used with conductor casing.
Freshwater - centralized every 3 joints to surface.
Freshwater - centralized every 3 joints to surface.
Goal - Bow Spring on every joint, will also be running ACP for isolating storage zone
Coal - Bow Spring on every joint, will also be running ACP for isolating storage zone
Coal - Bow Spring on first 2 joints then every third joint to 100 from surface.
Freduction - Run 1 spiral centralizer every 5 joints from the top of the curve to surface. Run 1 spiral centralizer every 3 joints from the 1st 5.5" long joint to the top of the curve.

RECEIVED
Office of Oil and Gas

NOV 1 6 2020

WV Department of Environmental Protection

24) Describe all cement additives associated with each cement type:

Conductor -N/A, Casing to be drilled in wi Dual Rotary Rig.
Finsh Water - 15.6 pog PNE-1 + 3% bwoc CaCI, 40% Excess Yield = 1.20, CTS Intermediate 1 - 1.20, Excess - 1.20 intermediate 1 - 1.20 intermediate 1 - 1.20 intermediate 2 - 1.20 inter

25) Proposed borehole conditioning procedures:

Conductor - Ensure the hole is clean at TD.
Fresh Water - Once casing is at setting depth, circulate a minimum of one hole volume with Fresh Water prior to pumping cement.
Coal - Once casing is at setting depth, Circulate and condition at TD. Circulate a minimum of one hole volume prior to pumping cement.
Coal - Once casing is at setting depth, Circulate and condition at TD. Circulate a minimum of one hole volume prior to pumping cement.
Intermediate - Once casing is at setting depth, Circulate and condition mud at TD. Circulate a minimum of one hole volume prior to pumping cement.
Production - Once on bottom/TD With casing, circulate at max altivately pump rate for at least 25 bottoms up, or undit returns and pump pressures indicate the hole is clean. Circulate a minimum of one hole volume prior to pumping cement.

*Note: Attach additional sheets as needed.

an april .

SEVINORA ROBINA ((Chi. eoffi.)

usos als vov.

WV Department of Covincing plant tratection



1206 N-1H Marcellus Shale Horizontal Harrison County, WV

No. Casing Security Conductor Co									Harrison Co	ounty, wv	
AZM 340,538 & 337,516* 1206 N-1H BHL 14,232319.62N 1807891.49E COMMENT COM						1206 N	1-1H SH	L	14	220780.27N 181547	74.77E
AZM 340.538 & 337.516" 1206 N-1H BHL 14232319.62N 1807891.49E	Ground Elevation 1350'				1206	N-1H LE	•	14219939.72N 1812638.84E			
WELLBORE DIAGRAM	E. I. S. S. S. S. S. S. S. S. S.	3				1206 N	I-1H BH	IL .	14	232319.62N 180789	91.49E
X X X X X X X X X X				75710	TOP				CENTRALIZERS	CONDITIONING	COMMENTS
X X X X X X X X X X	WELLBORE DIAGRAM	HOLE	CASING	GEOLOGI	10(2,.02					
X X X X X X X X X X		30"	The second of th	Conductor	0	125	AIR		N/A		Conductor casing = 0.5" wa thickness
X 24" 948 3.55 3.56				Fresh Water	0				2007.700.40	I have a construction of the construction of the	Surface casing = 0,438" wa
X X X X X X X X X X		24"		Coal	1010	1015	AIR	The second of the second		and any or of the control of the con	thickness
X			94# 5-55	Surface / FW	0	1175				**************************************	Burst-2110 psi
17.5" 15.28" 15.58 15.56 15.									Bow Spring on every		
X X X X X X X X X X		2.5	13-3/8" 68#	Little/Big Lime	1555 / 1596	1575 / 1658		The second secon		condition at TD. Circulate a minimum of one hole volume prior to pumping	Intermediate casing = 0.480 wall thickness Burst=3450 psi
Intermediate 1	x x	17.5"		Injun / Gantz (Storage)	1658 / 1985	1770 / 2050	-		ACP for isolating		
12.25* 9-5/8* 40# 15.5 BTC Gordon Stray / Gordon 2232 / 2272 2272 / 2288 AIR / KCL 5th Sand 2515 2527 Bayard / Warren 2581 / 2891 2601 / 2931				Intermediate 1	0	2200	15.80		storage zone*		
12.25" 9-5/8" 40# 12.25" 5/8 Sand 2515 2527 2527 / 2385 5/8 Sand 2515 2527 2527 / 2381 2591 / 2881 2601 / 2931 260	x x			Fifty / Thirty Foot	2095 / 2182	2157 / 2200		Lead: 15.4 ppg PNE-1 +		depth, Circulate and	Intermediate casing = 0,395" wall thickness Burst=3950 psi
Start Section Sectio				Gordon Stray / Gordon	2232 / 2272	2272 / 2385	AIR / KCL	2.5% bwoc CaCl			
X X		12.25"		5th Sand	2515	2527	Salt	40% EXCESS / Tall. 13.5	The state of the s		
Intermediate 2	x		0.00.010	Bayard / Warren	2591 / 2891	2601 / 2931	Polymer	CaCl	surface	The state of the s	
Balltown 3438 3448 9.0ppg POZ:PNE-1 + 0.3% bwoc R3 + 1% bwoc EC1 + 0.75 gal/sk P131 + 0.3% bwoc R3 + 1% bwoc EC1 + 0.75 gal/sk P131 + 0.3% bwoc R3 + 0.75 gal/sk P131 + 0.75 gal/s				Intermediate 2	0	3000		Zeio% Excess. C13			
Balltown 3438 3448 9.0pg SOBM Lead: 14.5 ppg POZ:PNE-1 + 0.3% bwo c R3 + 1% bwo c EC1 + 0.75 gal/sk FP13L + 5.0% bwo c R3 + 1.5ppg 11.5ppg 12.5ppg SOBM SoBM	x x			Speechley	3204	3224			every 5 joints from the	Once on bottom/TD with casing, circulate at max allowable pump rate for at least 2x bottoms up, or until returns and pump	Burst=16240 psi
Senson 4505 4525 SOLID POZ:PNE-1 + 0.3% bwoc R3 + 1% bwoc R3		9 Et Vortion	3	Balltown	3438	3448		1200 1100			
Rhinestreet 6395 6651		0.5 Vertica		Benson	4505	4525	SOBM		The second secon		
Rhinestreet 6395 6651 6751 6783 6854 6854 6864 700 7								bwoc R3 + 1% bwoc	23,20		
Sample S				Rhinestreet	6395	6651					
X X			5 4 1011	Cashaqua	6651	800708					
SOBM Sobb	X X		23#	Middlesex	1 2 2 2 2 2 2 2			0.35% bwoc R3 + 0.75			
Burkett Codd Substitution Su		8.5" Curve			A PERSON N				Run 1 spiral centralizer		schedules may be change
Hamilton 6972 7081 Lead Yield=1,19 Tail Yield=1,94 CTS Top of the curve. Cement. Top of the curve. Coment. CTS CTS			CDCTTG			- 10 - 200	10000000	bwoc MPA170	every 3 joints from the 1st 5.5" long joint to the	minimum of one hole	de to hole conditions
TMD / TVD								Lead Yield=1,19 Tail Yield=1,94			NOV I
TMD / TVD			_							ar in a contract of the contra	The V
				10171	0.03						1 6
		8.5" Latera	8.5" Lateral		21980	7252	12.5ppg	1 1			Oil and Oil An
X X X X X X X X X X X X X X X X X X X	x			Onondaga	7260						
A A A		X	X	X	X		X	٨	^	(TD +/-7252' TVD
	X	X	X	X	X		Х	Х	X	X	X=centralizers



HG Energy, LLC 5260 Dupont Road Parkersburg, WV 26101 (304) 420-1100 - Office (304) 863-3172 - Fax

December 5, 2020

Charles R. Sutton 593 Long Run Road Lost Creek, WV 26385

RE:

Antonio 1206 N-1H thru S-10H Well Work Permit Applications - Notifications

Modification Request to Extend Surface Casing 75' to 1175' to Cover an Additional Seam of Coal

Grant District, Harrison County, West Virginia

Dear Mr. Sutton:

Enclosed are copies of various application papers that we will be filing with the West Virginia Department of Environmental Protection (WVDEP), Office of Oil and Gas. A well work permit modification is being requested for the above-referenced well to extend the FW casing 75 feet to 1175' to cover an additional seam of coal.

Pursuant to WV Code Chapter 22B, Article 6, you are receiving copies of this correspondence because the well or other anticipated disturbance is located on your surface property. Your rights as a surface owner (road) are detailed in the enclosed permit application papers.

No action on your part is required. If you have any questions or comments regarding this notification, you may call this office at (304) 420-1119 or mailto:dwhite@hgenergyllc.com dwhite@hgenergyllc.com.

Very truly yours,

Diane White

Diane C. White

RECEIVED Office of Oil and Gas

DEC 1 0 2020

Enclosures

WV Department of
Environmental Protection



HG Energy, LLC 5260 Dupont Road Parkersburg, WV 26101 (304) 420-1100 - Office (304) 863-3172 - Fax

December 5, 2020

Antonio PLLC c/o Mike Ross P. O. Box 219 Coalton, WV 26257

RE: Antonio 1206 N-1H thru S-10H Well Work Permit Applications - Notifications

Modification Request to Extend Surface Casing 75' to 1175' to Cover an Additional Seam of Coal

Grant District, Harrison County, West Virginia

Dear Mr. Ross:

Enclosed are copies of various application papers that we will be filing with the West Virginia Department of Environmental Protection (WVDEP), Office of Oil and Gas. A well work permit modification is being requested for the above-referenced well to extend the FW casing 75 feet to 1175' to cover an additional seam of coal.

Pursuant to WV Code Chapter 22B, Article 6, you are receiving copies of this correspondence because the well or other anticipated disturbance is located on your surface property. Your rights as a surface owner (road) are detailed in the enclosed permit application papers.

No action on your part is required. If you have any questions or comments regarding this notification, you may call this office at (304) 420-1119 or mailto:dwhite@hgenergyllc.com dwhite@hgenergyllc.com.

Very truly yours, Diane White

Diane C. White

RECEIVED Office of Oil and Gas

DEC 1 0 2020

Enclosures

WW-6A (9-13)

API NO. 47	
OPERATOR WELL NO.	1206 N-1H to S-10H
Well Pad Name: Antonio 12	06

STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION, OFFICE OF OIL AND GAS NOTICE OF APPLICATION

Noti	ce Time Requirem	ent: notice shall be provid	led no later that	n the filing date of permit applic	ation.
	of Notice: 12/07/20	_ Date Permit Applicati	ion Filed: 11/30	/20	
Noti	ce of: PERMIT FOR AN	Y V CERTIFIC	CATE OF APP	ROVAL FOR THE	RECEIVED Office of Oil and Gas
Ľ	WELL WORK	•		AN IMPOUNDMENT OR PIT	DEC 1 0 2020
Deli	very method pursu	nant to West Virginia Co			WV Department of Environmental Protection
	PERSONAL SERVICE	☐ REGISTERED MAIL		OD OF DELIVERY THAT REQ PT OR SIGNATURE CONFIRM	
sedin the soil a description oper more well important proving substractory programs and the second water seco	nent control plan recurface of the tract or and gas leasehold being ribed in the erosion attor or lessee, in the ecoal seams; (4) The work, if the surface of a water well, spring ide water for consumosed well work active ection (b) of this seconds of the sheriff requision of this article to the R. § 35-8-5.7.a recompared to the sheriff consumption of the sheriff requision of the sheriff requis	quired by section seven of the which the well is or is proper in the proposed and sediment control plan surevent the tract of land on we event the tract of land on we event is to be used for the placescribed in section nine of the sure tract is to be used for the placescribed in section nine of the gor water supply source location by humans or domestivity is to take place. (c)(1) If the place is to be maintained pursue of the contrary, notice to a liquires, in part, that the operate owner subject to notice and	nis article, and to posed to be located well work, if abmitted pursuathich the well purface tract or tracement, constraints article; (5) Anted within one of more than three dis, the applicant uant to section of a holder is not ator shall also put displacement.	itted; (2) The owners of record of the the surface tract is to be used for rent to subsection (c), section seven reposed to be drilled is located [sic acts overlying the oil and gas leased uction, enlargement, alteration, reparty surface owner or water purveyor thousand five hundred feet of the composed of the operator of any natural gase tenants in common or other co-out may serve the documents require eight, article one, chapter elevenanotice to a landowner, unless the larovide the Well Site Safety Plan ("as provided in section 15 of this runtile surface of the control of the contro	g persons: (1) The owners of record of e surface tract or tracts overlying the bads or other land disturbance as of this article; (3) The coal owner, I is known to be underlain by one or cold being developed by the proposed air, removal or abandonment of any or who is known to the applicant to center of the well pad which is used to a storage field within which the wners of interests described in d upon the person described in the of this code. (2) Notwithstanding any ien holder is the landowner. W. Va. WSSP") to the surface owner and any le.
	application Notice URFACE OWNER		S Plan Notice	☐ Well Plat Notice is hereby ☐ COAL OWNER OR LESSEE	
Nan				Name:	
	ress: P. O. Box 219		-	Address:	
Auc	Coalton, WV 2625	57	_		
NIor			_	☐ COAL OPERATOR	
Nar	ress: 593 Long Run Ro		-	Name:	
Add	Lost Creek, WV 2		-	Address:	
		(s) (Road and/or Other Dis	- sturbonce)	riddress.	
		(s) (Road and/or Other Dis	stur barree)	□ SURFACE OWNER OF WA	TER WELL
	ne: See Above		_	AND/OR WATER PURVEYO	
Add					* -
				Name:	
				Address:	
Ado	iress:	· · · · · · · · · · · · · · · · · · ·	_	OPERATOR OF ANY NAT	TRAL GAS STORAGE FIELD
	THE LOE OTTATED	(a) (Immoundments on Dita	7		
		(s) (Impoundments or Pits)		Name:	
				Address:	
Ado	lress:		_	*m	if managamy
			_	*Please attach additional forms	n necessary

WW-6A (8-13)

API NO. 47-OPERATOR WELL NO. 1206 N-1H to S-10H Well Pad Name: Antonio 1206

Notice is hereby given:

Pursuant to West Virginia Code § 22-6A-10(b), notice is hereby given that the undersigned well operator has applied for a permit for well work or for a certificate of approval for the construction of an impoundment or pit.

Pursuant to W. Va. Code § 22-6A-10(b), this notice shall include: (1) copies of the application; (2) the erosion and sediment control plan required by section seven of this article; and (3) the well plat. WV Department of Environmental Protection

Pursuant to W. Va. Code § 22-6A-10(f), this notice shall include: (1) a statement of the time limits for filing written comments; (2) who may file written comments; (3) the name and address of the secretary for the purpose of filing the comments and obtaining additional information; and (4) a statement that the persons may request, at the time of submitting written comments, notice of the permit decision and a list of persons qualified to test water.

Pursuant to W. Va. Code R. § 35-8-5.7.a, the operator shall provide the Well Site Safety Plan to the surface owner and any water purveyor or surface owner subject to notice and water testing as provided in section 15 of this rule.

Pursuant to W. Va. Code R. § 35-8-15.2.c, this notice shall: (1) contain a statement of the surface owner's and water purveyor's right to request sampling and analysis; (2) advise the surface owner and water purveyor of the rebuttable presumption for contamination or deprivation of a fresh water source or supply; advise the surface owner and water purveyor that refusal to allow the operator to conduct a pre-drilling water well test constitutes a method to rebut the presumption of liability; (3) advise the surface owner and water purveyor of his or her independent right to sample and analyze any water supply at his or her own expense; advise the surface owner and water purveyor whether or not the operator will utilize an independent laboratory to analyze any sample; and (4) advise the surface owner and or water purveyor that he or she can obtain from the Chief a list of water testing laboratories in the subject area capable of and qualified to test water supplies in accordance with standard acceptable methods.

Additional information related to horizontal drilling may be obtained from the Secretary, at the WV Department of Environmental Protection headquarters, located at 601 57th Street, SE, Charleston, WV 25304 (304-926-0450) or by visiting www.dep.wv.gov/oiland-gas/pages/default.aspx.

Well Location Restrictions

Pursuant to W. Va. Code § 22-6A-12, Wells may not be drilled within two hundred fifty feet measured horizontally from any existing water well or developed spring used for human or domestic animal consumption. The center of well pads may not be located within six hundred twenty-five feet of an occupied dwelling structure, or a building two thousand five hundred square feet or larger used to house or shelter dairy cattle or poultry husbandry. This limitation is applicable to those wells, developed springs, dwellings or agricultural buildings that existed on the date a notice to the surface owner of planned entry for surveying or staking as provided in section ten of this article or a notice of intent to drill a horizontal well as provided in subsection (b), section sixteen of this article was provided, whichever occurs first, and to any dwelling under construction prior to that date. This limitation may be waived by written consent of the surface owner transmitted to the department and recorded in the real property records maintained by the clerk of the county commission for the county in which such property is located. Furthermore, the well operator may be granted a variance by the secretary from these distance restrictions upon submission of a plan which identifies the sufficient measures, facilities or practices to be employed during well site construction, drilling and operations. The variance, if granted, shall include terms and conditions the department requires to ensure the safety and protection of affected persons and property. The terms and conditions may include insurance, bonding and indemnification, as well as technical requirements. (b) No well pad may be prepared or well drilled within one hundred feet measured horizontally from any perennial stream, natural or artificial lake, pond or reservoir, or a wetland, or within three hundred feet of a naturally reproducing trout stream. No well pad may be located within one thousand feet of a surface or ground water intake of a public water supply. The distance from the public water supply as identified by the department shall be measured as follows: (1) For a surface water intake on a lake or reservoir, the distance shall be measured from the boundary of the lake or reservoir. (2) For a surface water intake on a flowing stream, the distance shall be measured from a semicircular radius extending upstream of the surface water intake. (3) For a groundwater source, the distance shall be measured from the wellhead or spring. The department may, in its discretion, waive these distance restrictions upon submission of a plan identifying sufficient measures, facilities or practices to be employed during well site construction, drilling and operations to protect the waters of the state. A waiver, if granted, shall impose any permit conditions as the secretary considers necessary. (c) Notwithstanding the foregoing provisions of this section, nothing contained in this section prevents an operator from conducting the activities permitted or authorized by a Clean Water Act Section 404 permit or other approval from the United States Army Corps of Engineers within any waters of the state or within the restricted areas referenced in this section. (d) The well location restrictions set forth in this section shall not apply to any well on a multiple well pad if at least one of the wells was permitted prior to the effective date of this article. (e) The secretary shall, by December 31, 2012, report to the Legislature on the noise, light, dust and volatile organic compounds generated by the drilling of horizontal wells as they relate to the well location restrictions regarding occupied dwelling structures pursuant to this section. Upon a finding, if any, by the secretary that the well location restrictions regarding occupied dwelling structures are inadequate or otherwise require alteration to address the items WW-6A (8-13) API NO. 47-OPERATOR WELL NO. 1206 N-1H to S-10H Well Pad Name: Antonio 1206

examined in the study required by this subsection, the secretary shall have the authority to propose for promulgation legislative rules establishing guidelines and procedures regarding reasonable levels of noise, light, dust and volatile organic compounds relating to drilling horizontal wells, including reasonable means of mitigating such factors, if necessary.

Water Well Testing:

Pursuant to West Virginia Code § 22-6A-10(d), notification shall be made, with respect to surface landowners identified in subsection (b) or water purveyors identified in subdivision (5), subsection (b) of this section, of the opportunity for testing their water well. The operator shall provide an analysis to such surface landowner or water purveyor at their request.

Water Testing Laboratories:

Pursuant to West Virginia Code § 22-6A-10(i), persons entitled to notice pursuant to subsection (b) of this section may contact the department to ascertain the names and locations of water testing laboratories in the subject area capable and qualified to test water supplies in accordance with standard accepted methods. In compiling that list of names the department shall consult with the state Bureau for Public Health and local health departments. A surface owner and water purveyor has an independent right to sample and analyze any water supply at his or her own expense. The laboratory utilized by the operator shall be approved by the agency as being certified and capable of performing sample analyses in accordance with this section.

Rebuttable Presumption for Contamination or Deprivation of a Fresh Water Source or Supply:

W. Va. Code § 22-6A-18 requires that (b) unless rebutted by one of the defenses established in subsection (c) of this section, in any action for contamination or deprivation of a fresh water source or supply within one thousand five hundred feet of the center of the well pad for horizontal well, there is a rebuttable presumption that the drilling and the oil or gas well or either was the proximate cause of the contamination or deprivation of the fresh water source or supply. (c) In order to rebut the presumption of liability established in subsection (b) of this section, the operator must prove by a preponderance of the evidence one of the following defenses: (1) The pollution existed prior to the drilling or alteration activity as determined by a predrilling or prealteration water well test. (2) The landowner or water purveyor refused to allow the operator access to the property to conduct a predrilling or prealteration water well test. (3) The water supply is not within one thousand five hundred feet of the well. (4) The pollution occurred more than six months after completion of drilling or alteration activities. (5) The pollution occurred as the result of some cause other than the drilling or alteration activity. (d) Any operator electing to preserve its defenses under subdivision (1), subsection (c) of this section shall retain the services of an independent certified laboratory to conduct the predrilling or prealteration water well test. A copy of the results of the test shall be submitted to the department and the surface owner or water purveyor in a manner prescribed by the secretary. (e) Any operator shall replace the water supply of an owner of interest in real property who obtains all or part of that owner's supply of water for domestic, agricultural, industrial or other legitimate use from an underground or surface source with a comparable water supply where the secretary determines that the water supply has been affected by contamination, diminution or interruption proximately caused by the oil or gas operation, unless waived in writing by that owner. (f) The secretary may order the operator conducting the oil or gas operation to: (1) Provide an emergency drinking water supply within twenty-four hours; (2) Provide temporary water supply within seventy-two hours; (3) Within thirty days begin activities to establish a permanent water supply or submit a proposal to the secretary outlining the measures and timetables to be used in establishing a permanent supply. The total time in providing a permanent water supply may not exceed two years. If the operator demonstrates that providing a permanent replacement water supply cannot be completed within two years, the secretary may extend the time frame on case-by-case basis; and (4) Pay all reasonable costs incurred by the real property owner in securing a water supply. (g) A person as described in subsection (b) of this section aggrieved under the provisions of subsections (b), (e) or (f) of this section may seek relief in court... (i) Notwithstanding the denial of the operator of responsibility for the damage to the real property owner's water supply or the status of any appeal on determination of liability for the damage to the real property owner's water supply, the operator may not discontinue providing the required water service until authorized to do so by the secretary or a court of competent jurisdiction.

Written Comment:

Pursuant to West Virginia Code § 22-6A-11(a), all persons described in subsection (b), section ten of this article may file written comments with the secretary as to the location or construction of the applicant's proposed well work within thirty days after the application is filed with the secretary. All persons described in West Virginia Code § 22-6A-10(b) may file written comments as to the location or construction of the applicant's proposed well work to the Secretary at:

Chief, Office of Oil and Gas Department of Environmental Protection 601 57th St. SE Charleston, WV 25304 (304) 926-0450

DEC 1 0 2020

WV Department of Environmental Protection

Such persons may request, at the time of submitting written comments, notice of the permit decision and a list of persons qualified to test water. NOTE: YOU ARE NOT REQUIRED TO FILE ANY COMMENT.

WW-6A (8-13) API NO. 47-_ OPERATOR WELL NO. 1206 N-1H to S-10H
Well Pad Name: Antonio 1206

Time Limits and Methods for Filing Comments.

The law requires these materials to be served on or before the date the operator files its Application. You have THIRTY (30) DAYS after the filing date to file your comments. Comments must be filed in person or received in the mail by the Chief's office by the time stated above. You may call the Chief's office to be sure of the date. Check with your postmaster to ensure adequate delivery time or to arrange special expedited handling. If you have been contacted by the well operator and you have signed a "voluntary statement of no objection" to the planned work described in these materials, then the permit may be issued at any time.

Pursuant to West Virginia Code § 22-6A-11(c)(2), Any objections of the affected coal operators and coal seam owners and lessees shall be addressed through the processes and procedures that exist under sections fifteen, seventeen and forty, article six of this chapter, as applicable and as incorporated into this article by section five of this article. The written comments filed by the parties entitled to notice under subdivisions (1), (2), (4), (5) and (6), subsection (b), section ten of this article shall be considered by the secretary in the permit issuance process, but the parties are not entitled to participate in the processes and proceedings that exist under sections fifteen, seventeen or forty, article six of this chapter, as applicable and as incorporated into this article by section five of this article.

Comment Requirements

Your comments must be in writing and include your name, address and telephone number, the well operator's name and well number and the approximate location of the proposed well site including district and county from the application. You may add other documents, such as sketches, maps or photographs to support your comments.

Disclaimer: All comments received will be placed on our web site http://www.dep.wv.gov/oil-and-gas/Horizontal-Permits/Pages/default.aspx and the applicant will automatically be forwarded an email notice that such comments have been submitted. The applicant will be expected to provide a response to comments submitted by any surface owner, water purveyor or natural gas storage operator noticed within the application.

Permit Denial or Condition

The Chief has the power to deny or condition a well work permit. Pursuant to West Virginia Code § 22-6A-8(d), the permit may not be issued or be conditioned, including conditions with respect to the location of the well and access roads prior to issuance if the director determines that:

- (1) The proposed well work will constitute a hazard to the safety of persons;
- (2) The plan for soil erosion and sediment control is not adequate or effective;
- (3) Damage would occur to publicly owned lands or resources; or
- (4) The proposed well work fails to protect fresh water sources or supplies.

A permit may also be denied under West Virginia Code § 22-6A-7(k), the secretary shall deny the issuance of a permit if the secretary determines that the applicant has committed a substantial violation of a previously issued permit for a horizontal well, including the applicable erosion and sediment control plan associated with the previously issued permit, or a substantial violation of one or more of the rules promulgated under this article, and in each instance has failed to abate or seek review of the violation within the time prescribed by the secretary pursuant to the provisions of subdivisions (1) and (2), subsection (a), section five of this article and the rules promulgated hereunder, which time may not be unreasonable.

Pursuant to West Virginia Code § 22-6A-10(g), any person entitled to submit written comments to the secretary pursuant to subsection (a), section eleven of this article, shall also be entitled to receive from the secretary a copy of the permit as issued or a copy of the order modifying or denying the permit if the person requests receipt of them as a part of the written comments submitted concerning the permit application. Such persons may request, at the time of submitting written comments, notice of the permit decision and a list of persons qualified to test water.

RECEIVED Office of Oil and Gas

DEC 1 0 2020

WW-6A (8-13)

Email:

API NO. 47-OPERATOR WELL NO. 1206 N-1H to S-10H Well Pad Name: Antonio 1206

Notice is hereby given by:

Well Operator: HG Energy II Appalachia, LLC

Telephone: 30

304-420-1119 dwhite@hgenergyllc.com

Diane White

Address: 5260 Dupont Road

Parkersburg, WV 26101

Facsimile: 304-863-3172

Oil and Gas Privacy Notice:

The Office of Oil and Gas processes your personal information, such as name, address and telephone number, as part of our regulatory duties. Your personal information may be disclosed to other State agencies or third parties in the normal course of business or as needed to comply with statutory or regulatory requirements, including Freedom of Information Act requests. Our office will appropriately secure your personal information. If you have any questions about our use or your personal information, please contact DEP's Chief Privacy Officer at depprivacyofficer@wv.gov.



Subscribed and sworn before me this 5th day of December, 2020

Cass A. Boesdon Notary Public

My Commission Expires 7 31 2022

RECEIVED Office of Oil and Gas

DEC 1 0 2020

WW 6A 1206 NIH - SIOH MOD Certified Notice Receipts

	INTERNATION DISCOURSE DESCRIPTION OF THE PROPERTY OF THE PROPE	
	IIS Poetal Sandoo	
	U.S. Postal Service™ CERTIFIED MAIL® RE	
	CERTIFIED WATER	CEIPT
1	Domestic Mail Only	
7		
T.A.	For delivery information, visit our webs	ite at www.usps.com*.
4		
D	Certified Mail Fee	
T. J. A. T.	Ostoned Main Lea	
11	Fixtra Services & Fees (check box, add fee as epproprise	SOWV SI
	Results Receibt Transfersion S	A. R.C.
FINDE	I Return Receipt (electronic) 5 / C	Postmark
Ξ	Curtilled Mail Restricted Salivary \$ //S	-i Hore
=	Adult Signaturo Required S S	- 200
	Adult Statisture Restricted Delivery \$	- 7
	Postage 2	0,
TAL	5	- WIH- SIPH
TL	Total Postage and Fees	1.14
	3	1500 EM WOD
II	Sent TO Antonio PLLC C/6	Mike Ross
701	Street and Apt. No., or PO Box No.	11110 11093
T	PO Box 219	
	City, State, 219+40 This WY 7	4257
	PS Form 3800, April 2015 Palitago re-copaga:	See Reverse for instructions
0000 1287 1693	U.S. Postal Service" GERTIFIED MAIL® REC Domestic Mail Only For delivery information, visit out websit Certified Mail Fee S Extra Services & Fees (check car, edd for as socretary) Serum Recent functopy) Serum Recent functopy Serum Recent functopy Serum Recent functopy Serum Recent functory Services & Fees (check car, edd for as socretary) Serum Recent functory Services & Fees (check car, edd for as socretary) Services & Fees (check car, edd for as socretary) Services & Fees (check car, edd for as socretary) Services & Fees (check car, edd for as socretary) Services & Fees (check car, edd for as socretary) Services & Fees (check car, edd for as socretary) Services & Fees (check car, edd for as socretary) Services & Fees (check car, edd for as socretary)	
	Adult Signature Regulfod S S Andult Bignature Restricted Delivery S Postage	107.00
2280	3	De
TI.	Total Postage and Fees	NIH- 510H
	s	1206 FW MOD.
7019	Sont To	
T	Charles R Sutton	
7	593 Long Run Road	
4		
	LOST Creek WV 2	6385
	PS Ferm 3800, April 2015 PSN 7630-02-000-9647	See Reverse for instructions



HG Energy, LLC 5260 Dupont Road Parkersburg, WV 26101 (304) 420-1100 - Office (304) 863-3172 - Fax

November 13, 2020

Mr. Wade Stansberry WVDEP Division of Oil & Gas 601 57th Street Charleston, West Virginia 25304

RE:

Antonio 1206 N-1H thru S-10H (47-033-05978,79,80,81,82,83,84,85,86,87))

Modification Request to Extend Surface Casing 75' to Cover an Additional Seam of Coal

Grant District, Harrison County, West Virginia

Dear Mr. Stansberry:

Per discussions with Sam Ward and Taylor Brewer, enclosed are revised WW-6B's and casing schematics for the ten permitted laterals on the Antonio 1206 well pad. We request the drill permits be modified to extend the surface casing from 1100' to 1175' to cover an additional seam of coal which was encountered during the drilling process.

Please let me know if you have any questions or require additional information. I can be reached at (304) 420-1119 or dwhite@hgenergyllc.com.

Very truly yours,

Diane White

Office of Oil and Gas

NOV 16 2020

WV Department of Environmental Protection

Diane C. White

Enclosures

cc: Sam Ward - DEP Inspector

Diane White

From:

Josh Hinton

Sent:

Friday, November 13, 2020 8:07 AM

To:

Diane White

Cc:

Dale Fidurko; Lori Barr

Subject:

RE: Permit modification

We will need to make this change to the other (9) wells on this pad. This is Surface Casing/Fresh Water Protection string.

So make TD/Hole Depth 1175' and Casing Shoe Set depth 1145'

From: hgtopholerig1@gmail.com <hgtopholerig1@gmail.com>

Sent: Friday, November 13, 2020 8:04 AM

To: Dale Fidurko <dfidurko@hgenergyllc.com>; Chip Queen <queenserviceswv@gmail.com>; Josh Hinton <jhinton@hgenergyllc.com>; Lori Barr <lbarr@hgenergyllc.com>; Diane White <dwhite@hgenergyllc.com>

Subject: Permit modification

Antonio 1206 N1 H and pad modification TD hole depth 1174', New casing shoe depth 1144', Last coal seam encounter 1126' to 1130' Reason for modification was the coal seam depth Chip has talk to Sam Ward about this modification Thanks Mike

RECEIVED
Office of Oil and Gas

NOV 1 6 2020