

LATITUDE 39°20'00"

LONGITUDE 80°20'00"

0.290
1.182
+

7'5 OGIS topo location

7.5' loc _____ 15' loc _____
_____ (calc.) _____

Company Commercial Coal & Coke

Farm R.J. Louder Estate #1

Quad Clarksburg 7'1/2

County Harrison

District Coal

WELL LOCATION MAP

File No. 033 - 30193

Plat of the proposed abandonment of Well #1 of the Commercial Coal and Coke Co of Clarksburg W Va on the Nathan Goff Farm consisting of 100 Acres Located in Coal District, Harrison County



I, the undersigned, hereby certify that this Map is correct and shows all the information to the best of my knowledge and belief, required by the oil and gas section of the Mining Law of West Virginia.

U. G. W.
Engineer

Acknowledged before me a Notary Public
this 26th day of April 1934

Fred C. Harper

My commission expires Aug 6 - 1943

HAR - 193-A

PRELIMINARY DATA SHEET NO. 1

File No.

Well No. 1

Commercial Coal and Coke Company, of Clarksburg, W. Va.

on the R. J. Loundes Estate, Farm

containing One Hundred acres. Location

West Fork River

Coal District, in Harrison County, West Virginia

The surface of the above tract is owned in fee by R. J. Loundes Estate.

of Clarksburg, W. Va. address, and the mineral rights are owned by

Commercial Coal and Coke Co. of Clarksburg, W. Va.

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit

No. No permit issued at time issued by the West Virginia Department of Mines, Oil and Gas Division

Well was drilled Sept. 1911. 193

Elevation of surface at top of well, 79 - gut Spirit Barometric

The number of feet of the different sized casings used in the well.

16 feet 16 inches size. Wood conductor.

130 feet 10 inch size, csg. 880 feet 8 1/4 inch sized csg.

1412 feet 6 5/8 size, csg. 2244 feet 5 - 3/16 sized csg.

feet size, csg. feet sized csg.

packer of 6 5/8 size, set at 1407

packer of 5 - 3/16 size, set at 2205

in casing perforated at feet to feet

in casing perforated at feet to feet

Coal was encountered at Well is below the coal. feet; thickness inches, and at

feet; thickness inches; and at feet; thickness inches

Linens were used as follows: (Give details) No Liners

April 20 1927

Date

Approved The Commercial Coal & Coke Co. Owner.

By

Joseph H. ... Secretary

Name	Color	Character	Oil, Gas or Water	Top	Bottom	Thickness	Total Depth	Remarks
Red Rock				15 feet				
Slate								
Lime								
Red Rock					20			
Slate								
Lime								
Red Rock								
Slate								
Sand				550	605	55		
Dirty lime								
Slate								2862
Lime								
Red Rock								
Lime								
Red Rock								
Slate				1388	1472	89		
Big engine sand								
Red Rock								
Lime & slate								
Thirty feet sand								
Slate shells								
Sand shells								
Fourth sand								
Lime shells								
Slate shells								
5th sand								
Gas from 2341 to 2349								
							2368	

shot
Well was not shot at 2245 feet; well was shot at _____ feet.

Salt
Fresh water at no water feet; fresh water at _____ feet.

producing
Well was _____ hole.

The Commercial Coal & Coke Company

April 20 1894
Date

Approved

Owner

Secretary

NOTE. All bottom formations must be noted as indicated above and all key rock and oil and gas sands must be recorded under their proper geological names in the district as well as any local names commonly used in the district for such strata.

WORK ORDER

Well to be plugged and filled as follows:

WORK TO BE SUPPLIED BY THE CONTRACTOR OR OTHER:

Bottom of Well 236'
 Fill hole with red clay from bottom 236' to 2257'
 Drive wood plug 2257' to 2254'
 Cement 2254' to 2244' sealing hole completely
 PULL 5 3/16" casing set at 2244'
 Fill with red clay from 2244' to 1943' - 20' above the 30-Foot Sand.
 Drive wood plug 1943' to 1940'
 Cement from 1940' to 1930' sealing the 30-Foot Sand.
 SET A PERMANENT BRIDGE at 1902' - 30' below the Big Injun Sand.
 Fill with red clay from 1902' to 1422'
 Drive wood plug 1422' to 1419'
 Cement from 1419' to 1412'
 PULL 8 1/4" casing set at 1412'
 Fill the hole with red clay from 1412' to 1363' - 20' above the
 Big Injun Sand.
 Drive wood plug 1363' to 1360'
 Cement from 1360' to 1350' Sealing the Big Injun Sand.

SET A PERMANENT BRIDGE at 900'
 Fill with red clay from 900' to 880'
 PULL 8 1/4" casing set at 880'
 Continue to fill with red clay from 880' to 530' - 20' above
 the Gritty Lime.
 Drive wood plug 530' to 527'
 Cement from 527' to 517'

SET A PERMANENT BRIDGE at 140'
 Fill hole with red clay from 140' to 130'
 PULL 10" casing and continue to fill with red clay to 19'
 Drive a wood plug 19' to 16' and fill to surface with red clay
 ERECT A MARKER such as is described in Rule 18, 1931 Regulations.
 All be done in workman-like manner

To the Department of Mines,
 Coal Owner or Operator,
 Lease or Property Owner.

Gentlemen:

This "work order" is submitted for your approval and concurrence and unless notified of your disapproval or non-concurrence, the undersigned will proceed with the plugging and filling of said well in the above described manner on the date stated in the notice of intention to plug and abandon the said well on opposite side of this sheet.

Very truly yours,

Well Operator.

No objections have been filed by the coal owner or coal operator, or any available adjacent lease or property owners or interposed by the Department of Mines to the manner herein described for the plugging and filling of the well above mentioned. Therefore, the same is hereby approved this 24th day

of April 1934

NOTICE OF INTENTION TO PLUG AND ABANDON WELL

(REQUIRED BY SECTION 8, ARTICLE 4, CHAPTER 22 OF THE CODE)

WEST VIRGINIA DEPARTMENT OF MINES
OIL AND GAS DIVISION

TO THE DEPARTMENT OF MINES,
Charleston, W. Va.

COAL OPERATOR OR COAL OWNER

ADDRESS

COAL OPERATOR OR COAL OWNER

ADDRESS

LEASE OR PROPERTY OWNER

ADDRESS

Plot shown
R. J. Lowndes Estate
NAME OF WELL OPERATOR

COMPLETE ADDRESS

April 25th 1924
WELL TO BE ABANDONED

District

County

Well No.

Farm

R. J. Lowndes Estate

Clarksburg, W. Va.

Coal

Harrison

one

R. J. Lowndes Estate

Gentlemen:—

The undersigned well operator is about to abandon the above described well and will commence the

work of plugging and abandoning said well on the 25 day of April, 1924, (which date shall not be less than five days after the day on which this notice so mailed is received, or in due course should be received by the Department of Mines).

This notice is given you in order that your respective representatives may be present at the plugging and filling of said well. You are further notified that whether you are represented or not represented the undersigned will proceed on that date, or shortly thereafter, to plug and fill said well in the manner required by Section 10, Article 4, Chapter 22 of the Code and given in detail on the reverse side of this notice, in "Work Order."

This notice is being mailed by registered mail to each of you at the above addresses on the above date.

Very truly yours,

The Lowndes Savings Bank & Trust Co.
Trustee.

Joseph Dubois
Well Operator, Trustee.

NOTE: Upon the abandonment of all wells drilled prior to June 1, 1922, a plat prepared by a competent engineer, showing the district and county in which the tract of land is located, the name and acreage of same, the names of the owners of adjacent tracts, and the location of the about to be abandoned well, determined by survey, and the courses and distances of such well from two permanent points or landmarks on said tract, shall be submitted with this notice.