

1352

Sardis District, Harrison County, W. Va. 202A
 By Pittsburgh & W. Va. Gas Co., Clarksburg, W. Va.
 On 50 acres, surface and mineral rights owned by L. S. Smith,
 R. F. D. No. 2, Wallace, W. Va.
 Well completed July 14, 1911.
 Elevation, 1001' L.
 13" conductor, 11'; 10" casing, 250'; 8 $\frac{1}{4}$ ", 872'; 6-5/8", 1646'.
 Coal was encountered at 318-324 and 350-356'.
 Well located 4-11-1911; began drg. 5-9-1911; completed drg. 7-14-1911.
 Abandonment reported to Dept. of Mines June 26, 1934.
 Well was shot at 2269' in 50-Ft. Sand, with 30 qts.
 Fresh water at 780'.
 6-5/8" hole.

	Top.	Bottom.	Thickness.
Unrecorded	0	- 39	39
Lime, white, hard	39	- 50	11
Lime, white, broken	50	- 160	110
Lime, white, hard	160	- 250	90
Slate, white, hard	250	- 318	68
Mapletown (Redstone) Coal, black, soft	318	- 324	6
Lime, white, hard	324	- 350	26
Pittsburgh Coal, black, soft	350	- 356	6
Red rock, soft	356	- 400	44
Slate and shells, white, broken	400	- 675	275
Lime, white, hard	675	- 765	90
Little Dunkard Sand, gray, hard (water, 780')	765	- 837	72
Slate, dark, soft	837	- 842	5
Big Dunkard Sand, gray, hard	842	- 920	78
Slate, dark, soft	920	- 1100	180
1st Salt Sand, dark, hard (gas, 1115')	1100	- 1130	30
Slate, dark, soft	1130	- 1206	76
2nd Salt Sand, gray, hard	1206	- 1290	84
Slate, dark, soft	1290	- 1300	10
Sand, white, soft	1300	- 1410	110
Slate, white, soft	1410	- 1440	30
Maxton Sand, mmh hard	1440	- 1530	90
Slate, red, soft	1530	- 1590	60
Little Lime, hard	1590	- 1600	10
Slate, black, soft	1600	- 1640	40
Big Lime, hard	1640	- 1690	50
Big Injun Sand, white, hard	1690	- 1800	110
Slate, black, soft	1800	- 2260	460
Fifty-foot Sand, white, open (gas, 2260')	2260	- 2287	27
Slate, soft	2287	- 2295	8
Unrecorded	2295	- 2398	103
Gordon Sand	2398	- 2428	30
Unrecorded	2428	- 2433	5
4th Sand (oil, 2460')	2433	- 2508	75
Unrecorded, to bottom	2508	- 2753	245