

MARSHALL MARTIN NO. 231 WELL.

No. 205 O.F.-Harrison.

2180

Clark District, Harrison County, W. Va.

By Wright Bros., Clarksburg, W. Va. (H. A. Wright, Mgr.)

On 96 acres, surface owned by Overt Cork and Dodd, Clarksburg, W. Va.

Elevation, 1117' L.

16' conductor; 10" casing, 185'; 8 $\frac{1}{2}$ "¹, 850'; 6-5/8", 1484':

B. H. Packer, 6-5/8 x 8 $\frac{1}{2}$ ", set at 1484'.

Starts below coal (Pittsburgh).

Abandonment reported to Dept. of Mines Dec. 26, 1934.

Well was shot at 2248-2260'.

Oil well.

	Top.	Bottom.
Little Dunkard Sand	390	- 410
Salt Sand	785	- 950
Big Injun Sand	1480	- 1585
50-Ft. Sand	1958	- 1980
Gordon Stray Sand	2112	- 2140
Gordon Sand (oil, 2254-2260')	2247	- 2269
Total depth		2269

L. B. Barnett



HAR-217-A

LEGEND

- Location
- Oil Well
- ⊙ Aband
- ⊛ Gas Well
- ⊙ Aband
- ⊕ Dry Hole

Field Book No. 511P18

Scale 1" = 500'

C-229 - March 3 1933
C-229 - June 14 1933

ENGINEER'S CERTIFICATE

I, the undersigned, hereby certify that this map is correct and shows all the information to the best of my knowledge and belief, required by the oil and gas section of the mining laws of West Virginia.

W. H. ...
ENGINEER

Acknowledged before me a Notary Public in and for the County of Harrison and State of West Virginia
this ... day of ... 19...

File No. /

WRIGHT BROTHERS

Company of CLARKSBURG, W. VA.

on the MARSHALL MARTIN

Farm

containing 96 acres. Location

CLARKSBURG

District, in HARRISON

County, West Virginia

The surface of the above tract owned in fee by OVERT COOK AND DODD

CLARKSBURG, W. VA.

address, and the mineral rights are owned by

NONE

of NONE

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit

No. issued by the West Virginia Department of Mines, Oil and Gas Division

193

Elevation of surface at top of well, 1,117

Spirit Barometric

The number of feet of the different sized casings used in the well.

		feet	16	size.	Wood conductor.
185	feet	10"	size, csg.	feet	sized csg.
850	feet	8 1/2"	size, csg.	feet	sized csg.
1484	feet	6 5/8"	size, csg.	feet	sized csg.
B. H		packer of	6 5/8" x 8 1/2"	size, set at	1484

packer of _____ size, set at _____

casing perforated at _____ feet to _____ feet.

casing perforated at _____ feet to _____ feet.

Coal was encountered at _____ feet; thickness _____ inches, and at _____

feet; thickness _____ inches; and at _____ feet; thickness _____ inches.

Liners were used as follows (Give details) _____

DECEMBER 24, 1934

Date.

Approved WRIGHT BROTHERS Owners.

By H. F. Wright, mgr.

Name	Color	Character	Oil, Gas or Water	Top	Bottom	Thickness	Total Depth	Remarks
LITTLE DUNKARK		SAND		390	410			190 - 20'
SALT SAND				785	950			200 - 250'
BIG INGUN		SAND		1480	1585			1480 - 6 1/2'
FIFTY FOOT		SAND		1958	1980			
GORDON STRAY		SAND		2112	2140			
GORDON		SAND		2247	2269		2269	
			2254					
			2260					
								BELOW THE PGH - COAL

shot
Well was not shot at feet; well was shot at 2248 - 2260 feet.

Salt
Fresh water at feet; salt
fresh water at feet.

producing
Well was oil hole.
dry

DECEMBER 26, 1924

Date

Approved WRIGHT BROTHERS

Owner

H. H. Wright

NOTE: All bottom formations must be noted as indicated above and all key-rocks and oil and gas sands must be recorded under their proper geological names in the district as well as any local names commonly used in the district for such strata.