



- New Lease
- Drill Done
- Abandoned

Company Lillian Moses

Address 2 W Main St. Salem, W. Va.

Farm W. Hartley

Treaty Area 90 Lease No. _____

STATE WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION
CLEVELAND

STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION

WELL RECORD

Oil or Gas Well *Oil*

Permit No.

Company *Welford Mines*
 Address *W. L. Hatcher*
 Farm *Acres 40*
 Location (waters)
 Well No. *one* Elev. *1237*
 District *Clay* County *Harrison*
 The surface of tract is owned in fee by *John P. Hatcher*
Natural Gas Address *For Bushy Mt.*
 Mineral rights are owned by *Frank M. Manning Co.*
Box 96 Address *Elkton, W. Va.*
 Drilling commenced *11-9-1910*
 Drilling completed *12-27-1910*
 Date Shot From To
 With
 Open Flow */10ths Water in* Inch
/10ths Merc. in Inch
 Volume Cu. Ft.
 Rock Pressure lbs. hrs.
 Oil bbls., last 24 hrs.
 Fresh water feet feet
 Salt water feet feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer
16			
13			Size of
10		<i>250</i>	
8 1/2		<i>1250</i>	Depth set
6 1/2		<i>1657</i>	
5 3/16		<i>1778</i>	
3			Perf. top
2			Perf. bottom
Liners Used			Perf. top
			Perf. bottom

CASING CEMENTED	SIZE	No. Ft.	Date
COAL WAS ENCOUNTERED AT <i>205</i> FEET INCHES			

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
<i>Bitum Coal</i>			<i>205</i>	<i>212</i>			
<i>L. Sand</i>			<i>780</i>	<i>880</i>			
<i>Gas Sand</i>			<i>980</i>	<i>1085</i>			
<i>Salt Sand</i>			<i>1134</i>	<i>1294</i>			
<i>S. Limestone</i>			<i>1610</i>	<i>1630</i>			
<i>B. Limestone</i>			<i>1640</i>	<i>1706</i>			
<i>B. Sandstone</i>			<i>1706</i>	<i>1840</i>			
<i>Fifty feet</i>			<i>2220</i>	<i>2292</i>			
<i>Total depth</i>				<i>2292</i>			

STATE OF WEST VIRGINIA
DEPARTMENT OF MINE
OIL AND GAS DIVISION

AFFIDAVIT OF PLUGGING AND FILING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE. ONE COPY SHALL BE TO THE TENDENT, ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY, AND EXTRA COPIES IF REQUIRED, SHOULD BE MAILED TO THE COAL OPERATOR AT THEIR RESPECTIVE OFFICES.

Coal Operator of Owner

Address

Coal Operator of Owner

Address

Lease or Property Owner

Address

Well Operator

Complete Address

Well and Location

1947

District

County

Well No.

Locality

Farm

STATE INSPECTOR SUPERVISING PLUGGING

AFFIDAVIT

STATE OF WEST VIRGINIA,

County of Harrison

ss.

being first duly sworn according to law depose and say that three experienced in the work of plugging and filling oil and gas wells and were employed by [Name] well operator, and participated in the work of plugging and filling above well, that said work was commenced on the 9th day of June, 1947 and that the well was plugged and filled in the following manner:

BAND OR BONE RECORD	FILLING MATERIAL			FEET USED	CASING	
	FOUNDRY	CONTENT	FEET		FEET FULLER	FEET LEFT IN
		Slag	100'	100'		
		Cement	100'	100'		
				100'	100'	100'
					100'	100'
		Unable to fill casing due to the casing 6-5/8" and 8" casing being worn and holes could not get through casing. After this being done, all the following was agreed upon.				
		Cement plug drove in top of casing at 138'				
		Cement plug drove in top of casing at 138'				
		10" casing left in well.				
		From the start there was no more of it.				
COAL SEAMS	DESCRIPTION OF MONUMENT					
(NAME)	Survey conducted according to					
(NAME)	[unclear]					
(NAME)						
(NAME)						

and that the work of plugging and filling said well was completed on the 11 day of June, 1947.

STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION

INSPECTOR'S PLUGGING REPORT

Permit No. *New 32*

Well No. *1*

COMPANY *William Mason*

ADDRESS *Seaman, W. Va.*

LABORER *W. Hartley*

DISTRICT *Clay*

COUNTY *Marion*

Filling Material *Coal*

PLUGS USED AND DEPTH PLACED			BRIDGES	CASING AND TUBING		
CEMENT THICKNESS	WOOD SIZE	LEAD	CONSTRUCTION/LOCATION	RECOVERED	SIZE	LOST
				150	6 1/2"	150'
				138	8"	111'
					12	250'

JUN 1911

Drillers' Names *Alb. Beebe, J. Robinson*

Remarks: *This is the well where the 6 1/2" & 8" casing collapsed due to hole slid from mine casing. Cement to follow No. 1 last plug was placed at 1665'. Unable to set bridge at 1300' or 300'. But down wood plug in top of 8" casing and used 17 bags of cement in 10' casing filled from 138' to 100' and left down hole. Some of cement went in around the 8" casing. At 100' to 100' on well near 16/22 - B. F. Mason*