

## C. S. DESPARD NO. 1 WELL.

```
Tenmile District, Harrison County, W. Va.

By A. M. Snider, Waynesburg, Pa.

Abandoned under permit Har-1487-A.

On 88-3/5 acres, on branch of Grass Run.

Elevation, 1162.28 L. (D. F.); 1160.60 L. (ground).

Drilling commenced June 23, 1921.

Shot Sept. 9, 1921, at 2991-2993', with 40 qts.

10" casing, 366' (pulled); 8½", 1626' (pulled); 6½", 2393'; 5½", 3100';

2" tubing, 2885'. Liner used, above packer, 141 joints.

5½" run-1941 to jts. below 6½" on hook wall packer. A lead plug was placed in Despard well No. 1, in the Fifty-foot Sand, between the oil pay and the gas pays, to separate the oil from the gas. Top of plug, 3016' 4".

Gas well. Record to Dept. of Mines stamped Sept. 17, 1951.

Record to RCT from Dept. of Mines (Lineberg) Mar. 12, 1952. O.F.No.1333.
```

	Top.	Bettom.
Native coal	_	- 597
Coal		<b>-</b> 678
Bluff Sand	740	- 795
Coal		- 860
Pittsburgh Coal	1134	- 1141
Murphy Sand	1480	- 1493
Little Dunkard Sand	1560	- 1590
Big Dunkard Sand	1624	- 1644
1st Gas Sand		- 1750
2nd Gas Sand		<b>-</b> 1858
1st Salt Sand		- 1891
2nd Salt Sand (water, 1921')		- 1935
3rd Salt Sand		<b>-</b> 20 <b>60</b>
Maxton Sand		- 2340
Little Lime, broken		<b>-</b> 2367
Pencil Cave	2379	- 2431
Big Injun Sand (gas, 24771; 2nd gas,		
2 <b>497*)</b>		- 2529
Squaw Sand		<b>-</b> 2682
Berea Grit	2881	<b>-</b> 29 <b>05</b>
(hard rock to set packer in,		
2881-2888')		
Fifty-foot Sand (1st show of gas,		
2991-2993'; 2nd show of gas,		
best pay, 2997-3000; 3rd show		
of gas, small, 3008-3012; show		
of eil, 3020')		- 3020
Thirty-foot Sand		- 3117½
Gordon Stray Sand		- 3191 2027
Gordon Sand	3212	- 3237 20191
Total depth		3248 <del>1</del>