





STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION

033-31578

WELL RECORD

Permit No.

Oil or Gas Well

Company **Crawford and Company**

Address **F. O. Box 182 - Spring Hill, W. Va.**

Owner **Victor S. Martin** Acres **1/43**

Location (waters): \_\_\_\_\_

Well No. **1** Elev. **933'**

District **Clay** County **Harrison**

The surface of tract is owned in fee by \_\_\_\_\_

Address \_\_\_\_\_

Mineral rights are owned by \_\_\_\_\_

Address \_\_\_\_\_

Drilling commenced \_\_\_\_\_

Drilling completed \_\_\_\_\_

Date Shut In From \_\_\_\_\_ To \_\_\_\_\_

With \_\_\_\_\_

Open Flow 100% Water in \_\_\_\_\_ Inch

100% Mem. in \_\_\_\_\_ Inch

Volume \_\_\_\_\_ Cu. Ft.

Back Pressure \_\_\_\_\_ lbs. \_\_\_\_\_ hrs.

Oil \_\_\_\_\_ feet \_\_\_\_\_ inch

Fresh water \_\_\_\_\_ feet \_\_\_\_\_ inch

Salt water \_\_\_\_\_ feet \_\_\_\_\_ inch

Casing and Tubing	Used in Drilling	Left in Well	Parkers
18			Kind of Parker
18			Size of
8 1/2	1800'	1800'	Depth av.
4 1/2	1800'	1800'	Perf. top
2	2430'	2400'	Perf. bottom
2			Perf. top
			Perf. bottom

Liners Used \_\_\_\_\_

CASING CEMENTED	SIZE	No. Ft.	DATA
COAL WAS ENCOUNTERED AT		FEET	INCHES
	FEET	INCHES	FEET
	FEET	INCHES	FEET
	FEET	INCHES	FEET

Formation	Color	Hard or Soft	Top	Bottom	Oil Gas or Water	Depth Found	Remarks
NO ACTUAL RECORD OF THIS WELL - FIRM NOTED THE AND APT IN CHECKING RECORD OF JAMES F. MCINTYRE WELL NO. 1 - 1000' DEEP AT THIS LOCATION, IT IS IN A FIFTY YARD WELL - approximately, 2685' deep							

STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
AND REVENUE DIVISION

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLI-CATE. ONE COPY TO BE FILED WITH THE DEPARTMENT OF MINES AND REVENUE, STATE OF WEST VIRGINIA, CHARLESTON, WEST VIRGINIA. THE OTHER TWO COPIES TO BE FILED WITH THE COUNTY CLERK OF THE COUNTY WHERE THE WELL IS LOCATED.

I, John H. ... of the County of Jefferson State of West Virginia  
do hereby certify that the above described well is a gas well and was plugged and filled in the following manner:  
1 1/2" of 10" casing  
The well is located at ...  
The well is located in ... County, State of West Virginia.  
The well is located on ... Farm.

STATE INSPECTOR OF SUPERVISION, DEPT. OF MINES AND REVENUE

AFFIDAVIT

STATE OF WEST VIRGINIA

County of Jefferson

Arthur ... and ...

being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling of and gas wells and were employed by ... well operators and participated in the work of plugging and filling the above well and said work was commenced on the ... day of MARCH ... and that the well was plugged and filled in the following manner:

BAND OR ZONE REMOVED	FILLING MATERIAL		PLUG USED	CASING
	DEPTH	THICKNESS		
REMOVED	10' to 110'	Best stone bracke on top of casing	100' 10"	10"
Best cement from 1000' to 1100'	Crushed stone 1000' - 1070'			
Filled with clay to 1100'	Best cement 1100' - 1140'			
Crushed stone 1140' - 1200'	Sealing hole below 1-1/2" casing			
5-1/2" casing below not put				
Hit 6" casing at 1200' and set 6" casing at top of 1200' to 1270'				
Removed 6" casing and filled with best cement to 1270'				
Best cement 1270' - 1340'	Crushed stone 1270' - 1320'			
6" casing in well hole 1320' and that cemented in well could not be set a permanent bracke at 1320'				
Best cement 1320' - 1380'	Crushed stone 1320' - 1380'			
Sealed with clay 1380' - 1400'	Best cement 1380' - 1400'			
Crushed stone 1400' - 1470'	Sealing hole at bottom hole			
Set a permanent bracke at 1470'	Best cement 1470' - 1500'			
Crushed stone 1500' - 1570'	Best cement 1500' - 1570'			