

Simpson District, Harrison County, W. Va. 70064  
 By The Manufacturers Light & Heat Co. (Tri-State Gas Co.)  
 Starts 60' below Harlem Coal. (52', in Romines Mill Section,  
 page 126, D&H Rept.)

Elev. 1015' B

	Top.	Bottom.	Thickness.
Little Dunkard Sand	140	- 180	40
Big Dunkard Sand	230	- 280	50
Coal	310	- 314	4
Salt Sand (2 bailers water per hour)	440	- 490	50
2nd Salt Sand (little gas and show of oil at 520')	520	- 680	160
3rd Salt Sand	700	- 840	140
Red rock	840	- 900	60
Maxton Sand	900	- 985	85
Red rock	985	- 1100	115
Little Lime	1100	- 1118	18
Big Lime	1135	- 1225	90
Big Injun Sand (little gas on top)	1225	- 1320	95
Squaw Sand	1360	- 1390	30
Gantz Sand	1575	- 1725	150
Stray Sand	1937	- 1964	27
Gordon Sand	1975	- 2000	25
4th Sand	2065	- 2085	20
Slate and shells (No 5th Sand)	2085	- 2930	845
A sand shell, about one foot thick.	2930	- 2931	1
Slate and shells, lime, to bottom	2931	- 3290	359

.....District, Harrison County, W. Va.

Authority, A. H. Davisson, Route 2, Lost Creek, W. Va.

	Top.	Bottom.	Thickness.
Little Dunkard Sand	140	- 180	40
Big Dunkard Sand	230	- 280	50
Coal	310	- 314	4
Coal	360	- 363	3
Gas Sand	370	- 435	65
Coal	435	- 440	5
First Salt Sand (oil and gas, 585')	440	- 490	50
Second Salt Sand	520	- 680	160
Third Salt Sand	700	- 840	140
Red rock	840	- 900	60
Maxton Sand	900	- 985	85
Red rock			
Little Lime	1100	- 1118	18
Big Lime	1135	- 1225	90
Big Injun Sand (gas)	1225	- 1320	95
Squaw Sand	1360	- 1390	30
Gantz Sand	1575	- 1725	150
<del>Remains in section</del>	<del>1975</del>	<del>- 2000</del>	<del>25</del>
Stray Sand	1937	- 1964	27
Gordon Sand	1975	- 2000	25
4th Sand	2065	- 2085	20
5th Sand	2160	- 2175	15
Slate and shells			
Total depth			3290